




TEM



touching completeness





TEM

Dobrodošli v družini MODUL

Welcome to the MODUL family


Za vas dopolnjujemo in izpopolnjujemo
sodobno družino stikal Modul za vse vrste vaših prostorov.

We are expanding and perfecting the modern
Modul switch family for all types of rooms.

discovering new insights
odkrivamo nove poglede




MODUL



Obliskovne linije Pure, Line in Soft so odraz sodobnega, prefinjenega in individualnega življenjskega stila. Iz široke in bogate palete barv, vzorcev in oblik lahko svoja stikala in vtičnice kadarkoli preprosto prilagodite želenemu ambientu in razpoloženju.

The Pure, Line and Soft design lines reflect a modern, sophisticated and independent lifestyle. You can choose from a wide and rich selection of colours, patterns and shapes to alter the appearance of your switches and sockets so that they fit the desired atmosphere and mood.



line



soft



ravne linije
straight lines



mehke linije
soft lines



PURE



čudovito bivanje wonderful living

Iz čistih, neomadeževanih podob na novo rojenega sveta je vzklila zgodba Pure. Dotik naravnih motivov smo prepletli s prefinjenim okusom za linije in obliko ter vtkali niti vrhunske tehnologije.

From the cleanliness and purity of a new-born world stems the story of the Pure line. The touch of natural motifs is intertwined with a sophisticated taste for lines and form and interwoven with threads of state-of-the-art technology.



PURE






občutek narave feeling of nature

Linijo stikal Pure odlikujejo naravni materiali: kovina, les, steklo. Poseben dotik se izraža skozi edinstveno obliko. Je opazen, a hkrati nevzljiv. Izžareva čutnost, prefinjenost, merila visokega standarda in seveda čistost.

The Pure switch line is distinguished by its natural materials: metal, wood and glass. Its unique design gives it a special touch. It is striking yet unobtrusive. It radiates sensuality, sophistication, high standards and, of course, cleanliness.



line



harmonija ravnih oblik








harmony of straight lines

Pripravite se na elegantno popolnost ravnih oblik. Preizkusite sijajnost površin, ki se nežno poigravajo z modernimi elementi vašega prostora. Posebej za vas smo vgradili tehnologijo Soft Touch, da je vsak vaš dotik posebno doživetje.

Prepare for the elegant perfection of straight shapes. Try brilliant surfaces that gently play with modern elements of your room. We have incorporated "Soft Touch" technology especially for you, turning every touch into a unique experience.



~~line~~






sodoben dizajn modern design

Čiste, ravne linije ustvarjajo brezčasen dizajn.
Popoln, ravno oblikovan tanek profil in ergonomija
mehkega dotika dajeta vrhunski videz z vseh strani.

Its straight, smooth lines make for a timeless design.
Its perfectly straight, sleek profile and soft-touch ergonomics
give it an amazingly elegant appearance from all angles.



soft



mehkoba v vašem domu softness in your home


Dovolite, da zaobljene oblike in nežni prehodi
prinesejo mehkobo v vaš dom.

Let the rounded shapes and soft transitions
bring softness into your home.



soft






toplina doma a warm home


Popolnost mehke oblike smo nadgradili s subtilnim izborom barv in posebnimi nanosi, ki jih čutite ob dotiku.

Perfectly soft shapes rounded off by a subtle selection of colours and special coatings for a special touch.



univerzalni zatemnilnik

universal dimmer



možnost
nastavitev
različne
jakosti
osvetlitve
adjustable
light
intensity

možnost
izbire
različnih
barv
osvetlitve
choosing
illumination
colour

V temi postane Touch nežna, ambientalna lučka, ki označuje mesto stikala in blago razsvetljuje prostor. Izberete lahko eno od osmih različnih barv nežne svetlobe, katerih svetlost lahko kadarkoli poljubno prilagodite svojemu razpoloženju.

In the dark Touch becomes a tender soft ambient light. It marks the spot of a switch and gently illuminates a place. You can choose among eight different colours of tender light and adapt its brightness according to your mood.

TOUCH.[®]

svetloba, kot še nikoli light as never seen before

Pridušena svetloba ustvarja ozračje miru, pa tudi čutnosti in romantične. Je zaščitni znak romantičnih lokalov in mirnih poznovečernih ur doma ali v delovnem prostoru. Mehak, podaljšan vklop ne podaljšuje le življenske dobe sijalke, ampak tudi veliko prijazneje in počasnejše zamenja temo s svetlobo. Touch omogoča, da zatemnite svetlogo kjerkoli, ne glede na tip sijalke ali žarnice.

A dimmed light makes peaceful, sensual and romantic atmosphere. It is a trade mark of romantic places and quiet late evening hours spent at home or at work. Switching is soft and extended. It does not only prolong the lamp life expectancy, but also changes darkness into light in a slower and much more pleasant way. Touch enables you to dim the light anywhere, regardless of the type of lamps.



multimedija

multimedia



vse na enem mestu

everything in one place

Vaša hiša je postala središče življenja. Množica vseh naprav zahteva številne priključke in vtičnice. Sestavite si svoj multimedijijski center, ki vam nudi možnost priključitve in upravljanja več različnih komponent na enem mestu.

Your house is the centre of your life. The multitude of devices you use requires a number of connectors and sockets. Create your own multimedia centre, one that will allow you to connect and use a multiple number of different components in one place.



inovativen krmilnik temperature innovative temperature controller

Poskrbite za svoje udobje in s pametnim termostatom upravljajte temperaturo bivalnih in delovnih prostorov v vseh letnih časih. Upravljate lahko naprave gretja in hlajenja z možnostjo ekonomičnega delovanja.

Make yourself comfortable by controlling the temperature in your living and working rooms during all seasons with a smart thermostat. It allows you to control heating and cooling devices and features an eco-function.

udobje prostora comfort in your room



udobje uporabe

convenience of use



TOUCHLESS-brez dotika

Brezdotično stikalo vam omogoča sodoben način življenja, saj svetila lahko prižigate in ugašate, ne da bi se dotaknili stikala. Ta možnost je zelo uporabna, če imate polne ali umazane roke, saj lahko luč prižgete brez dotika.

The touchless switch allows you to enjoy a modern lifestyle, enabling the turning on and off of your lights, without the need for physical interaction. This option is very useful when you find yourself with your hands full, or dirty, as you can achieve the desired lighting without undue fuss.



sodobna osvetlitev

modern illumination





3D svetilka

3D lamp

Hiter tempo življenja prinaša množico informacij. 3D barvna svetilka je elegantna rešitev za označevanje, usmerjanje in sporočanje. Grafiko izdelamo po vaši želji.

The rapid pace of life means you are constantly being bombarded with a plenty of information. 3D colour lamp provide an elegant solution for information and direction signs. We can make graphics according to your wishes.



ARX – adijo ključi

ARX – say goodbye to keys

ARX ONE vam omogoča varen in udoben vstop v stanovanje, hišo ali poslovni prostor. Potreben je le poteg s prstom in vrata se odklenejo. Deluje kot samostojna enota, za upravljanje ne potrebujete povezave z računalnikom.

The ARX ONE allows you to gain access to your apartment, house or office securely and conveniently. It takes only a swipe of the finger to unlock the door. It functions as an independent unit and requires no computer connection.

povečana varnost
improved security

29



individualhost

individuality




naredite si svojega make it your own

Bodite drugačni. Zaželite si stikala po vaši meri. Izbirajte med različnimi barvami okvirjev, lahko vam jih okrasimo s poljubnimi grafikami in napisi. Izberite barvo osvetlitve, ki ustreza vašemu ambientu.

Be different. Make a switch according to your taste. You can choose between different frame colours and we can decorate them for you with custom graphics or signs. Choose a illumination colour that suits the ambience of your room.




primerno za javno uporabo
suitable for public use



kakovost in trpežnost quality and durability

Kakovostni in trpežni materiali zagotavljajo dolgo življenjsko dobo modularnih stikal in vtičnic MODUL. Sistem je zato primeren za vgradnjo in brezskrbno uporabo v javnih ustanovah, poslovnih zgradbah, turističnih nastanitvah, trgovskih centrih, šolah in športnih objektih. Prilagodi se tako sodobni arhitekturi kot klasičnim interierjem.

Quality and durable materials ensure the long lifetime of the MODUL modular switches and sockets. The system is suitable for mounting and carefree use in public facilities, business premises, tourist accommodation, shopping centres, schools and sports facilities. It fits perfectly in both modern architecture and classical interiors.





zmogljivi USB polnilniki powerful USB chargers

Z zmogljivimi USB polnilniki Modul boste hitro in enostavno napolnili pametne telefone, tablične računalnike in ostale e-naprave prek standardnega USB priključka. Na voljo so v velikostih 1M in 2M. Idealni so tako za uporabo v zasebnih kot javnih prostorih.

The powerful Modul USB chargers enable the fast and simple charging of your smartphones, tablets and other electronic devices via a standard USB connection. They are available in 1M and 2M sizes and are perfect for use in private and public rooms.

hitro polnjenje
fast charging



sodobno delovno okolje

a modern working environment





estetski aluminijasti kanali aesthetic aluminium trunkings

Poskrbite za urejenost pisarniških, šolskih in delovnih prostorov. Znebite se vidnih kablov in nerodnih podaljškov. Elegantni aluminijasti kanali modernega videza nudijo veliko prostora za elektroinštalacije. Stikala, vtičnice in komunikacijski priključki so hitro dostopni in na voljo tam, kjer jih potrebujete. Enostavno jih lahko spremenite ali naknadno dodate nove. Ustvarite si prijetno funkcionalno okolje.

Organise your office, school and work areas. Forget visible cables and unpractical extensions. The elegant and modern aluminium trunkings offer plenty of space for electrical installations. Switches, sockets and communication elements are easily accessible and available in the right place to be used. They can be easily adapted or upgraded. Arrange a pleasant and functional environment for yourself.


modularnost

modularity



Poskrbeli smo za celovit sistem. V njem najdete vse elemente za poljuben sestav.
Osnovni elementi sistema so moduli.
Kombinirate jih lahko vodoravno ali navpično.

We have designed a comprehensive system that features a variety of elements, allowing you to create any configuration you wish. The basic elements of the system are modular and can be combined horizontally or vertically.





1M =

2M = **=**

univerzalnost

universality

Sistem odlikuje popoln izbor elementov in enostavna vgradnja.
Set stikal lahko umestite v prostor na veliko načinov,
naj bo doza okrogla ali pravokotna, samostojna ali v nizu.

The system features a comprehensive selection of elements and is easy to install. Switch sets can be positioned in many different ways, regardless of whether the box is round or rectangular, individual or serial.



modulmanager.tem.si



Preizkusite orodje "ModulManager",
ki vam bo pomagal
sestaviti poljubne kombinacije.

Try out the "ModulManager" tool,
which will help you put together
any combination you want.

rešitve za primer 4 stikal

solutions for 4 switches

1/2M ○ ○ ○ ○



2M ○ ○ ○ ○



2M ○ ○



1/3M □ □ □ □



2/3M ○ ○ ○ ○



2/3M ○ ○



4M □



2x2M ○○



2x2M ○○ ○○



4x2M ○○○○




3x2M ○○○○



MODUL MANAGER

enostavno in hitro / easy and fast



Download on the
App Store

ANDROID APP ON
Google play



konfigurator stikal in vtičnic configurator of switches and sockets

Modul Manager vam omogoča popolno in hitro izdelavo popisa stikal z gradbišča ali domačega naslonjača. Pripravili smo vam edinstven način naročanja, ki je praktičen in hiter, na voljo imate možnost kreiranja barv stikal in oblik okvirjev, da jih lahko prilagodite vašemu prostoru ali zahtevi kupca. Preizkusite nas, potrebujete le telefon, tablico ali računalnik in <http://modulmanager.tem.si>.

The Modul Manager allows you to perform a complete and quick inventory of switches from the building site itself or from the comfort of your own home. We have prepared a unique ordering method, which is both practical and quick. You can select the colours of the switches, as well as the shape of the frames, meaning you can tailor them to your space or the client's demands. Why not try us out? All you need is a smartphone, a tablet, or a computer and <http://modulmanager.tem.si>.

funkcionalnost

functionality

Modul smo razvili za vse, ki znate ceniti premišljeno načrtovan izdelek. Sistem potrebuje manj prostora, saj je v isti okvir možno sestaviti poljubno kombinacijo funkcijskih elementov. Primeren je za novogradnje in adaptacije.

The Modul was developed for those who can appreciate a thoughtfully designed product. The system takes up less space, as any combination of function elements can be fitted inside the same cover plate. It is suitable for new, as well as renovated buildings.



Modul Soft tudi v antibakterijski izvedbi AW.

The Modul Soft is also available in an antibacterial solution AW.

dekorativni okvirji
decorative cover plates



funkcijski elementi
function elements




enostavnost

simplicity


Funkcijske elemente enostavno pritrdite v nosilec. Za vas smo razvili rešitev "klik-in, klik-out", ki vam skrajša čas montaže. Priklučni kontakti so lahko dostopni s sprednje strani.

The function elements are easily fitted inside the mounting frame. The "klik-in, klik-out" solution we have developed for you will reduce installation time. The connection contacts are easily accessible from the front.






"klik-out" - enostavno in hitro,
brez viačenja.

"klik-out" - simple and quick,
no screws necessary.



V pravokotnih dozah je več
prostora za priključne vodnike.


Rectangular boxes have more
space for connection wires.



sestavljivost combinability

Modul vam ponuja veliko možnosti tudi ob uporabi okroglih doz. Kombinirate lahko vodoravno ali navpično, samostojno ali v skupinah. Kovinski nosilec zagotavlja odlično stabilnost tudi pri grobi uporabi in je primeren za vse dekorativne okvirje.

The Modul enables a many possibilities even with round boxes. You can combine them horizontally or vertically, individually or in groups. The metal mounting frame ensures excellent stability even with rough use and is suitable for any decorative cover plates.




Isti okvir je možno uporabiti vodoravno ali navpično.

The same cover plate can be positioned horizontally or vertically.




Nosilci se lahko pritrdijo z vijaki ali krempeljci.

Mounting frames can be fixed with screws or claws.



Nosilce velikosti 2M je mogoče s preprostim preklopom povezati v večje skupine.

2M mounting frames are easily joined into groups.



univerzalnost

universality



line




soft




PURE




2M




2 x 2M



3 x 2M




4 x 2M




Sistem je univerzalen, primeren za vgradnjo v okrogle in pravokotne doze.

The system is universal and can be fitted in both round and rectangular boxes.



funkcijski elementi

function elements



Zanesljiva priključitev vodnikov različnih premerov.

Reliable connection even when different size of wires are used.



Dolga življenska doba stikal in ustreznost sodobnim standardom.

Long-life of switches and adequacy to the international standards.

Poskrbeli smo, da v družini Modul najdete širok nabor funkcijskih elementov. Z njimi lahko načrtujete enostavne ali zahtevne inštalacije.

We have designed a wide selection of function element for the Modul family. You can use them to design both simple and complex installations.



• vtičnice /
sockets

• zabava /
entertainment

• osvetlitev /
illumination

Vse vtičnice imajo vgrajeno varovalo pred dotikom elementov pod napetostjo.

All the sockets are equipped with a safety shutters assuring the protection to live contacts.

Zanesljivost preklopa omogočajo srebrne kontaktne kovice.

The switch is highly reliable via its silver rivets contacts.

16 AX
kontakti

edinstvena širina uporabnosti

unique range of usability

Modul Soft AW
antibakterijska izvedba /
antibacterial solution



M O D U L

CUBO IP20

nadomestna ohišja
surface mounted boxes



CUBO IP55

nadomestna ohišja
surface mounted boxes



IP44

podomet
flush mounted



Opremljate dom, pisarno ali delavnico?

Modul lahko uporabite tako v bivalnih kot delovnih prostorih, zasebnih in javnih zgradbah. Edinstven je v tem, da lahko stikala in vtičnice vgradite tam, kjer jih potrebujete.

Are you furnishing your home, office or workshop? The Modul is suitable for living as well as working spaces and both private and public buildings. It is unique in that the switches and sockets can be fitted wherever they are needed.

D

opeka
brick




H

votla stena
hollow wall



B

beton
concrete



● funkcionalni elementi /
function elements

stikala / switches
vtičnice / sockets
komunikacije / communications
senzorji / sensors
regulatorji / regulators
osvetlitve / illuminations

MA

parapetni kanali
trunking systems



MO

razdelilne omarice
distribution boards



MT

talne doze
floor boxes




podometne rešitve


flush mounted solutions

opeka / brick

Modul lahko vgradite v katerokoli vrsto stene, naj bo klasična, suho montažna ali betonska. Vgradnja je enostavna, ponuja vam možnosti sestavljanja pravokotnih ali okroglih doz na ustrezne razdalje. Uporabljeni materiali so testirani po visokih standardih.

The Modul is suitable for all wall types and can be used in conventional, hollow wall or concrete constructions. It is easy to install and enables you to combine rectangular or round boxes at the proper distances. The materials used are compliant with high standards.






druge rešitve

other solutions

IP44
podomet
flush mounted



CUBO IP20
nadometna ohišja
surface mounted boxes



CUBO IP55
nadometna ohišja
surface mounted boxes



Potrebujete stikalo ali vtičnico v podometni, nadometni ali talni izvedbi? Modul ponuja različne rešitve vgradnje, v različnih IP zaščitah, v parapetne kanale, razdelilne omarice ali talne doze. Izbira je vaša.

Do you need switch or socket in flush, surface or floor solution? The Modul provides different mounting solutions with different IP protections, for trunking systems, distribution boards or floor boxes. The choice is yours.



tehnični katalog

technical catalogue



MODUL

— funkcijski elementi
function elements



62

dizajn
design

PURE
—
line
soft



112

doze
boxes



132

distribucija
distribution



154

Ekonomik —

fontana —



178



206

TEM



KATALOG /
CATALOGUE

MODUL

FUNKCIJSKI ELEMENTI
FUNCTION ELEMENTS

STIKALA SM
SWITCHES SM  64

TIPKE TM
BUTTONS TM  69

INDIKACIJA IA
ILLUMINATION IA  72

VTIČNICE VM
SOCKETS VM  74

KOMUNIKACIJE KM
COMMUNICATIONS KM  78

KOMUNIKACIJSKI PRIBOR KA
COMMUNICATION ACCESSORIES KA  84

ELEKTRONIKA EM
ELECTRONICS EM  86

SETI CM
SETS CM  105

ANTIBAKTERIJSKI PROGRAM AW
ANTIBACTERIAL PROGRAM AW  108

OBLIKA
DESIGN

OKVIRJI PURE OP
COVER PLATES PURE OP  112

OKVIRJI LINE OL
COVER PLATES LINE OL  116

OKVIRJI SOFT OS
COVER PLATES SOFT OS  120



NOSILCI NM
MOUNTING FRAMES NM  128

tip type	naziv description	tehnični opis technical data	velikost size	barva colour	opcijski opis 1 optional data 1	opcijski opis 2 optional data 2
SM10	STIKALO ENOPOLNO SWITCH 1WAY	16AX 250V~	1M	<input type="checkbox"/> PW bela-sijaj polar white	NT neutral neutral	01
SM11	TIPKALO ENOPOLNO PUSH BUTTON 1WAY	16A 250V~	1M	<input checked="" type="checkbox"/> SB črna-mat soft touch black		02
SM12	STIKALO ENOPOLNO SWITCH 1WAY	20A 250V~	1M	<input type="checkbox"/> ES srebrena-mat elox silver	IN indikator indicator	03
.	.	.	.	<input type="checkbox"/> IW bež-sijaj ivory white		
.	.	.	.			
.	.	.	.			

STIKALO ENOPOLNO 16AX 250V~ 1M


SM10

- stikalo brez tipke
- 16AX 250V~, tip SM10
- ustreza EN 60669-1
- vijačna pritrditev vodnikov 1.5-2.5mm²

**TIPKALO ENOPOLNO 16A 250V~ 1M**


SM11

- tipkalo brez tipke
- 16A 250V~, tip SM11
- ustreza EN 60669-1
- vijačna pritrditev vodnikov 1.5-2.5mm²

**STIKALO ENOPOLNO 20A 250V~ 1M**

SM12

- stikalo brez tipke
- 20A 250V~, tip SM12
- ustreza EN 60669-1
- vijačna pritrditev vodnikov 1.5-2.5mm²


**STIKALO DVOPOLNO 16AX 250V~ 1M**

SM20

- stikalo brez tipke
- 16AX 250V~, tip SM20
- ustreza EN 60669-1
- vijačna pritrditev vodnikov 1.5-2.5mm²
- samo v kombinaciji s tipko TM15

SWITCH 2POLE 16AX 250V~ 1M


- switch without button
- 16AX 250V~, type SM20
- in accordance with EN 60669-1
- screw contacts 1.5-2.5mm²
- only in combination with button TM15



SWITCHES SM




SM40




STIKALO ŽALUZIJSKO 1-0-2 16AX 250V~ 1M

- stikalo brez tipke
 - 16AX 250V~, tip SM40
 - ustreza EN 60669-1
 - vijačna pritrditev vodnikov 1.5-2.5mm²
- SWITCH SHUTTERS 1-0-2 16AX 250V~ 1M**
- switch without button
 - 16AX 250V~, type SM40
 - in accordance with EN 60669-1
 - screw contacts 1.5-2.5mm²




SM41




TIPKALO ŽALUZIJSKO 1-0-2 16A 250V~ 1M

- tipkalo brez tipke
 - 16A 250V~, tip SM41
 - ustreza EN 60669-1
 - vijačna pritrditev vodnikov 1.5-2.5mm²
- PUSH BUTTON SHUTTERS 1-0-2 16A 250V~ 1M**
- push button without button
 - 16A 250V~, type SM41
 - in accordance with EN 60669-1
 - screw contacts 1.5-2.5mm²




SM60




STIKALO MENJALNO 16AX 250V~ 1M

- stikalo brez tipke
 - 16AX 250V~, tip SM60
 - ustreza EN 60669-1
 - vijačna pritrditev vodnikov 1.5-2.5mm²
- SWITCH 2WAY 16AX 250V~ 1M**
- switch without button
 - 16AX 250V~, type SM60
 - in accordance with EN 60669-1
 - screw contacts 1.5-2.5mm²




SM61




TIPKALO MENJALNO 16A 250V~ 1M

- tipkalo brez tipke
 - 16A 250V~, tip SM61
 - ustreza EN 60669-1
 - vijačna pritrditev vodnikov 1.5-2.5mm²
- PUSH BUTTON 2WAY 16A 250V~ 1M**
- push button without button
 - 16A 250V~, type SM61
 - in accordance with EN 60669-1
 - screw contacts 1.5-2.5mm²






SM70



STIKALO KRIŽNO 16AX 250V~ 1M

- stikalo brez tipke
 - 16AX 250V~, tip SM70
 - ustreza EN 60669-1
 - vijačna pritrditev vodnikov 1.5-2.5mm²
- SWITCH INTERMEDIATE 16AX 250V~ 1M**
- switch without button
 - 16AX 250V~, type SM70
 - in accordance with EN 60669-1
 - screw contacts 1.5-2.5mm²

1M = 22,5 x 45
2M = 45 x 45



PW bela-sijaj
polar white



SB črna-mat
soft touch black



ES srebrna-mat
elox silver



IW bež-sijaj
ivory white

STIKALO ENOPOLNO 16AX 250V~ 1M



SM10PW
 SM10SB
 SM10ES
 SM10IW

- 16AX 250V~, tip SM10
- ustreza EN 60669-1
- vijačna pritrditev vodnikov 1.5-2.5 mm²
- zamenljiva tipka

SWITCH 1WAY 16AX 250V~ 1M

- 16AX 250V~, type SM10
- in accordance with EN 60669-1
- screw contacts 1.5-2.5 mm²
- replaceable button



STIKALO ENOPOLNO 16AX 250V~ 1M _ IN



SM10PWIN
 SM10SBIN
 SM10ESIN
 SM10IWIN

- IN indikator
- 16AX 250V~, tip SM10
- ustreza EN 60669-1
- vijačna pritrditev vodnikov 1.5-2.5 mm²
- tlivka ni priložena
- zamenljiva tipka

SWITCH 1WAY 16AX 250V~ 1M _ IN

- IN indicator
- 16AX 250V~, type SM10
- in accordance with EN 60669-1
- screw contacts 1.5-2.5 mm²
- lamp is not included
- replaceable button



TIPKALO ENOPOLNO 16A 250V~ 1M



SM11PW
 SM11SB
 SM11ES
 SM11IW

- 16A 250V~, tip SM11
- ustreza EN 60669-1
- vijačna pritrditev vodnikov 1.5-2.5 mm²
- zamenljiva tipka

PUSH BUTTON 1WAY 16A 250V~ 1M

- 16A 250V~, type SM11
- in accordance with EN 60669-1
- screw contacts 1.5-2.5 mm²
- replaceable button



TIPKALO ENOPOLNO 16A 250V~ 1M _ IN 01



SM11PWIN01
 SM11SBIN01
 SM11ESIN01
 SM11IWIN01

- IN 01 indikator zvonec
- 16A 250V~, tip SM11
- ustreza EN 60669-1
- vijačna pritrditev vodnikov 1.5-2.5 mm²
- tlivka ni priložena
- zamenljiva tipka

PUSH BUTTON 1WAY 16A 250V~ 1M _ IN 01

- IN 01 indicator bell
- 16A 250V~, type SM11
- in accordance with EN 60669-1
- screw contacts 1.5-2.5 mm²
- lamp is not included
- replaceable button



S W I T C H E S S M



- SM11PWIN02
- SM11SBIN02
- SM11ESIN02
- SM11IWIN02

TIPKALO ENOPOLNO 16A 250V~ 1M _ IN 02

- IN 02 indikator luč
- 16A 250V~, tip SM11
- ustreza EN 60669-1
- vijačna pritrditev vodnikov 1.5-2.5 mm²
- tlivka ni priložena
- zamenljiva tipka

PUSH BUTTON 1WAY 16A 250V~ 1M _ IN 02

- IN 02 indicator light
- 16A 250V~, type SM11
- in accordance with EN 60669-1
- screw contacts 1.5-2.5 mm²
- lamp is not included
- replaceable button



- SM20PWNT03
- SM20SBNT03
- SM20ESNT03
- SM20IWIN03

STIKALO DVOPOLNO 16AX 250V~ 1M _ NT 03

- NT 03 nevtral 0-1
- 16AX 250V~, tip SM20
- ustreza EN 60669-1
- vijačna pritrditev vodnikov 1.5-2.5 mm²
- zamenljiva tipka

SWITCH 2POLE 16AX 250V~ 1M _ NT 03

- NT 03 neutral 0-1
- 16AX 250V~, type SM20
- in accordance with EN 60669-1
- screw contacts 1.5-2.5 mm²
- lamp is not included
- replaceable button




- SM20PWIN
- SM20SBIN
- SM20ESIN
- SM20IWIN

STIKALO DVOPOLNO 16AX 250V~ 1M _ IN

- IN indikator
- 16AX 250V~, tip SM20
- ustreza EN 60669-1
- vijačna pritrditev vodnikov 1.5-2.5 mm²
- tlivka ni priložena
- zamenljiva tipka

SWITCH 2POLE 16AX 250V~ 1M _ IN

- IN indicator
- 16AX 250V~, type SM20
- in accordance with EN 60669-1
- screw contacts 1.5-2.5 mm²
- lamp is not included
- replaceable button




- SM40PWNT10
- SM40SBNT10
- SM40ESNT10
- SM40IWIN10

STIKALO ŽALUZJSKO 1-0-2 16AX 250V~ 1M _ NT 10

- NT 10 nevtral 1-0-2
- 16AX 250V~, tip SM40
- ustreza EN 60669-1
- vijačna pritrditev vodnikov 1.5-2.5mm²
- zamenljiva tipka

SWITCH SHUTTERS 1-0-2 16AX 250V~ 1M _ NT 10

- NT 10 neutral 1-0-2
- 16AX 250V~, type SM40
- in accordance with EN 60669-1
- screw contacts 1.5-2.5mm²
- replaceable button




- SM41PWNT10
- SM41SBNT10
- SM41ESNT10
- SM41IWIN10

TIPKALO ŽALUZJSKO 1-0-2 16A 250V~ 1M _ NT 10

- NT 10 nevtral 1-0-2
- 16A 250V~, tip SM41
- ustreza EN 60669-1
- vijačna pritrditev vodnikov 1.5-2.5mm²
- zamenljiva tipka

PUSH BUTTON SHUTTERS 1-0-2 16A 250V~ 1M _ NT 10

- NT 10 neutral 1-0-2
- 16A 250V~, type SM41
- in accordance with EN 60669-1
- screw contacts 1.5-2.5mm²
- replaceable button



- SM60PW
- SM60SB
- SM60ES
- SM60IW


STIKALO MENJALNO 16AX 250V~ 1M

- 16AX 250V~, tip SM60
- ustreza EN 60669-1
- vijačna pritrditev vodnikov 1.5-2.5 mm²
- zamenljiva tipka

SWITCH 2WAY 16AX 250V~ 1M

- 16AX 250V~, type SM60
- in accordance with EN 60669-1
- screw contacts 1.5-2.5 mm²
- replaceable button





- SM61PW
- SM61SB
- SM61ES
- SM61IW

TIPKALO MENJALNO 16A 250V~ 1M

- 16A 250V~, tip SM61
 - ustreza EN 60669-1
 - vijačna pritrditev vodnikov 1.5-2.5 mm²
 - zamenljiva tipka
- PUSH BUTTON 2WAY 16A 250V~ 1M**
- 16A 250V~, type SM61
 - in accordance with EN 60669-1
 - screw contacts 1.5-2.5 mm²
 - replaceable button



- SM62PWCD
- SM62SBCD
- SM62ESCD
- SM62IWCD

TIPKALO MENJALNO Z VRVICO 16A 250V~ 1M _ CD

- CD indikator+vrvica
 - vrvica dolžine 1.5m
 - 16A 250V~, tip SM62
 - ustreza EN 60669-1
 - vijačna pritrditev vodnikov 1.5-2.5 mm²
- PUSH BUTTON 2WAY WITH CORD 16A 250V~ 1M _ CD**
- CD indicator+cord
 - cord lenght 1.5m
 - 16A 250V~, type SM62
 - in accordance with EN 60669-1
 - screw contacts 1.5-2.5 mm²




- SM70PW
- SM70SB
- SM70ES
- SM70IW

STIKALO KRIŽNO 16AX 250V~ 1M


- 16AX 250V~, tip SM70
 - ustreza EN 60669-1
 - vijačna pritrditev vodnikov 1.5-2.5 mm²
 - zamenljiva tipka
- SWITCH INTERMEDIATE 16AX 250V~ 1M**
- 16AX 250V~, type SM70
 - in accordance with EN 60669-1
 - screw contacts 1.5-2.5 mm²
 - replaceable button



1M = 22,5 x 45
2M = 45 x 45



BUTTONS TM



03


TM11

PW

NT

tip type	naziv description	tehnični opis	velikost size	barva colour	opcijski opis 1 optional data 1	opcijski opis 2 optional data 2
TM11	TIPKA BUTTON		1M	<input type="checkbox"/> PW bela-sijaj polar white	NT nevral neutral	01
TM12	TIPKA BUTTON		2M	<input checked="" type="checkbox"/> SB črna-mat soft touch black	IN indikator indicator	02
TM21	POLNINO BLANK		1M	<input type="checkbox"/> ES srebrna-mat elox silver		03
				<input type="checkbox"/> IW bež-sijaj ivory white		

TIPKA 1M



- TM11PW
- TM11SB
- TM11ES
- TM11IW

- zamenljiva tipka velikosti 1M
- ustreza EN 60669-1

BUTTON 1M

- replaceable button 1M
- in accordance with EN 60669-1



TIPKA 1M INDIKATOR



- TM11PWIN
- TM11SBIN
- TM11ESIN
- TM11IWIN


- zamenljiva tipka velikosti 1M
- ustreza EN 60669-1

BUTTON 1M INDICATOR

- replaceable button 1M
- in accordance with EN 60669-1



TIPKA 2M



- TM12PW
- TM12SB
- TM12ES
- TM12IW


- zamenljiva tipka velikost 2M z nosilcem tipke
- uporablja se pri nadgradnji stikala ali tipkala
velikosti 1M v velikost 2M
- ustreza EN 60669-1

BUTTON 2M

- replaceable button 2M with button carrier
- to upgrade switch or push button
from size 1M to size 2M
- in accordance with EN 60669-1



TIPKA 2M INDIKATOR




- TM12PWIN
- TM12SBIN
- TM12ESIN
- TM12IWIN

- zamenljiva tipka velikost 2M z nosilcem tipke
- uporablja se pri nadgradnji stikala ali tipkala
velikosti 1M v velikost 2M
- ustreza EN 60669-1

BUTTON 2M INDICATOR

- replaceable button 2M with button carrier
- to upgrade switch or push button
from size 1M to size 2M
- in accordance with EN 60669-1






- TM13PWIL
- TM13SBIL
- TM13ESIL
- TM13IWIL

TIPKA 2M Z NAPISNO PLOŠČICO

- zamenljiva tipka velikost 2M z nosilcem tipke
- uporablja se pri nadgradnji stikala ali tipkala
velikosti 1M v velikost 2M
- ustreza EN 60669-1

BUTTON 2M WITH INSCRIPTION PLATE

- replaceable button 2M with button carrier
- to upgrade switch or push button
from size 1M to size 2M
- in accordance with EN 60669-1




- TM15PW
- TM15SB
- TM15ES
- TM15IW

TIPKA 1M DVOPOLNA

- zamenljiva tipka velikosti 1M
- samo v kombinaciji z mehanizmom SM20
- ustreza EN 60669-1

BUTTON 1M 2POLE

- replaceable button 1M
- only in combination with mechanism SM20
- in accordance with EN 60669-1



- TM21PW
- TM21SB
- TM21ES
- TM21IW

POLNILO 1M

- za zapolnjevanje praznih mest
- ustreza EN 60669-1

BLANK 1M

- blank modul to fill up empty spaces
- in accordance with EN 60669-1




- TM22PW
- TM22SB
- TM22ES
- TM22IW

POLNILO 2M

- za zapolnjevanje praznih mest
- ustreza EN 60669-1

BLANK 2M

- blank modul to fill up empty spaces
- in accordance with EN 60669-1



- TM31PW
- TM31SB
- TM31ES
- TM31IW

UVODNICA 1M


- uvodnica za kabel
- ustreza EN-60669-1

CABLE OUTLET 1M


- outlet for cable
- in accordance with EN-60669-1




1M = 22,5 x 45
2M = 45 x 45




TM11
TM15




TM12
TM13



TM21




TM22



TM31

B U T T O N S T M


MODUL
E

LASERSKI TISK NA TIPKE

- laserski tisk poljubne grafike na označena mesta
- standardni simboli iz zaloge, ostali po naročilu

LASER PRINT ON BUTTONS

- laser print of any graphics on marked locations
- standard symbols from stock, other on request



1M

A
B
C

2M

A	D	G
B	E	H
C	F	I


GRAFIKE


SYMBOLS

01	02	03	04	05	06	07	08	09	10	11	12	20	21	22	23
!	!	0	0	!	!	!	!	!	^	^	^	+	-	!	!
24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39
!	!	!	!	!	!	!	!	!	!	!	!	!	!	!	!
40	41	42	43	44	45	46	47	48							
!	!	!	!	!	!	!	!	!							

STANDARDNE GRAFIKE

STANDARD SYMBOLS





IA20

WH

tip type	naziv description	tehnični opis technical data	barva colour
IA10	TLIVKA NEON LAMP	230V~ 0,34W	<input type="checkbox"/> WH bela white
IA20	SIJALKA LED LED LAMP	230V~ AC/DC 0,40W	<input checked="" type="checkbox"/> BL modra blue
IA21	SIJALKA LED LED LAMP	24V AC/DC 0,20W	<input checked="" type="checkbox"/> RD rdeča red
.	.	.	<input checked="" type="checkbox"/> GR zelena green
.	.	.	<input checked="" type="checkbox"/> OR oranžna orange

TLIVKA 230V~ 0,34W IA10OR

- za indikacijo, osvetlitev
ali stalno osvetlitev stikala
- v kombinaciji s tipko z indikatorjem

NEON LAMP 230V~ 0,34W

- for indication, illumination or
constant illumination of switch
- in combination with button with indicator

**SIJALKA LED 230V AC/DC 0,40W**
 IA20WH
 IA20GR
 IA20RD
 IA20BL

- za indikacijo, osvetlitev
ali stalno osvetlitev stikala
- v kombinaciji s tipko z indikatorjem

LED LAMP 230V AC/DC 0,40W

- for indication, illumination or
constant illumination of switch
- in combination with button with indicator

**SIJALKA LED 24V AC/DC 0,20W**
 IA21WH
 IA21RD

- za indikacijo, osvetlitev
ali stalno osvetlitev stikala
- v kombinaciji s tipko z indikatorjem

LED LAMP 24V AC/DC 0,20W

- for indication, illumination or
constant illumination of switch
- in combination with button with indicator

**SIJALKA LED 12V AC/DC 0,10W**
 IA22WH
 IA22RD

- za indikacijo, osvetlitev
ali stalno osvetlitev stikala
- v kombinaciji s tipko z indikatorjem

LED LAMP 12V AC/DC 0,10W


- for indication, illumination or
constant illumination of switch
- in combination with button with indicator

**RC VEZJE 250V~**


- RC vezje za odpravo motenj pri
delovanju LED sijalk
- možna je vzporedna vezava več RC vezij
s sijalkami
- 0,1 µF, 100 Ω, 250V~

RC CIRCUIT 250V~


- RC circuit to eliminate disturbances in the operation
of LED lamps
- parallel connections of more RC circuits with lamps
are possible
- 0,1 µF, 100 Ω, 250V~




IA50




* Indikacija /
Indication




Osvetlitev /
Illumination




Stalna osvetlitev /
Constant illumination




SM60 + SM60




SM60 + SM60




SM60 + SM60




SM60 + SM70 + SM60




SM60 + SM70 + SM60




SM60 + SM70 + SM60



SM20




SM20



* vezave primerne za varčne (CFL, LED) sijalke /
wiring scheme for compact fluid lamp (CFL, LED)

1M = 22,5 x 45
2M = 45 x 45





tip type	naziv description	tehnični opis technical data	velikost size	barva colour
VM10	VTIČNICA SCHUKO+KS SOCKET SCHUKO+KS	2P+E 16A 250V~	2M	<input type="checkbox"/> PW bela-sijaj polar white
VM11	VTIČNICA SCHUKO+KS+POKROV SOCKET SCHUKO+KS+COVER	2P+E 16A 250V~	2M	<input checked="" type="checkbox"/> SB črna-mat soft touch black
VM20	VTIČNICA EURO+KS SOCKET EURO+KS	2P 10A 250V~	1M	<input type="checkbox"/> ES srebrna-mat elox silver
.	.	.	.	<input type="checkbox"/> IW bež-sijaj ivory white
.	.	.	.	<input type="checkbox"/> RD rdeča red
.	.	.	.	<input type="checkbox"/> GR zelena green
.	.	.	.	<input type="checkbox"/> OR oranžna orange
				<input checked="" type="checkbox"/> PT bela+prozorna white+transparent
				<input checked="" type="checkbox"/> BT črna+prozorna soft touch black+transparent
				<input type="checkbox"/> ST srebrna+prozorna silver+transparent
				<input type="checkbox"/> IT bež+prozorna ivory+transparent
				<input checked="" type="checkbox"/> RT rdeča+prozorna red+transparent
				<input type="checkbox"/> GT zelena+prozorna green+transparent
				<input checked="" type="checkbox"/> OT oranžna+prozorna orange+transparent
				<input type="checkbox"/> SS srebrna+srebrna silver+silver
				<input type="checkbox"/> II bež+bež ivory+ivory
				<input checked="" type="checkbox"/> RR rdeča+rdeča red+red
				<input type="checkbox"/> GG zelena+zelena green+green
				<input type="checkbox"/> OO oranžna+ oranžna orange+orange




VTIČNICA SCHUKO+KS 2P+E 16A 250V~ 2M



- VM10PW
- VM10SB
- VM10ES
- VM10IW

- 2P+E schuko
 - 16A 250V~, tip VM10
 - ustreza IEC 60884-1, CEE7
 - vijačna pritrditev vodnikov 1.5-2.5 mm²
 - KS vgrajena otroška zaščita pred dotikom kontaktov
- SOCKET SCHUKO+KS 2P+E 16A 250V~ 2M
- 2P+E schuko
 - 16A 250V~, type VM10
 - in accordance with IEC 60884-1, CEE7
 - screw contacts 1.5-2.5 mm²
 - KS build-in child protection - shuttered live contacts



- VM10RD
- VM10GR
- VM10OR


- 2P+E schuko
 - 16A 250V~, tip VM10
 - ustreza IEC 60884-1, CEE7
 - vijačna pritrditev vodnikov 1.5-2.5 mm²
 - KS vgrajena otroška zaščita pred dotikom kontaktov
- SOCKET SCHUKO+KS 2P+E 16A 250V~ 2M
- 2P+E schuko
 - 16A 250V~, type VM10
 - in accordance with IEC 60884-1, CEE7
 - screw contacts 1.5-2.5 mm²
 - KS build-in child protection - shuttered live contacts



- VM11PT
- VM11BT
- VM11ST
- VM11IT

- 2P+E schuko+pokrov
 - 16A 250V~, tip VM11
 - ustreza IEC 60884-1, CEE7
 - vijačna pritrditev vodnikov 1.5-2.5 mm²
 - KS vgrajena otroška zaščita pred dotikom kontaktov
- SOCKET SCHUKO+KS+COVER
2P+E 16A 250V~ 2M
- 2P+E schuko+cover
 - 16A 250V~, type VM11
 - in accordance with IEC 60884-1, CEE7
 - screw contacts 1.5-2.5 mm²
 - KS build-in child protection - shuttered live contacts





- VM20PW
 VM20SB
 VM20ES
 VM20IW

VTIČNICA EURO+KS 2P 10A 250V~ 1M

- 2P euro
- 10A 250V~, tip VM20
- ustreza IEC 60884-1, CEE7
- vijačna pritrditev vodnikov 1.5-2.5 mm²
- KS vgrajena otroška zaščita pred dotikom kontaktov

SOCKET EURO+KS 2P 10A 250V~ 1M

- 2P Euro
- 10A 250V~, type VM20
- in accordance with IEC 60884-1, CEE7
- screw contacts 1.5-2.5 mm²
- KS build-in child protection - shuttered live contacts




- VM40PW
 VM40SB
 VM40ES
 VM40IW

VTIČNICA FRANCOSKA+KS 2P+E 16A 250V~ 2M

- 2P+E francoska
- 16A 250V~, tip VM40
- ustreza IEC 60884-1, NF C 61-314, CEE7
- vijačna pritrditev vodnikov 1.5-2.5 mm²
- KS vgrajena otroška zaščita pred dotikom kontaktov

SOCKET FRENCH+KS 2P+E 16A 250V~ 2M

- 2P+E French
- 16A 250V~, type VM40
- in accordance with IEC 60884-1, NF C 61-314, CEE7
- screw contacts 1.5-2.5 mm²
- KS build-in child protection - shuttered live contacts



- VM40RD
 VM40GR
 VM40OR

VTIČNICA FRANCOSKA+KS 2P+E 16A 250V~ 2M

- 2P+E francoska
- 16A 250V~, tip VM40
- ustreza IEC 60884-1, NF C 61-314, CEE7
- vijačna pritrditev vodnikov 1.5-2.5 mm²
- KS vgrajena otroška zaščita pred dotikom kontaktov

SOCKET FRENCH+KS 2P+E 16A 250V~ 2M

- 2P+E French
- 16A 250V~, type VM40
- in accordance with IEC 60884-1, NF C 61-314, CEE7
- screw contacts 1.5-2.5 mm²
- KS build-in child protection - shuttered live contacts




- VM41PT
 VM41BT
 VM41ST
 VM41IT

VTIČNICA FRANCOSKA+KS+POKROV 2P+E 16A 250V~ 2M

- 2P+E francoska+pozadina
- 16A 250V~, tip VM41
- ustreza IEC 60884-1, NF C 61-314, CEE7
- vijačna pritrditev vodnikov 1.5-2.5 mm²
- KS vgrajena otroška zaščita pred dotikom kontaktov

SOCKET FRENCH+KS+COVER 2P+E 16A 250V~ 2M

- 2P+E French+cover
- 16A 250V~, type VM41
- in accordance with IEC 60884-1, NF C 61-314, CEE7
- screw contacts 1.5-2.5 mm²
- KS build-in child protection - shuttered live contacts




- VM30PW
 VM30SB
 VM30ES
 VM30IW

VTIČNICA ITALIJANSKA P17/11+KS 2P+E 16A 250V~ 1M

- 2P+E italijanska P17/11
- 16A 250V~, tip VM30
- ustreza IEC 60884-1, CEI 23-50
- vijačna pritrditev vodnikov 1.5-2.5 mm²
- KS vgrajena otroška zaščita pred dotikom kontaktov

SOCKET ITALIAN P17/11+KS 2P+E 16A 250V~ 1M

- 2P+E Italian P17/11
- 16A 250V~, type VM30
- in accordance with IEC 60884-1, CEI 23-50
- screw contacts 1.5-2.5 mm²
- KS build-in child protection - shuttered live contacts



- VM31PW
 VM31SB
 VM31ES
 VM31IW


VTIČNICA SCHUKO/ITA P17/11+KS 2P+E 16A 250V~ 2M

- 2P+E schuko/italijanska P17/11
- 16A 250V~, tip VM31
- ustreza IEC 60884-1, CEI 23-50
- vijačna pritrditev vodnikov 1.5-2.5 mm²
- KS vgrajena otroška zaščita pred dotikom kontaktov

SOCKET SCHUKO/ITA P17/11+KS 2P+E 16A 250V~ 2M

- 2P+E schuko/Italian P17/11
- 16A 250V~, type VM31
- in accordance with IEC 60884-1, CEI 23-50
- screw contacts 1.5-2.5 mm²
- KS build-in child protection - shuttered live contacts





- VM32PW
 VM32SB
 VM32ES
 VM32IW

VTIČNICA SCHUKO/ITA P30+KS 2P+E 16A 250V~ 2M

- 2P+E schuko/italijanska P30
- 16A 250V~, tip VM32
- ustreza IEC 60884-1, CEI 23-50
- vijačna pritrditev vodnikov 1.5-2.5 mm²
- KS vgrajena otroška zaščita pred dotikom kontaktov

SOCKET SCHUKO/ITA P30+KS

2P+E 16A 250V~ 2M

- 2P+E schuko/Italian P30
- 16A 250V~, type VM32
- in accordance with IEC 60884-1, CEI 23-50
- screw contacts 1.5-2.5 mm²
- KS build-in child protection - shuttered live contacts




- VM33PW
 VM33SB
 VM33ES
 VM33IW

VTIČNICA ITALIJANSKA P11+KS 2P+E 10A 250V~ 1M

- 2P+E Italijanska P11
- 10A 250V~, tip VM33
- ustreza IEC 60884-1, CEI 23-50
- vijačna pritrditev vodnikov 1.5-2.5 mm²
- KS vgrajena otroška zaščita pred dotikom kontaktov

SOCKET ITALIAN P11+KS 2P+E 10A 250V~ 1M

- 2P+E Italian P11
- 10A 250V~, type VM33
- in accordance with IEC 60884-1, CEI 23-50
- screw contacts 1.5-2.5 mm²
- KS build-in child protection – shuttered live contacts




- VM21PW
 VM21SB
 VM21ES
 VM21IW

VTIČNICA EURO/AMERIŠKA+KS 2P 16A 250V~ 1M

- 2P euro/ameriška
- 16A 250V~, tip VM21
- vijačna pritrditev vodnikov 1.5-2.5 mm²
- KS vgrajena otroška zaščita pred dotikom kontaktov
- samo za države izven EU

SOCKET EURO/AMERICAN+KS 2P 16A 250V~ 1M

- 2P Euro/American
- 16A 250V~, type VM21
- screw contacts 1.5-2.5 mm²
- KS build-in child protection - shuttered live contacts
- only for countries not members of EU




- VM51PW
 VM51SB
 VM51ES
 VM51IW

VTIČNICA BRITANSKA BS 546+KS 2P+E 15A 250V~ 2M

- 2P+E britanski standard BS 546
- 15A 250V~, tip VM51
- ustreza BS 546
- vijačna pritrditev vodnikov 1.5-4 mm²
- vgrajena zaščita pred dotikom kontaktov

SOCKET BRITISH BS 546+KS 2P+E 15A 250V~ 2M

- 2P+E British BS 546
- 15A 250V~, type VM51
- in accordance with BS 546
- screw contacts 1.5-4 mm²
- KS build-in child protection - shuttered live contacts



- VM52PW
 VM52SB
 VM52ES
 VM52IW

VTIČNICA BRITANSKA BS 1363-2+KS 2P+E 13A 250V~ 2M

- 2P+E britanski standard BS 1363-2
- 13A/250V~, tip VM52
- ustreza BS 1363-2
- vijačna pritrditev vodnikov 1.5-4 mm²
- vgrajena zaščita pred dotikom kontaktov

SOCKET BRITISH BS 1363-2+KS 2P+E 13A 250V~ 2M

- 2P+E British BS 1363-2
- 13A 250V~, type VM52
- in accordance with BS 1363-2
- screw contacts 1.5-4 mm²
- KS build-in child protection - shuttered live contacts




VM80

PRENAPETOSTNA ZAŠČITA MPE MINI 275V/50Hz

- vzporedna vezava s prvo vtičnico v seriji
- razred zaščite III
- $U_c = 275\text{Vac}$, $U_{oc}/I_{sc} = 6\text{kV}/3\text{kA}$, $Up < 800\text{V}$
- ustreza IEC 61643-1
- vodniki 1.5mm², IP20
- zvočni signal ob uničenju

SURGE PROTECTOR MPE MINI 275V/50Hz

- parallel connection with the first socket in the row
- protection class III
- $U_c = 275\text{Vac}$, $U_{oc}/I_{sc} = 6\text{kV}/3\text{kA}$, $Up < 800\text{V}$
- in accordance with IEC 61643-1
- wires 1.5mm², IP20
- sound signal at breakdown



S O C K E T S V M


UJEMANJE VTIČNIC IN VTIČEV
SOCKETS AND PLUGS MATCHING

VTIČNICA / SOCKET	VM10 VM11	VM20	VM30	VM33	VM31	VM32	VM40 VM41	VM21
nemški / German  	•				•	•		
francoski / French  	•				•	•	•	
italijanski / Italian S11  			•	•	•	•		
italijanski / Italian S17  			•		•			
euro  	•	•	•	•	•	•	•	•

UJEMANJE VTIČNIC IN VTIČEV
SOCKETS AND PLUGS MATCHING

VTIČNICA / SOCKET	VM21	VM51	VM52
ameriški / American  	•		
britanski / British BS 546  		•	
britanski / British BS 1363-2  			•


1M = 22,5 x 45
2M = 45 x 45





tip type	naziv description	tehnični opis technical data	velikost size	barva colour
KM10	VTIČNICA TV OSNOVNA SOCKET TV BASIC	0dB	1M	<input type="checkbox"/> PW bela-sijaj polar white
KM11	VTIČNICA TV KONČNA SOCKET TV END-LINE	1dB	1M	<input checked="" type="checkbox"/> SB črna-mat soft touch black
KM12	VTIČNICA TV PREHODNA SOCKET TV TROUHPASS	10dB	1M	<input type="checkbox"/> ES srebrna-mat elox silver
.	.	.	.	<input type="checkbox"/> IW bež-sijaj ivory white
.	.	.	.	

VTIČNICA TV OSNOVNA 0dB 1M




KM10PW
 KM10SB
 KM10ES
 KM10IW

- TV osnovna
 - dušenje 0dB
 - konektor zadaj – F standard
- SOCKET TV BASIC 0dB 1M**
- TV basic
 - reduction 0dB
 - back connector – F standard



VTIČNICA TV OSNOVNA 0dB 2M




KM20PW
 KM20SB
 KM20ES
 KM20IW

- TV osnovna
 - dušenje 0dB
 - konektor zadaj – F standard
- SOCKET TV BASIC 0dB 2M**
- TV basic
 - reduction 0dB
 - back connector – F standard



VTIČNICA TV KONČNA 1dB 1M




KM11PW
 KM11SB
 KM11ES
 KM11IW

Ad: 1dB
24V 500 mA max
IEC 60169-2 male

- TV končna
 - frekvenčni pas 5÷2400 MHz
 - dušenje < 1 dB
 - ustreza EN 50083-1
 - vijačna priključitev
- SOCKET TV END-LINE 1dB 1M**
- TV end-line
 - frequency range 5÷2400 MHz
 - reduction < 1 dB
 - in accordance with EN 50083-1
 - screw contacts



VTIČNICA TV PREHODNA 10dB 1M



KM12PW
 KM12SB
 KM12ES
 KM12IW

Ad: 10dB
IEC 60169-2 male

- TV prehodna
 - frekvenčni pas 5÷2400 MHz
 - dušenje < 10 dB
 - ustreza EN 50083-1
 - vijačna priključitev
- SOCKET TV TROUHPASS 10dB 1M**
- TV troughpass
 - frequency range 5÷2400 MHz
 - reduction < 10 dB
 - in accordance with EN 50083-1
 - screw contacts






- KM15PW
- KM15SB
- KM15ES
- KM15IW

VTIČNICA SAT OSNOVNA 0dB 1M

- SAT osnovna
 - dušenje 0dB
 - konektor zadaj – F standard
- SOCKET SAT BASIC 0dB 1M**
- SAT basic
 - reduction 0dB
 - back connector – F standard



- KM24PW
- KM24SB
- KM24ES
- KM24IW

VTIČNICA SAT OSNOVNA 0dB 2M

- SAT osnovna
 - dušenje 0dB
 - konektor zadaj – F standard
- SOCKET SAT BASIC 0dB 2M**
- SAT basic
 - reduction 0dB
 - back connector – F standard



- KM16PW
 - KM16SB
 - KM16ES
 - KM16IW
- Ad: 1dB
24V 500 mA max
IEC 60169-2 male

VTIČNICA SAT KONČNA 1dB 1M

- SAT končna
- frekvenčni pas 5÷2400 MHz
- dušenje < 1dB
- ustreza EN 50083-1
- vijačna priključitev

- SOCKET SAT END-LINE 1dB 1M**
- SAT end-line
 - frequency range 5÷2400 MHz
 - reduction < 1dB
 - in accordance with EN 50083-1
 - screw contacts




- KM19PW
- KM19SB
- KM19ES
- KM19IW

VTIČNICA R OSNOVNA 0dB 1M

- R osnovna
- dušenje 0dB
- konektor zadaj – F standard

- SOCKET R BASIC 0dB 1M**
- R basic
 - reduction 0dB
 - back connector – F standard




- KM29PW
- KM29SB
- KM29ES
- KM29IW

VTIČNICA R OSNOVNA 0dB 2M

- R osnovna
- dušenje 0dB
- konektor zadaj – F standard

- SOCKET R BASIC 0dB 2M**
- R basic
 - reduction 0dB
 - back connector – F standard




- KM25PW
- KM25SB
- KM25ES
- KM25IW

VTIČNICA SAT-TV KONČNA 1dB 2M

- SAT-TV končna
- frekvenčni pas 5÷2400 MHz
- dušenje < 1dB
- ustreza EN 50083-1
- vijačna priključitev


- SOCKET SAT-TV END-LINE 1dB 2M**
- SAT-TV end-line
 - frequency range 5÷2400 MHz
 - reduction < 1dB
 - in accordance with EN 50083-1
 - screw contacts



OSNOVNE VEZALNE SHEME


BASIC CONNECTION SAMPLES

samostojna vezava
stand alone connection




KM10
KM20
KM11
KM15
KM24
KM16
KM19
KM29
KM25

zvezda vezava
star connection



KM10
KM20
KM11
KM15
KM24
KM16
KM19
KM29
KM25

prehodna vezava
throughpass connection



KM12 KM11

VTIČNICA AVUDIO 2xRCA 1M



- KM22PW
- KM22SB
- KM22ES
- KM22IW

SOCKET AUDIO 2xRCA 1M

- avdio 2x RCA
- pritrđitev vodnikov zadaj s spajkanjem
- audio 2x RCA
- soldering connection of cable at the back side



VTIČNICA AVUDIO ZVOČNIŠKA 1M



- KM23PW
- KM23SB
- KM23ES
- KM23IW

SOCKET AUDIO LOUDSPEAKERS 1M

- avdio 2x Ø4mm
- za priklop zvočniškega vodnika, vtiča Ø4mm ali viličastega kabel čevlja
- pritrđitev vodnikov zadaj s spajkanjem
- audio 2x Ø4mm
- to accommodate speaker wire, banana plug Ø4mm or spades
- soldering connection of cable at the back side



VTIČNICA AVUDIO ZVOČNIŠKA 2M




- KM26PW
- KM26SB
- KM26ES
- KM26IW

SOCKET AUDIO LOUDSPEAKERS 2M


- avdio 2x Ø4mm
- za priklop zvočniškega vodnika, vtiča Ø4mm ali viličastega kabel čevlja
- pritrđitev vodnikov zadaj s spajkanjem
- audio 2x Ø4mm
- to accommodate speaker wire, banana plug Ø4mm or spades
- soldering connection of cable at the back side




1M = 22,5 x 45
2M = 45 x 45




KM10
KM11
KM12




KM16




KM19




KM22
KM23



KM25



KM20
KM24
KM26




KM30PW
 KM30SB
 KM30ES
 KM30IW

VTIČNICA TEL LT RJ11 6/4 1M

- TEL LT vijak
- RJ11 6/4
- ustreza IEC 60603-7
- vijačna pritrditev vodnikov

SOCKET TEL LT RJ11 6/4 1M

- TEL LT screw
- RJ11 6/4
- in accordance with IEC 60603-7
- screw contacts




KM31PW
 KM31SB
 KM31ES
 KM31IW

VTIČNICA TEL BT SEC 6/6 1M

- TEL BT britanski standard
- SEC sekundarna 6/6
- ustreza BS 6312
- vijačna pritrditev vodnikov

SOCKET TEL BT SEC 6/6 1M

- TEL BT British standard
- SEC secondary 6/6
- in accordance with BS 6312
- screw contacts




KM36PW
 KM36SB
 KM36ES
 KM36IW

VTIČNICA TEL KS RJ11 6/4 1M

- KS keystone pritrditveni standard
- RJ11 6/4
- ustreza IEC 60603-7

SOCKET TEL KS RJ11 6/4 1M

- KS keystone fixing standard
- RJ11 6/4
- in accordance with IEC 60603-7




KM37PW
 KM37SB
 KM37ES
 KM37IW

VTIČNICA CAT5e KS RJ45 8/8 1M

- KS keystone pritrditveni standard
- CAT5e, RJ45 8/8
- ustreza IEC 60603-7

SOCKET CAT5e KS RJ45 8/8 1M

- KS keystone fixing standard
- CAT5e, RJ45 8/8
- in accordance with IEC 60603-7




KM35PW
 KM35SB
 KM35ES
 KM35IW

ADAPTER KS 1M

- KS keystone pritrditveni standard
- AMP, Avaya, Brandrex, FMT, Mfico, Tyco, ...
- komunikacijski modul ni vgrajen

ADAPTER KS 1M

- KS keystone fixing standard
- AMP, Avaya, Brandrex, FMT, Mfico, Tyco, ...
- communication module not included



KM38PW
 KM38SB
 KM38ES
 KM38IW


ADAPTER KS S PRAŠNO ZAŠČITO 1M

- KS keystone pritrditveni standard s protipašnim pokrovom
- AMP, Avaya, Brandrex, FMT, Mfico, Tyco, ...
- komunikacijski modul ni vgrajen

ADAPTER KS WITH DUST PROTECTION 1M

- KS keystone fixing standard with dust protection
- AMP, Avaya, Brandrex, FMT, Mfico, Tyco, ...
- communication module not included






- KM39PW
- KM39SB
- KM39ES
- KM39IW

VTIČNICA CAT6 SCH KS RJ45 8/8 1M

- KS keystone pritrditveni standard
 - CAT6 UTP toolless, RJ45 8/8
 - ustreza ISO/IEC 11801
- SOCKET CAT6 SCH KS RJ45 8/8 1M**
- KS keystone fixing standard
 - CAT6 UTP toolless, RJ45 8/8
 - in accordance with ISO/IEC 11801




- KM50PW
- KM50SB
- KM50ES
- KM50IW

ADAPTER KS UNIVERZALNI 1M

- KS keystone pritrditveni standard
- primeren za HDMI, USB
- komunikacijski modul ni vgrajen

ADAPTER KS UNIVERSAL 1M

- KS keystone fixing standard
- suitable for HDMI, USB
- communication module not included




- KM40PW
- KM40SB
- KM40ES
- KM40IW

ADAPTER PD 1M

- PD Panduit Mini-COM pritrditveni standard
- komunikacijski modul ni vgrajen

ADAPTER PD 1M

- PD Panduit Mini-COM fixing standard
- communication module not included




- KM43PW
- KM43SB
- KM43ES
- KM43IW

ADAPTER PD S PRAŠNO ZAŠČITO 1M

- PD Panduit Mini-COM pritrditveni standard s protiprašnim pokrovom
- komunikacijski modul ni vgrajen

ADAPTER PD WITH DUST PROTECTION 1M

- PD Panduit Mini-COM fixing standard with dust protection
- communication module not included



- KM46PW
- KM46SB
- KM46ES
- KM46IW

ADAPTER R&M 1M

- R&M pritrditveni standard
- komunikacijski modul ni vgrajen

ADAPTER R&M 1M

- R&M fixing standard
- communication module not included



- KM47PW
- KM47SB
- KM47ES
- KM47IW


ADAPTER R&M S PRAŠNO ZAŠČITO 1M

- R&M pritrditveni standard s protiprašnim pokrovom
- komunikacijski modul ni vgrajen

ADAPTER R&M WITH DUST PROTECTION 1M

- R&M fixing standard with dust protection
- communication module not included



**ADAPTER LK 1M**

- KM45PW
- KM45SB
- KM45ES
- KM45IW

- LK LeoniKerpen eLine / BKS NewLine pritrditveni strandard
- komunikacijski modul ni vgrajen

ADAPTER LK 1M

- LK LeoniKerpen eLine / BKS NewLine fixing standard
- communication module not included





KA26

ADAPTER NEXANS/SCHRACK 2M

- adapter za pritrditev modulov Nexans LANmark in Schrack velikosti 45x45mm
- primerena za Nexans tip N423.540N
- primeren za Schrack tip HSEMD02W2F
- komunikacijski modul ni vgrajen

ADAPTER NEXANS/SCHRACK 2M

- fixing adapter for Nexans LANmark and Schrack module 45x45mm
- suitable for Nexans type N423.540N
- suitable for Schrack type HSEMD02W2F
- communication module not included



- KM48PW
- KM48SB
- KM48ES
- KM48IW

ADAPTER AT&T SYSTIMAX S PRAŠNO ZAŠČITO 1M

- AT&T Systimax pritrditveni standard s protipašnim pokrovom
- komunikacijski modul ni vgrajen

ADAPTER AT&T SYSTIMAX WITH DUST PROTECTION 1M

- AT&T Systimax fixing standard with dust protection
- communication module not included



- KM51PW
- KM51SB
- KM51ES
- KM51IW


VTIČNICA USB TIP A 1M

- USB 2.0 vtičnica tip A
- vijačna pritrditev vodnikov, raster 5 mm, 1,5 mm2, 1x2P + 1x3P
- ozičenje:
PIN 1 – VCC (+5V, rdeča žica)
PIN 2 – signal - (bela žica)
PIN 3 – signal + (zelená žica)
PIN 4 – GND - masa (črna žica)
S – oklop
- ustreza direktivi 2011/95/EU (RoHS2)


**SOCKET USB TYPE A 1M**

- USB 2.0 socket type A
- screw contacts, raster 5 mm, 1,5 mm², 1x2P + 1x3P
- wiring:
PIN 1 – VCC (+5V, red wire)
PIN 2 – Data - (white wire)
PIN 3 – Data + (green wire)
PIN 4 – GND - ground (black wire)
S – shield
- in accordance with directive 2011/95/EU (RoHS2)





1M = 22,5 x 45
2M = 45 x 45





KM30



KM31

KM35
KM38
KM48KM36
KM37
KM39KM40
KM43

KM45

KM46
KM47
KM50

KM51



KA10

tip type	naziv description	tehnični opis technical data
KA10	KONEKTOR KS CAT3 CONNECTOR KS CAT3	RJ11 6/4
KA11	KONEKTOR KS CAT5e CONNECTOR KS CAT5e	RJ45 8/8
KA12	KONEKTOR KS CAT5eS CONNECTOR KS CAT5eS	RJ45 8/8

KONEKTOR KS CAT3 RJ11 6/4

KA10

- KS keystone pritrditveni standard
- CAT3, RJ11 6/4
- ustreza IEC 60603-7

CONNECTOR KS CAT3 RJ11 6/4
*- KS keystone fixing standard
- CAT3, RJ11 6/4
- in accordance with IEC 60603-7*

KONEKTOR KS CAT5e RJ45 8/8

KA11

- KS keystone pritrditveni standard
- CAT5e, RJ45 8/8
- ustreza IEC 60603-7

CONNECTOR KS CAT5e RJ45 8/8
*- KS keystone fixing standard
- CAT5e, RJ45 8/8
- in accordance with IEC 60603-7*

KONEKTOR KS CAT5eS RJ45 8/8

KA12

- KS keystone pritrditveni standard
- CAT5eS, RJ45 8/8
- ustreza IEC 60603-7

CONNECTOR KS CAT5eS RJ45 8/8
*- KS keystone fixing standard
- CAT5eS, RJ45 8/8
- in accordance with IEC 60603-7*

KONEKTOR KS CAT6 SCH RJ45 8/8

KA15

- KS keystone pritrditveni standard
- CAT6 UTP toolless, RJ45 8/8
- ustreza ISO/IEC 11801

CONNECTOR KS CAT6 SCH RJ45 8/8
*- KS keystone fixing standard
- CAT6 UTP toolless, RJ45 8/8
- in accordance with ISO/IEC 11801*

KONEKTOR KS CAT6S SCH RJ45 8/8

KA16

- KS keystone pritrditveni standard
- CAT6S STP toolless, RJ45 8/8
- ustreza ISO/IEC 11801

CONNECTOR KS CAT6S SCH RJ45 8/8
*- KS keystone fixing standard
- CAT6S STP toolless, RJ45 8/8
- in accordance with ISO/IEC 11801*

KONEKTOR KS CAT6a SCH RJ45 8/8

KA17

- KS keystone pritrditveni standard
- CAT6a STP toolless, RJ45 8/8
- ustreza ISO/IEC 11801

CONNECTOR KS CAT6a SCH RJ45 8/8
*- KS keystone fixing standard
- CAT6a STP toolless, RJ45 8/8
- in accordance with ISO/IEC 11801*



KA18

KONEKTOR SLIM KS CAT6S SCH RJ45 8/8

- KS keystone pritrditveni standard
- slim verzija
- CAT6S STP toolless, RJ45 8/8
- ustreza ISO/IEC 11801
- primeren tudi za dvojni adapter KE46

CONNECTOR SLIM KS CAT6S SCH RJ45 8/8

- KS keystone fixing standard
- slim style
- CAT6S STP toolless, RJ45 8/8
- in accordance with ISO/IEC 11801
- suitable also for KE46 double adapter



KA27

KONEKTOR KS HDMI

- KS keystone pritrditveni standard
- samo v kombinaciji z adapterjem KM50
- HDMI/HDMI

CONNECTOR KS HDMI

- KS keystone fixing standard
- only in combination with adapter KM50
- HDMI/HDMI



EM31



PW



Make up Room!
Do not Disturb!

tip type	naziv description	tehnični opis technical data	velikost size	barva colour
EM10	ZATEMNILNIK ROTACIJSKI DIMMER ROTATIVE	R 300W	1M	<input type="checkbox"/> PW bela-sijaj polar white
EM12	ZATEMNILNIK ROTACIJSKI MENJALNI DIMMER ROTATIVE 2WAY	RL 300W	1M	<input checked="" type="checkbox"/> SB črna-mat soft touch black
EM21	ZATEMNILNIK VGRADNI DIMMER INBOX	RLC 300W	/	<input type="checkbox"/> ES srebrna-mat elox silver
.	.	.	.	<input type="checkbox"/> IW bež-sijaj ivory white
.	.	.	.	<input type="checkbox"/> BL modra blue
.	.	.	.	<input type="checkbox"/> RD rdeča red
.	.	.	.	<input type="checkbox"/> GR zelena green
.	.	.	.	<input type="checkbox"/> OR oranžna orange
.	.	.	.	<input type="checkbox"/> RG rdeča/zelena red/green

ZATEMNILNIK ROTACIJSKI R 300W 1M



- EM10PW
- EM10SB
- EM10ES
- EM10IW

- rotacijski brez stikala
- tip RTS34.43 RVP, breme R, 40W - 300W
- napajanje 230V~ 50Hz
- vezava z menjalnim stikalom ni možna
- vezava večih zatemnilnikov ni dovoljena
- ustreza EN 60669-1
- vijačna pritrditev vodnikov 1.5-2.5 mm²
- LED indikacija

DIMMER ROTATIVE R 300W 1M

- rotation control without switch
- type RTS34.43 RVP, load R, 40W - 300W
- supply voltage 230V~ 50Hz
- 2-way switch combination is not possible
- more dimmers combination is not allowed
- in accordance with EN 60669-1
- screw contacts 1.5-2.5mm²
- LED indication



ZATEMNILNIK ROTACIJSKI/MENJALNI RL 300 W 1M



- EM12PW
- EM12SB
- EM12ES
- EM12IW

- rotacijski z menjalnimi stikaloma
- breme RL, 40W - 300W
- napajanje 230V~ 50Hz
- možna vezava z menjalnimi stikaloma
- montaža več naprav skupaj v eno dozo dovoljena samo pod pogojem, da njihovo skupno maksimalno breme ne presega maksimalne moči enega zatemnilnika
- v istem tokokrogu je dovoljena uporaba samo enega zatemnilnega stikala
- varovalka ni vgrajena – potrebna vezava zunanjne varovalke
- ustreza EN 60669-1
- vijačni kontakti - 1.5-2.5mm²
- vgrajena LED indikacija stopnje zatemnitve



DIMMER ROTATIVE/2WAY RL 300W 1M

- rotation control with 2-way switch
- load RL, 40W - 300W
- supply voltage 230V~ 50Hz
- 2-way switch combination is possible
- installing several devices together in one box is only permitted if their total maximum load does not exceed the maximum power of a single dimmer
- one circuit allows the use of only one dimmer
- no built-in fuse – external fuse must be used
- in accordance with EN 60669-1
- screw contacts - 1.5-2.5mm²
- integrated LED indication of dimming level



- EM13PW
- EM13SB
- EM13ES
- EM13IW

ZATEMNLNIK ROTACIJSKI/MENJALNI LED 60 W 1M

- rotacijski z menjalnim stikalom
- bremena: LED, 0 – 60 W (max. 6 LED zatemnilnih sijalk)
GLS, 0 – 60 W
- napajanje 230V~ 50Hz
- možna vezava z menjalnim stikalom
- montaža več naprav skupaj v eno dozo dovoljena samo pod pogojem, da njihovo skupno maksimalno breme ne presega maksimalne moči enega zatemnilnika
- v sistem tokokrogu je dovoljena uporaba samo enega zatemnilnega stikala
- varovalka ni vgrajena – potrebna vezava zunanje varovalke
- ustrezza IEC60669-2-1
- vijačni kontakti - 1.5–2.5mm²



- EM14PW
- EM14SB
- EM14ES
- EM14IW

ZATEMNLNIK ROTACIJSKI/MENJALNI LED 180 W 1M

- rotacijski z menjalnim stikalom
- bremena:
 - LED, 0 – 180 W (max. 20 LED zatemnilnih sijalk)
GLS, 0 – 180 W
- napajanje 230V~ 50Hz
- možna vezava z menjalnim stikalom
- montaža več naprav skupaj v eno dozo dovoljena samo pod pogojem, da njihovo skupno maksimalno breme ne presega maksimalne moči enega zatemnilnika
- v sistem tokokrogu je dovoljena uporaba samo enega zatemnilnega stikala
- varovalka ni vgrajena – potrebna vezava zunanje varovalke
- ustrezza IEC60669-2-1
- vijačni kontakti - 1.5–2.5mm²



DIMMER ROTATIVE/2WAY LED 180W 1M

- rotation control with 2-way switch
- loads:
 - LED, 0 – 180W (max. 20 dimmable LED lamps)
GLS, 0 – 180W
- supply voltage 230V~ 50Hz
- 2-way switch combination is possible
- installing several devices together in one box is only permitted if their total maximum load does not exceed the maximum power of a single dimmer
- one circuit allows the use of only one dimmer
- no built-in fuse – external fuse must be used
- in accordance with IEC60669-2-1
- screw contacts - 1.5–2.5mm²



EM21

ZATEMNLNIK VGRADNI RLC 300W

- vgradni, za vezavo s tipkalom
- tip RHUN, breme RLC, 25W - 300W ali 25VA - 250VA
- napajanje 230V~ 50Hz
- možna vezava z več tipkali
- vezava večih zatemnilišnikov ni dovoljena
- vgrajena spominska funkcija
- funkcija mehkega vklopa / izklopa
- ustreza EN 61058-1
- vodniki 1.5mm²

**DIMMER INBOX RLC 300W**

- inbox, controlled by external push button
- type RHUN, load RLC, 25W - 300W or 25VA - 250VA
- supply voltage 230V~ 50Hz
- several push-buttons combination is possible
- more dimmers combination is not allowed
- light intensity memory
- soft start / stop function
- in accordance with EN 61058-1
- wires 1.5mm²



EM22


ZATEMNLNIK VGRADNI R 500W

- vgradni, za vezavo s tipkalom
- tip RTL500UN, breme R, 40W - 500W
- napajanje 230V~ 50Hz
- možna vezava z več tipkali
- vezava večih zatemnilišnikov ni dovoljena
- vgrajena spominska funkcija
- funkcija mehkega vklopa / izklopa
- ustreza EN 61058-1
- vijačna pritridlev vodnikov 1.5-2.5mm²


**DIMMER INBOX R 500W**

- inbox, controlled by external push button
- type RTL500UN, load R, 40W - 500W
- supply voltage 230V~ 50Hz
- several push-buttons combination is possible
- more dimmers combination is not allowed
- light intensity memory
- soft start / stop function
- in accordance with EN 61058-1
- screw contacts 1.5-2.5mm²


EM10 (40÷300W),
EM22 (40÷500W)



EM12 (40÷300W)



EM13 (0÷60W), EM14 (0÷180W),
EM21 (25÷300W, 25÷250VA)













1 - žarnica z žarilno nitko /
incandescent lamp

2 - halogenska žarnica /
halogen lamp

3 - klasični transformator /
classical transformer

4 - elektronski transformator /
electronic transformer





POZOR!

V primeru montaže več zatemnilnih stikal v isto dozo se za vsako dodatno zatemnilno stikalo zmanjša maksimalna skupna moč za 10%.

ATTENTION!

If more dimmers are connected in one box reduce maximum common power for 10% for each dimmer.





□ EM25PW
■ EM25SB
□ EM25ES
■ EM25IW

TOUCH EM25 je mikroprocesorsko voden elektronski zatemnilnik. Omogoča vklop, izklop in zatemnjevanje vseh zatemnilnih žarnic in nekaterih nezatemnilnih žarnic in sijalk. Vgrajeni mikroprocesor samodejno zazna vrsto sijalke in prilagodi režim delovanja. Ob izklopu si zapomni zadnjo nastavitev, saj ima vgrajeno spominško funkcijo. Funkcija mehkega zagona podaljša življenjsko dobo sijalk. V tipku je vgrajena elegantna LED osvetlitev, z možnostjo izbiре barve in nastavitev jakosti. Na EM25 lahko vežemo do 5 dodatnih upravljalnih tipkal EM26 (»slave«).

TOUCH EM25 is microprocessor controlled electronic light dimmer. It serves as switch and dimmer for dimmable and some of no-dimmable lamps. Integrated microprocessor automatically identifies the type of lamp and adjusts the operating mode. It remembers the level of dimming after switching off due to integrated memory function. Soft-start function extends the lamp service life. In button integrated elegant LED illumination enables many different colors and intensity levels. Optionally one can connect of up to 5 additional control tasters EM26 (»slave«).

STIKALO / ZATEMNILNIK UNIVERZALNI RLC 0-300W 2M


- univerzalni elektronski zatemnilnik za vklop, izklop in zatemnjevanje vseh zatemnilnih žarnic in sijalk (klasične, halogenske, LED, CFL, ...) in nekaterih nezatemnilnih sijalk
- samodejno zazna vrsto sijalke in temu prilagodi režim delovanja
- z zatemnjevanjem se zmanjša poraba električne energije
- funkcija mehkega zagona podaljša življenjsko dobo sijalk
- upravljanje preko vgrajenih mikro-stikal
- vgrajena spominška funkcija - ob izklopu si zapomni nivo zatemnitve
- možna vezava do pet (5) dodatnih upravljalnih tipkal EM26
- vezava z menjalnimi stikali ni možna
- vgrajene zaščite pred kratkim stiskom, pregrevanjem in preobremenitvijo
- napajanje 230V~ 50Hz
- vgrajena elegantna LED osvetlitev, z možnostjo nastavitev barve in jakosti
- omogoča zamenjavo klasičnega stikala – dvožična vezava⁽¹⁾
- s trožično vezavo dosežemo polno funkcionalnost zatemnilnika⁽²⁾
- ustreza EN 60669-1 in EN 60669-2-1
- vijačna pritrivitev vodnikov 1.5mm² (maks. moment privitja vijakov 0,4 Nm)



SWITCH / DIMMER UNIVERSAL RLC 0-300W 2M

- universal electronic dimmer for ON/OFF switching and dimming of all dimmable lamps (classical, halogen, LED, CFL, ...) and some no-dimmable lamps
- automatic detection of lamp type and adjustment of operating mode
- reduction of energy consumption
- soft start function extends life of lamps
- controlled by build-in micro switches
- memory function included – memorizes brightness on turn-off
- up to five (5) additional control units EM26 can be connected
- connection with 2-way switch is not possible
- build-in short-circuit, overheating and overload protection
- supply voltage 230V~ 50Hz
- elegant LED illumination, adjustable colour and brightness
- replacement of classical switch is possible at two-wire connection⁽¹⁾
- full functionality is achieved at three-wire connection⁽²⁾
- in accordance with EN 60669-1 and EN 60669-2-1
- screw contacts 1.5mm² (max. tightening torque 0.4Nm)


⁽¹⁾dvožična vezava
two-wire connection



- dvožična vezava omogoča zatemnjevanje zatemnilnih žarnic in sijalk

- two-wire connection allows dimming of dimmable lamps

⁽²⁾trožična vezava
three-wire connection



- trožična vezava omogoča zatemnjevanje zatemnilnih žarnic in sijalk in nekaterih nezatemnilnih LED in CFL sijalk

- three-wire connection allows dimming of dimmable lamps and some of no-dimmable LED and CFL lamps

	12		5	6	7
Min. Max.	40 W 300 W	40 W 300 W	40 VA 300 VA	40 VA 100 VA	40 VA 100 VA

1 - žarnica z žarilno nitko /
incandescent lamp

2 - halogenska žarnica /
halogen lamp

4 - elektronski transformator /
electronic transformer

5 - klasični transformator /
classical transformer

	12		4	6	7	8	9
Min. Max.	0 W 300 W	0 W 300 W	0 VA 120 VA				

6 - zatemnilna varčna CFL sijalka /
dimmable energy saving CFL lamp

7 - zatemnilna LED sijalka /
dimmable LED lamp

8 - nezatemnilna varčna CFL sijalka /
no-dimmable energy saving CFL lamp

9 - nezatemnilna LED sijalka /
no-dimmable LED lamp


opombe /
remarks

- (F) filter EM27
- priporočamo uporabo filtra EM27 /
it is recommended to use filter EM27

- vse krmiljene žarnice in sijalke morajo biti enake /
all controlled lamps must be the same

- tabela bremen velja za sijalke s faktorjem PF>0.5 /
table of loads is valid for lamps with power factor PF>0.5

vklop in izklop ter zatemnjevanje luči /
on / off switching and dimming of lamp



vklop / izklop
kratki pritisk
on / off
short press

izberi barve in nastavitev jakosti LED osvetlitve /
LED colour selection and intensity level adjustment




izklop luči
kratki pritisk
lamp off
short press

*funkcija "RESET" /
"RESET" function




izklop luči
kratki pritisk
lamp off
short press

osvetljevanje
daljši pritisk
dimming up
long press



osvetljevanje
daljši pritisk
dimming up
long press



hkratni pritisk ~3s
vgrajena lučka 3x utripne
simultaneous press ~3s
integrated LED blinks 3 times

hkratni pritisk ~3s
vgrajena lučka 3x utripne
simultaneous press ~3s
integrated LED blinks 3 times

zatemnjevanje
daljši pritisk
dimming down
long press



zatemnjevanje
daljši pritisk
dimming down
long press



izberi barve
kratki pritisk
colour selection
short press

ponovni hkratni pritisk ~5s
vgrajena lučka 5x utripne
re-simultaneous press ~5s
integrated LED blinks 5 times

osvetljevanje vgrajene LED
daljši pritisk
integrated LED dimming up
long press




osvetljevanje vgrajene LED
daljši pritisk
integrated LED dimming up
long press

zatemnjevanje vgrajene LED
daljši pritisk
integrated LED dimming down
long press







zatemnjevanje vgrajene LED
daljši pritisk
integrated LED dimming down
long press




shranitev nastavitev - hkratni kratek pritisk
vgrajena lučka 3x utripne
settings saving - simultaneous short press
integrated LED blinks 3 times

- * - priporočamo ob vgradnji zatemnilnika in menjavi žarnic ali sijalk
- obvezno ob uporabi nezatemnilnih sijalk
- funkcija "RESET" pri uporabi dvožične vezave ne deluje
- možno samo pri EM25
- it is recommended at dimmer installation and lamp replacement
- mandatory when using no-dimmable lamps
- "RESET" function is not possible when using two-wire connection
- only possible on EM25

opozorila za vgradnjo /
installation precautions



pri montaži ne pritiskej na tipko /
do not push on button during mounting



- EM26PW
- EM26SB
- EM26ES
- EM26IW

TIPKALO UPRAVLJALNO 2M


- v povezavi z univerzalnim zatemnilnikom EM25 omogoča upravljanje luči z več (do pet) lokacij z enako funkcionalnostjo kot EM25
- napajanje 230V~ 50Hz
- ustreza EN 60669-1 in EN 60669-2-1
- vijačna pritridlev vodnikov 1.5mm² (maks. moment privitja vijakov 0,4 Nm)



PUSH-BUTTON CONTROL UNIT 2M


- connected to universal dimmer EM25 allows controlling of lamps with same functionality as EM25
- supply voltage 230V~ 50Hz
- in accordance with EN 60669-1 and EN 60669-2-1
- screw contacts 1.5mm² (max. tightening torque 0.4Nm)

(1) dvožična vezava
two-wire connection



- dvožična vezava omogoča zatemnjevanje zatemnilnih žarnic in sijalk
- pri dvožični vezavi uporaba vsakega dodatnega upravljalnega tipkala poveča minimalno moč bremena za 25W
- two-wire connection allows dimming of dimmable lamps
- in a two-wire connection each additional control unit increases the minimum load by 25W

(2) trožična vezava
three-wire connection



- trožična vezava omogoča zatemnjevanje zatemnilnih žarnic in sijalk in nekaterih nezatemnilnih LED in CFL sijalk
- three-wire connection allows dimming of dimmable lamps and some of non-dimmable LED and CFL lamps




EM27

FILTER OMREŽNIH MOTENJ

- filter frekvenčnih motenj za EM25
- slika je simbolična

FREQUENCY FILTER

- frequency filter for EM25
- image is symbolic



SET STIKALO / ZATEMNILNIK UNIVERZALNI RLC 0-300W 2M PP OL20

- EM25PPOL20




- set vsebuje zatemnilnik EM25, nosilec 2M in okvir LINE 2M PW
- za tehnični opis glej EM25

SET SWITCH / DIMMER UNIVERSAL RLC 0-300W 2M PP OL20

- set includes dimmer EM25, mounting frame 2M and cover plate LINE 2M PW
- for technical details see EM25



2M = 45 x 45





- EM31PW
- EM31SB
- EM31ES
- EM31IW

IR STIKALO 5A 230V~ 1M

- IR infrardečé stikalo
- napajanje: 230V~ ±10 % 50Hz
- rele: 5A / 250V~ izhod za omejen tok z visokim uporom za zero crossing
- stopnja varnosti: IP40
- presek žic pri stičniku: 0,75 - 2,5 mm²
- kot zaznavanja: do 110° pri 20°C
- območje zaznavanja: približno 8 m pri 20°C
- nastavljivost časovnega trajanja: od približno 5 s do 12 min
- nastavljivost osvetlitve: od približno 5 do 200 LUX
- temperatura delovanja: od 0°C do +40°C
- ni primeren za vgradnjo v doze, globine 45 mm in ohišja CUBO IP20
- samo za notranjo uporabo



IR SWITCH 5A 230V~ 1M

- IR infrared switch
- supply voltage: 230V~ ±10 % 50Hz
- relay: 5A / 250V~ output for limited current with high resistance for zero crossing
- protection rating: IP40
- cross-section of wires at the contact terminal: 0.75 - 2.5 mm²
- detection angle: up to 110° at 20°C
- detection area: approx. 8 m at 20°C
- adjustability of duration: from approx. 5 s to 12 min
- adjustability of brightness: from approx. 5 to 200 LUX
- operating temperature: from 0°C to +40°C
- not suitable for installation in 45 mm deep boxes and surface mount box CUBO IP20
- only for indoor usage



- EM32PW
- EM32SB
- EM32ES
- EM32IW

IR STIKALO 5A 230V~ 2M




- IR infrardečé stikalo
- napajanje: 230V~ ±10 % 50Hz
- rele: 5A / 250V~ izhod za omejen tok z visokim uporom za zero crossing
- stopnja varnosti: IP40
- presek žic pri stičniku: 0,75 - 2,5 mm²
- kot zaznavanja: do 110° pri 20°C
- območje zaznavanja: približno 8 m pri 20°C
- nastavljivost časovnega trajanja: od približno 5 s do 12 min
- nastavljivost osvetlitve: od približno 5 do 200 LUX
- temperatura delovanja: od 0°C do +40°C
- ni primeren za vgradnjo v doze, globine 45 mm in ohišja CUBO IP20
- samo za notranjo uporabo




IR SWITCH 5A 230V~ 2M

- IR infrared switch
- supply voltage: 230V~ ±10 % 50Hz
- relay: 5A / 250V~ output for limited current with high resistance for zero crossing
- protection rating: IP40
- cross-section of wires at the contact terminal: 0.75 - 2.5 mm²
- detection angle: up to 110° at 20°C
- detection area: approx. 8 m at 20°C
- adjustability of duration: from approx. 5 s to 12 min
- adjustability of brightness: from approx. 5 to 200 LUX
- operating temperature: from 0°C to +40°C
- not suitable for installation in 45 mm deep boxes and surface mount box CUBO IP20
- only for indoor usage

območje zaznavanja /
detection range



nastavitev občutljivosti in časa osvetlitve /
time and twilight adjustment



	5 LUX	200 LUX
	~5 s	~12 min

	1	2	3	4	5	6	7	8
Min.	1 W	1 W			1 W	1 W	1 VA	1 VA
Max.	800 W	800 W			6x36 W	4x36 W (20μF)	6x23 VA	6x20 VA

1 - žarnica z žarilno nitko /
incandescent lamp

2 - halogenska žarnica /
halogen lamp

3 - uporovno grelno telo /
resistive heating element

4 - elektronski transformator /
electronic transformer


5 - fluorescentna cev (izvedba 1) /
fluorescent tube (version 1)

6 - fluorescentna cev (izvedba 2) /
fluorescent tube (version 2)


7 - varčna CFL sijalka /
energy saving CFL lamp

8 - LED sijalka /
LED lamp

opozorila /
attention



1M = 22,5 x 45





□ EM37PW
■ EM37SB
▢ EM37ES
▢ EM37IW


TERMOSTAT OSNOVNI 6A 230V~ 2M

- termostat elektronski osnovni
- način delovanja: ogrevanje / hlajenje / izklop
- napajanje: 230 VAC, 50 Hz
- izhod: 6(2) A, 230 VAC, preklopni rele
- območje regulacije: +10 °C do +30 °C
- histerezis: ±0,5 °C, ED = 20min
- zaščita proti zmrzovanju (način ogrevanja): +6 °C
- zaščita proti pregrevanju (način hlajenja): +32 °C
- funkcija ECO za znižanje temperature za 3 °C za 6 ur v načinu ogrevanje in povečanje temperature za 3 °C za 6 ur v načinu hlajenje
- funkcija adaptivni ECO, avtomatsko vsak dan ob istem času zniža temperaturo za 3 °C za 6 ur v načinu ogrevanje in poveča temperaturo za 3 °C za 6 ur v načinu hlajenje
- možnost vklopa ECO režima delovanja z zunanjim proženjem preko ločenega vhoda
- LED indikacija delovanja
- ni primeren za električno talno ogrevanje
- višjačna pritrditev vodnikov max. 2,5 mm²
- ustreza LV Direktivi, EMC direktivi, standardi EN60730-1 in EN60730-2-9
- za pravilno delovanje, priporočamo vgradnjo v samostojno dozo, ločeno od naprav, ki generirajo topilo
- temperatura uporabe: 5 °C do 35 °C
- temperatura skladiščenja: -20 °C do 50 °C




Termostat je namenjen regulirjanju temperature v prostoru. Termostat omogoča dva načina delovanja – ogrevanje ali hlajenje. Vgrajene ima varovalne funkcije zaščito proti zmrzovanju (način ogrevanja) in zaščito proti pregrevanju (način hlajenja). Delovanje se signalizira s pomočjo LED lučk. Nastavljanje termostata se vrši s pomočjo rotacijskega gumba za nastavitev temperature in kapacitivnih tipk na dotik.

The thermostat is intended for regulating temperature in a room. A thermostat enables two modes of operation – heating or cooling. It has safety functions installed for protection against freezing (heating mode) and protection against overheating (cooling mode). The operation is indicated via LED lights. Thermostat setup is performed with the help of a rotary button for setting the temperature and with other capacitive touch buttons.



obtočna črpalka, gorilnik (direktna priključitev), termoelektrični pogon /

circulation pump, burner (direct connection)
thermoelectric drive



kotel, toplotna črpalka, gorilnik (krnilni vhod T1/T2) /
boiler, heat pump, burner (control input T1/T2)

nastavitev delovanja in temperature /
function and temperature adjustment

tipka za izbiro delovanja in
LED indikator stanja:
rdeča: ogrevanje
modra: hlajenje
ne svetli: izklopljeno

function selection button and
LED status indicator:
red: heating
blue: air conditioning
no light: switched off

nastavitev temperature
temperature setting





tipka za izbiro "ECO" režima in
LED indikator "ECO" režima
zelen: ECO režim vklopljen
oranžna: adaptivni ECO aktiviran
ne svetli: dnevni režim

"ECO" function selection button and
LED "ECO" status indicator
green: ECO energy saving ON
orange: adaptive ECO mode activated
no light: day mode

LED indikator stanja izhodnega releja
bel: rele vklopljen
ne svetli: rele izklopljen


LED output relay state indicator
white: relay ON
no light: relay OFF


opozorila /
attention



motorni pogon (omejena uporaba pri talnem ogrevanju) /
motor drive (limited use with underfloor heating)

2M = 45 x 45





NM39

NOSILEC Z VIJAKI ZA TERMOSTATE FANTINI COSMI 3M

- nosilec z vijaki za termostate Fantini Cosmi 3M
- namenjen za uporabo z dnevнимi termostati Fantini Cosmi za modela CH121 in CH123
- namenjen za uporabo s tedenskimi termostati Fantini Cosmi za modela CH141A in CH143A
- montaža v pravokotne doze velikosti 3M
- primeren za sestavo z okvirji PURE, Line, Soft



MOUNTING FRAME WITH SCREWS FOR FANTINI COSMI THERMOSTATS 3M

- mounting frame with screws for Fantini Cosmi thermostats 3M
- suitable for use with Fantini Cosmi daily thermostats models CH121 and CH123
- suitable for use with Fantini Cosmi weekly thermostats models CH141A and CH143A
- for mounting in rectangular boxes 3M
- suitable for assembling with cover plates PURE, Line, Soft



- EM40PW
- EM40SB
- EM40ES
- EM40IW




KARTIČNO STIKALO ZA VARČEVANJE Z ENERGIJO 3A 250V~ 3M

- kartično stikalno osnovno, poljubna ISO kartica
- napajanje 230V~ 50Hz
- izhod 3A 250V~ za vklop zunanjega kontaktora *
- zakasnitev izklopa 15-20s
- ustreza EN 61000-6-1
- kartica ni priložena
- ni namenjeno kontroli pristopa



- card switch basic, any ISO card
- supply voltage 230V~ 50Hz
- output 3A 250V~ for switching contactor *
- switch off delay 15-20s
- in accordance with EN 61000-6-1
- card is not included
- not for access control

3M = 67,5 x 45



EM47

KARTICA ISO


- ISO kartica
- za uporabo s kartičnim stikalom EM40
- velikost: 85x54 mm

CARD ISO

- ISO card
- for combination with card switch EM40
- size: 85x54 mm



■ EM44BK

**KARTIČNO STIKALO ZA VARČEVANJE Z ENERGIJO RF HF 13,56MHz 3M**


- kartično stikalo elektronsko na RFID ISO kartico
- napajanje iz rele enote EM49 preko kabla s konektorji RJ12
- izhod za povezavo z relo enoto EM49
- zakasnitev izklopa "main power" ob izvlečenju kartice 15-20 s
- zakasnitev izklopa "HVAC" ob izvlečenju kartice pri odprtih balkonskih vratih ali oknu - 1 min
- ustreza EN 61000-6-1
- kartica ni priložena
- ni namenjeno kontroli pristopa

ENERGY SAVER CARD SWITCH RF HF 13,56MHz 3M

- electronic card switch for RFID ISO card
- supply from relay unit EM49 through cable connectors RJ12
- output to be connected to relay output unit EM49
- 15-20s "main power" switch off delay with card withdrawal
- 1 min "HVAC" switch off delay with card withdrawal when balcony doors or windows opened
- in accordance with EN 61000-6-1
- card is not included
- not for access control



EM49

**RELE ENOTA ZA KARTIČNO STIKALO 2X16A 250V~**

- relo enota za kartična stikala EM44
- napajanje 230V~ 50 Hz
- ustreza EN 61000-6-1
- montaža na DIN letev 35mm, 3MU
- vhodi in izhodi glede na vgradnjo: enosobno ali dvosobno

**ENERGY SAVER CONTROL UNIT 2x16A 250V~**

- relay unit for card switches EM44
- supply voltage 230V~ 50Hz
- in accordance with EN 61000-6-1
- mounting on DIN rail 35mm, 3MU
- input and output depending on implementation: single or double room



EM45


RAZDELILNIK SPL-1

- za povezavo dveh kartičnih stikal EM44 z relo enoto EM49
- komunikacijski konektor RJ12
- velikost: 37 x 30 x 27 mm



SPLITTER SPL-1


- used to connect two peripheral modules EM44 to relay unit EM49
- communication connector RJ12
- size: 37 x 30 x 27 mm

vezalna shema za enosobno delovanje /
wiring diagram for single room implementation




povezovalni kabel RJ12 med EM44 in EM49 /
connection cable RJ12 between EM44 and EM49






- EM60PW
- EM60SB
- EM60ES
- EM60IW

3M = 67,5 x 45




VTIČNICA ZA BRIVNIK 230V~/125V~ 3M

- vtičnica za brivnik z ločilnim transformatorjem 20VA
 - vhod: 230V~ 50-60Hz
 - izhod:
 - 230V~ za 2P 2.5A EURO vtič ali
 - 125V~ za 2P 15A ameriški vtič - razred zaščite II
 - ustreza EN 61558-2-5
- SOCKET SHAVER 230V~/125V~ 3M**
- shaver supply unit with isolating transformer 20VA
 - supply: 230V~ 50-60Hz
 - output:
 - 230V~ for 2P 2.5A Europlug or
 - 125V~ for 2P 15A American plug - Class II
 - in accordance with EN 61558-2-5





POLNILNIK USB 5V 1A 2M



- EM65PW
- EM65SB
- EM65ES
- EM65IW

2M = 45 x 45



- za polnjenje elektronskih naprav preko standardnega USB priključka (kompatibilno tudi z Apple napravami)
- omogoča hkratno polnjenje dveh naprav
- napajanje: 230V~ 50Hz
- poraba v mirovanju: 50 mW pri 230V~
- izhodna napetost: 5 VDC ($\pm 5\%$) SELV
- nihanje izhodne napetosti: 150 mV
- nominalni izhodni tok: 1 A (1 x 1.000 mA ali 2 x 500 mA) ($\pm 10\%$)
- učinkovitost: več kot 67%
- IP zaščitni razred: IP20, samo za notranjo uporabo
- vijačna pritridlev vodnikov max. 2,5 mm²
- ustreza standardom EN 60950-1 in EMC direktivi
- polnilnik mora biti varovan z ustreznim zunanjim odklopnikom


POWER SUPPLY UNIT USB 5V 1A 2M

- for charging of electronic devices via a standard USB port (also compatible with Apple devices)
- enables charging of two devices simultaneously
- power supply: 230V~ 50Hz
- stand-by power consumption: 50 mW at 230V~
- nominal output voltage: 5 VDC ($\pm 5\%$) SELV
- output ripple voltage: 150 mV
- nominal output current: 1 A (1 x 1.000 mA or 2 x 500 mA) ($\pm 10\%$)
- efficiency: greater than 67%
- IP protection class: IP20, indoor use only
- screw contacts: max. 2.5 mm²
- in accordance with EN 60950-1 and EMC directive
- an appropriate external disconnect device needs to be considered as part of installation

POLNILNIK USB 5V 2,1A 1M

- EM66PW
- EM66SB
- EM66ES
- EM66IW

- za polnjenje elektronskih naprav prek standardnega USB priključka (kompatibilno tudi z Apple napravami)
 - napajanje: 100-230 V~ 50/60 Hz
 - poraba med delovanjem:
 300 mA pri 100 V~/150 mA pri 230 V~
 - poraba v mirovanju: 30 mW pri 230 V~
 - izhodna napetost: 5 VDC ($\pm 5\%$) SELV
 - nihanje izhodne napetosti: 150 mV
 - nominalni izhodni tok: 2,1 A (1 x 2.100 mA) ($\pm 10\%$)
 - ucinkovitost: maksimalno 77 %
 - temperatura delovanja: 0 °C/+ 45 °C (notranja uporaba)
 - IP zaščitni razred: IP20, samo za notranjo uporabo
 - varnostni razred napreve II
 - prenapetostna zaščita (EN 62109): razred III
 - vijačna pritridlev vodnikov max. 2,5 mm²
 - naprava z odmikom kontaktov min. 3 mm
 - ustreza standardu EN 60950-1 in direktivam EMC in LVD

**USB POWER SUPPLY UNIT 5V 2,1A 1M**

- for charging of electronic devices via a standard USB port (also compatible with Apple devices)
 - power supply: 100-230V~ 50/60Hz
 - power consumption: 300mA at 100V~/150mA at 230V~
 - standby power consumption: 30mW at 230V~
 - nominal output voltage: 5 VCD ($\pm 5\%$) SELV
 - output ripple voltage: 150mV
 - nominal output current: 2,1A (1 x 2.100mA) ($\pm 10\%$)
 - efficiency: maximum of 77%
 - operating temperature: 0°C/+45°C (indoor use)
 - IP protection class: IP20, indoor use only
 - class device II
 - overvoltage category (EN 62109): Class III
 - screw contacts: max. 2,5 mm²
 - device with a contact gap of at least 3mm
 - in accordance with EN 60950-1 and LVD & EMC directives



- EM55



LED ZASILNA SVETILKA 250V~ 0.9W, NiCd 3h 7M


- zasilna LED svetilka
 - napajanje 230V~ 50Hz 3xLED 0,3W,
 10000mcd, 6500K
 - NiCd 4,8V akumulator 400 mAh, zamenljiv
 - avtonomija 3h, polnenje 24h
 - razred zaščite II
 - ustreza EN 60598-1, EN 60598-2-2, EN 60598-2-22

**LED EMERGENCY LIGHT 250V~ 0.90W, NiCd 3h 7M**

- emergency LED lamp
 - supply voltage 230V~ 50Hz 3xLED 0,3W, 10000mcd, 6500K
 - NiCd accumulator 400 mAh, replaceable
 - autonomy 3h, charging 24h
 - Class II
 - in accordance with EN 60598-1, EN 60598-2-2, EN 60598-2-22

7M = 151,5 x 45





- EM50WH
- EM50BL
- EM50RD
- EM50GR


SVETILKA LED ENOBARVNA 250V~ 0,8W 2M

- LED svetilka za osvetlitev stopnišč ali hodnikov
- napajanje 230V~ 50Hz 0,8W, 6500°K
- razred zaščite II
- ustreza EN 60598-1
- uporaba tudi za usmerjanje ali signalizacijo z možnostjo laserskega tiska poljubne grafike



LED LAMP MONOCOLOR 250V~ 0,8W 2M

- step marker LED lamp
- supply voltage 230V~ 50Hz 0,8W, 6500°K
- Class II
- in accordance with EN 60598-1
- optional usage for directional or signal illumination with customized laser printing on diffuser



- EM51RG


SVETILKA LED DVOBARVNA 250V~ 2x0,4W 2M

- LED dvobarvna svetilka (rdeča/zelena) za signalizacijo
- napajanje 230V~ 50Hz 2x0,4W, 6500°K
- razred zaščite II
- ustreza EN 60598-1
- vsebuje grafiko kot na sliki
- možnost laserskega tiska poljubne grafike



LED LAMP DUAL COLOR 250V~ 2x0,4W 2M

- signaling dual color (red/green) LED lamp
- supply voltage 230V~ 50Hz 2x0,4W, 6500°K
- Class II
- in accordance with EN 60598-1
- diffuser includes graphics as shown
- possible customized laser printing on diffuser



- EM52RG
- EM52RG90
- EM52RG91
- EM52RG99

SVETILKA LED 3D DVOBARVNA 250V~ 2x0,4W 2M

- LED dvobarvna svetilka (rdeče/zelena) s 3D simbolom, za signalizacijo
- napajanje 230V~ 50Hz 2x0,4 W, 6500°K
- razred zaščite II
- ustreza EN 60598-1
- možnost tiska različnih grafik po naročilu
- 90 moški simbol, 91 ženski simbol, 99 simbol po naročilu





LED LAMP 3D DUAL COLOR 250V~ 2x0,4W 2M

- signalling LED lamp, dual color (red/green) with 3D symbol
- supply voltage 230V~ 50Hz 2x0,4W, 6500°K
- class II
- in accordance with EN 60598-1
- possible customized graphics on request
- 90 male symbol, 91 female symbol, 99 symbol on request



2M = 45 x 45





- EM70PW
- EM70SB
- EM70ES
- EM70IW

STIKALO NA PRSTNI ODTIS ARX ONE 2M

- stikalno na prstni odtis v kompletu z notranjo enoto
- za odklepanje električnih ključavnic
- kapaciteta 1000 odtisov
- enostavno programiranje z dvema tipkama
- termalni biometrični senzor
- napajanje notranje rele enote 110-230V~ 50-60Hz
- izhodni rele 2x3A 12V DC
- 256-bitna enkrizacija povezave med stikalom in notranjo rele enoto
- ustreza EN 61000-6-1

FINGERPRINT SWITCH ARX ONE 2M

- fingerprint switch with included internal relay unit
- for unlocking electrical locks
- capacity 1000 fingerprints
- easy programming with two buttons
- thermal biometric sensor
- internal relay unit supply 110-230V~ 50-60Hz
- output relay 2x3A 12V DC
- 256-bit encrypted link between switch and internal relay unit
- in accordance with EN 61000-6-1



VNOS UPRAVNika

1. Prvi trije odtisi imajo upravnike pravice.
2. Postopek vnosa je enak kot pri dodajanju uporabnika, le brez drugega koraka.

ADMINISTRATOR ENROLMENT

1. The first three fingerprints enrolled are assigned administrative rights.
2. Administrator enrolment procedure is same as user enrolment without second step.

DODAJANJE UPORABNIKA

1. Na zunani enoti držimo levo tipko 3 sekunde. Oranžna dioda začne počasi utripati.
2. Uporabnik s prstom enkrat potegne po senzoru. Oranžna dioda začne hitro utripati.
3. Pritisnemo levo tipko. Za potrditev se prizge zelena dioda in pisk za 1 s.
4. Oranžna in zelena dioda izmenično utripata. Sedaj prst po senzoru štirikrat potegne uporabnik. Vsa vnos spremlja pisk.
5. Ko je uporabniški odtis uspešno vnešen, zasveti zelena dioda, zasliši se pisk.

USER ENROLMENT

1. The left button on the exterior unit is pressed for 3 seconds. The orange LED starts flashing slow.
2. An administrator swipes his finger over the sensor once. When he/she is identified, the orange LED will start flashing fast.
3. Press left button. The green LED confirms.
4. The orange and green LED will flash alternately. At this point the user swipes his/her finger over the sensor four times. Each successful entry is indicated by a buzz.
5. When the user is correctly enrolled, the green LED will flash and the buzzer will buzz at the same time.

BRISANJE UPORABNIKA

1. Na zunani enoti držimo desno tipko 5 sekund. Oranžna dioda začne počasi utripati.
2. Uporabnik s prstom enkrat potegne po senzoru. Uspešna identifikacija je potrjena, ko zasveti zelena dioda in se zasliši pisk.
3. Rdeča in zelena dioda izmenično utripata. Prst po senzoru enkrat potegne uporabnik, ki ga želimo zbrisati. Ko je pozitivno identificiran, zasveti zelena dioda in pisk za 1 s. Uporabnik je uspešno izbrisani.

DELETING A USER




1. The right button on the exterior unit should be pressed for 5 seconds whereupon the orange LED will start flashing slow.
2. An administrator swipes his finger over the sensor once. When he/she is identified, the green LED will flash and the buzzer will buzz at the same time.
3. The red and green LED will flash alternately. Then the user swipes his finger over the sensor once. When the user is identified, the green LED flash and the buzzer will buzz once. The user has been successfully deleted from the system.

BRISANJE VSEH ODTISOV

1. Na zunani enoti držimo obe tipki skupaj 10 sekund. Oranžna in rdeča dioda začeta izmenično utripati.
2. Uporabnik s prstom enkrat potegne po senzoru. Uspešna identifikacija je potrjena, ko zasveti zelena dioda in se zasliši pisk.
3. Oranžna in rdeča dioda zopet izmenično utripata. Uporabnik ponovi 2. korak.
4. Po kratkem premoru rdeča in oranžna dioda skupaj petkrat zasvetita, naprava pa petkrat zapiska v enakem intervalu. Vsi odtisi so bili uspešno izbrisani iz baze podatkov.



DELETING ALL FINGERPRINTS

1. Press the left and right button on the exterior unit together for a period of 10 seconds whereupon the orange and red LED will flash alternately.
2. The administrator then swipes his/her finger once. Identification is confirmed when the green LED flashes and the buzzer buzzes at the same time.
3. The orange and red LED will flash alternately again. The administrator repeats secod step.
4. The red and orange LED will flash and the buzzer will buzz five times simultaneously. All fingerprint templates will then have been deleted.



zunana enota
exterior unit

notranja rele enota
interior relay unit





■ EM80GW

STIKALO BREZDODIČNO 10A 240V~

- stikalo brezdodično za vkllop in izklop ("master")
- napajanje: 240 V~ 50 Hz
- izhodni rele 10A / 250V~ (2400W pri 240V~)
- nastavljiv domet od 2 do 10 cm
- namenjeno za montažo v standardne okrogle doze Ø60 mm
- za priklop je nujen ničelnji vodnik (N)
- vezava z menjalnimi stikali ni možna
- možna vezava do 5 upravljalnih stikal EM81
- enostavna montaža dekorativnih okvirjev s pomočjo magnetov
- vijačna pritrditev vodnikov do 2,5 mm² (maks. moment privitja vijakov 0,4 Nm)
- ustreza EN 60669-1 in EN 60669-2-1
- samo za notranjo uporabo

**SWITCH, TOUCHLESS 10A 240V~**

- touchless switch for turning on/off ("master")
- power supply: 240 V~ 50 Hz
- output relay 10A / 250V~ (2400W at 240V~)
- adjustable range from 2 to 10 cm
- intended for installation into a standard round Ø60 mm box
- a neutral lead (N) is required for connection
- connection with toggle switches is not possible
- connection with up to 5 EM81 control switches is possible
- simple installation of decorative covers with the help of magnets
- screw fastening of leads up to 2.5 mm² (max. screw tightening torque is 0.4 Nm)
- in accordance with EN 60669-1 and EN 60669-2-1
- only for indoor use







■ EM81GW


STIKALO BREZDODIČNO UPRAVLJALNO

- stikalo upravljalno (»slave«)
- deluje samo v povezavi s stikalom EM80 (»master«)
- nastavljiv domet od 2 do 10 cm
- enostavna montaža dekorativnih okvirjev s pomočjo magnetov
- vijačna pritrditev vodnikov do 2,5 mm² (maks. moment privitja vijakov 0,4 Nm)
- ustreza EN 60669-1 in EN 60669-2-1
- samo za notranjo uporabo

**SWITCH, TOUCHLESS, CONTROL UNIT**

- control switch (»slave«)
- works only when connected with the EM80 switch (»master«)
- adjustable range from 2 to 10 cm
- simple installation of decorative covers with the help of magnets
- screw fastening of leads up to 2.5 mm² (max. screw tightening torque is 0.4 Nm)
- in accordance with EN 60669-1 and EN 60669-2-1
- only for indoor use






- EM90PW
- EM90SB
- EM90ES
- EM90IW

BRENČAČ 8VA 230V~ 1M


- signalni brenčač
- dolžina zvoka je enaka dolžini pritiska na tipko
- napajanje 230V~ 50Hz 8VA



- EM91PW
- EM91SB
- EM91ES
- EM91IW

BRENČAČ 8VA 12V~ 1M


- signalni brenčač
- dolžina zvoka je enaka dolžini pritiska na tipko
- napajanje 12V~ 50Hz 8VA



- EM92PW
- EM92SB
- EM92ES
- EM92IW

ZVONEC 8VA 230V~ 1M

- signalni zvonec
- dolžina zvoka je enaka dolžini pritiska na tipko
- napajanje 230V~ 50Hz 8VA





- EM93PW
- EM93SB
- EM93ES
- EM93IW

ZVONEC 8VA 12V~ 1M

- signalni zvonec
- dolžina zvoka je enaka dolžini pritiska na tipko
- napajanje 12V~ 50Hz 8VA

- BELL 8VA 230V~1M**
- signal bell
 - the sound emission has the same lasting time as the control operation
 - supply voltage 230V~ 50Hz 8VA






- EM95PW
- EM95SB
- EM95ES
- EM95IW

REGULATOR GLASNOSTI ZA 100V AVUDIO LINIJO 35W 2M



- regulator glasnosti (attenuator) za 100V avdio sisteme
- nazivna moč 35W (max. 45W), 6 stopenjska nastavitev glasnosti
- primeren za vgradnjo v globoke doze (min. 60 mm)
- ni primeren za vgradnjo v doze globine 45 mm in ohišja CUBO IP20
- samo za notranjo uporabo



- EM96PW
- EM96SB
- EM96ES
- EM96IW

REGULATOR GLASNOSTI NIZKOOHMSKI 4-8 Ω 35W 2M

- regulator glasnosti za nizkonapetostne izhode 4-8 Ω 35W
- za priklop na HI-Fi naprave
- nazivna moč 35W, 6 stopenjska nastavitev glasnosti
- primeren za vgradnjo v globoke doze (min. 60 mm)
- ni primeren za vgradnjo v doze globine 45 mm in ohišja CUBO IP20
- samo za notranjo uporabo






CM25

PW

OS

tip type	naziv description	tehnični opis technical data	velikost size	barva colour	opcionalni opis 1 optional data 1
CM10	SET VTIČNIC 2x SCHUKO SOCKET SET 2x SCHUKO	2P+E 16A 250V~	4M	<input type="checkbox"/> PW bela-sijaj polar white	<input type="checkbox"/> OL okvir LINE cover plate LINE
CM11	SET VTIČNIC 3x SCHUKO SOCKET SET 3x SCHUKO	2P+E 16A 250V~	7M	<input checked="" type="checkbox"/> SB črna-mat soft touch black	<input type="checkbox"/> OS okvir SOFT cover plate SOFT
CM15	SET VEZNICKOV BARVNI LINK WIRE SET	3x1.5mm ²	1M	<input type="checkbox"/> ES srebrna-mat elox silver	
				<input type="checkbox"/> IW bež-sijaj ivory white	

SET VTIČNIC 2x SCHUKO 2P+E 16A 250V~ 4M




- CM10PW
- CM10ES

- set vtičnic 2x schuko VM10 2P+E 16A 250V~
- vtičnice povezane z vezniki CM16
- z nosilcem 4M brez vijakov
- za pritrdiritev nosilcev uporabiti vijke CM17, CM18 ali CM19
- vijačna pritrdiritev vodnikov 1.5-2.5 mm²
- ustreza IEC 60884-1, CEE7

SOCKETS SET 2x SCHUKO 2P+E 16A 250V~ 4M

- socket set 2x schuko VM10 2P+E 16A 250V~
- prewired with link wires CM16
- with mounting frame 4M without screws
- for mounting frame fixing use screws CM17, CM18 or CM19
- screw contacts 1.5-2.5 mm²
- in accordance with IEC-60884-1, CEE7



SET VTIČNIC 3x SCHUKO 2P+E 16A 250V~ 7M





- CM11PW
- CM11ES

- set vtičnic 3x schuko VM10 2P+E 16A 250V~
- vtičnice povezane z vezniki CM16
- z nosilcem 7M brez vijakov
- za pritrdiritev nosilcev uporabiti vijke CM17, CM18 ali CM19
- vijačna pritrdiritev vodnikov 1.5-2.5 mm²
- ustreza IEC 60884-1, CEE7

SOCKETS SET 3x SCHUKO 2P+E 16A 250V~ 7M

- socket set 3x schuko VM10 2P+E 16A 250V~
- prewired with link wires CM16
- with mounting frame 7M without screws
- for mounting frame fixing use screws CM17, CM18 or CM19
- screw contacts 1.5-2.5 mm²
- in accordance with IEC-60884-1, CEE7







CM15

SET VEZNIKOV BARVNI 3x1.5mm² 1M

- set veznikov za povezavo dveh elementov velikosti 1M
- vsebuje 10 črnih, 10 modrih in 10 rumeno-zelenih veznikov

LINK WIRE SET 3x1.5mm² 1M

- link wire set to connect two elements size 1M
- includes 10 black, 10 blue and 10 yellow/green wires




CM16

SET VEZNIKOV BARVNI 3x2.5mm² 1M

- set veznikov za povezavo dveh elementov velikosti 2M
- vsebuje 10 črnih, 10 modrih in 10 rumeno-zelenih veznikov

LINK WIRE SET 3x2.5mm² 1M


- link wire set to connect two elements size 2M
- includes 10 black, 10 blue and 10 yellow/green wires

CM17
CM18
CM19**SET VIJAKOV 3,5**

- set vijakov za pritrditev nosilcev setov NM30, NM32, NM40, NM41, NM70
- CM17 - l=20mm, 100kos
- CM18 - l=35mm, 50kos
- CM19 - l=50mm, 50kos

SCREW SET 3,5

- screw set for fixing mounting frames NM30, NM32, NM40, NM41, NM70
- CM17 - l=20mm, 100pcs
- CM18 - l=35mm, 50pcs
- CM19 - l=50mm, 50pcs

 CM22PW**SET ZA STIKALA IP44 2M**

- za vgradnjo v vlažne prostore
- IP44 zaščito zagotavlja za vsa stikala Modul
- stikala in tipke niso sestavni del seta
- okvir SOFT 2M z napisno ploščico
- ustreza IEC 60669-1

SET SWITCHES IP44 2M


- for usage in humid areas
- IP44 protection provides for all Modul switches
- switches and buttons are not part of the set
- SOFT 2M cover plate with inscription plate
- in accordance with IEC 60669-1

 CM23PW**SET ZA VTIČNICE IP44 2M**

- za vgradnjo v vlažne prostore
- IP44 zaščito zagotavlja le v kombinaciji z vtičnico s pokrovom (VM11, VM41)
- vtičnice niso sestavni del seta
- okvir SOFT 2M z napisno ploščico
- ustreza IEC 60884-1

SET SOCKETS IP44 2M


- for usage in humid areas
- IP44 protection can be achieved only in combination with covered socket (VM11, VM41)
- sockets are not part of the set
- SOFT 2M cover plate with inscription plate
- in accordance with IEC 60884-1


 CM25PWOL
 CM25IWOL
 CM25PWOS
 CM25IWOS**KOPALNIŠKI SET 3x20A 250V~ 4M**

- set stikal 3xSM12 20A 250V~ z nosilcem in okvirjem
- vijačna pritrditev vodnikov 1.5-2.5mm²
- ustreza EN 60669-1
- možnost pritrditev na že vgrajene doze pritrditvenih mer od 108 do 135mm ali na doze velikosti 4M
- višina okvirja 90mm

SWITCH SET FOR BATHROOM 3x20A 250V~ 4M

- switch set 3xSM12 20A 250V~ with mounting frame and cover plate
- screw contacts 1.5-2.5mm²
- in accordance with EN 60669-1
- universal solution for renovation on boxes with fixing dimensions 108-135mm or boxes 4M size
- cover plate height 90mm






NM41

NOSILEC KOPALNIŠKI SET 4M

- nosilec kopalniški set univerzalni z vijaki
 - možnost pritrdilive na že vgrajene pravokotne
 doze pritrditvenih mer od 108 do 135mm ali
 na doze velikosti 4M
 - ustreza EN 60669-1

MOUNTING FRAME BATHROOM SET 4M

- universal mounting frame for bathroom set with screws
 - universal solution for mounting on rectangular boxes with
 fixing dimensions 108-135mm or boxes 4M size
 - in accordance with EN 60669-1




OL41PW
OL41NB
OL41IW
OL41ES
OL41SG
OL41IB
OL41MG

OKVIR LINE KOPALNIŠKI SET

- dekorativni okvir kopalniški set LINE
 - višina 90mm
 - ustreza EN 60669-1

COVER PLATE LINE BATHROOM SET

- decorative cover plate bathroom set LINE
 - height 90mm
 - in accordance with EN 60669-1




OS41PW
OS41NB
OS41IW
OS41ES
OS41SG
OS41SB
OS41WE


OKVIR SOFT KOPALNIŠKI SET

- dekorativni okvir kopalniški set SOFT
 - višina 90mm
 - ustreza EN 60669-1

COVER PLATE SOFT BATHROOM SET

- decorative cover plate bathroom set SOFT
 - height 90mm
 - in accordance with EN 60669-1





ANTIBAKTERIJSKI PROGRAM MODUL

- stikala in vtičnice so vsakodnevno izpostavljene dotiku večjega števila ljudi, zato so to pogosta mesta za razvoj in širjenje bakterij
- zahvaljujoč svojim naravnim antibakterijskim lastnostim je srebro že 3 tisočletja v uporabi kot varno in učinkovito dezinfekcijsko sredstvo, saj je popolnoma naravno ter zdravju in okolju prijazno
- poseben antibakterijski dodatek srebrovih ionov zagotavlja dolgoročno, zanesljivo in učinkovito zaščito pred razvojem in širjenjem različnih bakterij, virusov, mikrobov in gliciv
- antibakterijska zaščita pomeni večjo higieničnost, čistoto in zdravje ljudi
- antibakterijski program MODUL je primeren za uporabo povsod, kjer veljajo strogi higienski pogoji (bolnišnice, zdravstveni domovi, farmacevtski objekti, domovi za starejše, negovalni domovi, laboratoriji, restavracije, hoteli, letališča, avtobusne in železniške postaje, poslovni in trgovski prostori, javne institucije...)
- laboratorijska testiranja so bila opravljena v neodvisni instituciji na podlagi najvišjih japonskih standardov JIS Z 2801
- nizki stroški za zagotavljanje zdravja ljudi
- oblika in funkcionalnost antibakterijskega programa MODUL omogočata enostavno čiščenje in vzdrževanje
- antibakterijski program MODUL kombiniramo z antibakterijskimi tipkami, okvirji in vtičnicami skupaj s klasičnimi nosilci in stikali
- vsak izdelek je zaradi lažje identifikacije na zadnji strani označen z AW (antibacterial white)

ANTIBACTERIAL PROGRAM MODUL

- switches and sockets are daily touched by many people, so this is a common place for development and spread of bacteria
- thanks to its natural antibacterial characteristics silver has been used for three millennia as a safe and effective disinfectant, since it is completely natural, healthy and environmentally friendly
- special antibacterial silver ions additive provides long-term, reliable and effective protection against the development and spread of bacteria, viruses, microbes and fungi
- antibacterial protection ensures hygiene, cleanliness and health for people
- perfectly suitable for use in environments with strict hygiene conditions (hospitals, health centers, pharmaceutical facilities, homes for elderly, nursing homes, laboratories, restaurants, hotels, airports, bus and railway stations, business and shopping areas, public institutions ...)
- independent laboratory testings have been carried out in accordance with highest Japanese standards JIS Z 2801
- low cost for providing human health
- design and functionality of antibacterial program MODUL allow easy cleaning and maintenance
- antibacterial buttons, cover plates and sockets are combined with classic mounting frames and switches
- products are labelled on the back with AW (antibacterial white)

A N T I B A C T E R I A L P R O G R A M M O D U L

TIPKA 1M

 TM11AW

- zamenljiva tipka velikosti 1M
 - ustreza EN 60669-1
 - antibakterijska zaščita skladna z JIS Z 2801
- BUTTON 1M**
- replaceable button 1M
 - in accordance with EN 60669-1
 - antibacterial protection in accordance with JIS Z 2801



TIPKA 1M INDIKATOR

 TM11AWIN

- zamenljiva tipka velikosti 1M
 - ustreza EN 60669-1
 - antibakterijska zaščita skladna z JIS Z 2801
- BUTTON 1M INDICATOR**
- replaceable button 1M
 - in accordance with EN 60669-1
 - antibacterial protection in accordance with JIS Z 2801



TIPKA 2M

 TM12AW

- zamenljiva tipka velikost 2M z nosilcem tipke
 - uporablja se pri nadgradnji stikala ali tipkala velikosti 1M v velikost 2M
 - ustreza EN 60669-1
 - antibakterijska zaščita skladna z JIS Z 2801
- BUTTON 2M**
- replaceable button 2M with button carrier
 - to upgrade switch or push button from size 1M to size 2M
 - in accordance with EN 60669-1
 - antibacterial protection in accordance with JIS Z 2801



TIPKA 2M INDIKATOR

 TM12AWIN

- zamenljiva tipka velikost 2M z nosilcem tipke
 - uporablja se pri nadgradnji stikala ali tipkala velikosti 1M v velikost 2M
 - ustreza EN 60669-1
 - antibakterijska zaščita skladna z JIS Z 2801
- BUTTON 2M INDICATOR**
- replaceable button 2M with button carrier
 - to upgrade switch or push button from size 1M to size 2M
 - in accordance with EN 60669-1
 - antibacterial protection in accordance with JIS Z 2801



POLNILO 1M

 TM21AW

- za zapolnjevanje praznih mest
 - ustreza EN 60669-1
 - antibakterijska zaščita skladna z JIS Z 2801
- BLANK 1M**
- blank modul to fill up empty spaces
 - in accordance with EN 60669-1
 - antibacterial protection in accordance with JIS Z 2801



POLNILO 2M

 TM22AW

- za zapolnjevanje praznih mest
 - ustreza EN 60669-1
 - antibakterijska zaščita skladna z JIS Z 2801
- BLANK 2M**
- blank modul to fill up empty spaces
 - in accordance with EN 60669-1
 - antibacterial protection in accordance with JIS Z 2801





VM10AW

VTIČNICA SCHUKO+KS 2P+E 16A 250V~ 2M

- 2P+E schuko
 - 16A 250V~, tip VM10
 - ustreza IEC 60884-1, CEE7
 - vijačna pritrditev vodnikov 1.5-2.5 mm²
 - KS vgrajena otroška zaščita pred dotikom kontaktov
 - antibakterijska zaščita skladna z JIS Z 2801
- SOCKET SCHUKO+KS 2P+E 16A 250V~ 2M**
- 2P+E schuko
 - 16A 250V~, type VM10
 - in accordance with IEC 60884-1, CEE7
 - screw contacts 1.5-2.5 mm²
 - KS build-in child protection - shuttered live contacts
 - antibacterial protection in accordance with JIS Z 2801



VM11AW

VTIČNICA SCHUKO+KS+POKROV 2P+E 16A 250V~ 2M

- 2P+E schuko + pokrov
- 16A 250V~, tip VM11
- ustreza IEC 60884-1, CEE7
- vijačna pritrditev vodnikov 1.5-2.5 mm²
- KS vgrajena otroška zaščita pred dotikom kontaktov
- antibakterijska zaščita skladna z JIS Z 2801

SOCKET SCHUKO+KS+COVER

- 2P+E 16A 250V~ 2M**
- 2P+E schuko + cover
 - 16A 250V~, type VM11
 - in accordance with IEC 60884-1, CEE7
 - screw contacts 1.5-2.5 mm²
 - KS build-in child protection - shuttered live contacts
 - antibacterial protection in accordance with JIS Z 2801



VM20AW

VTIČNICA EURO+KS 2P 10A 250V~ 1M

- 2P euro
- 10A 250V~, tip VM20
- ustreza IEC 60884-1, CEE7
- vijačna pritrditev vodnikov 1.5-2.5 mm²
- KS vgrajena otroška zaščita pred dotikom kontaktov
- antibakterijska zaščita skladna z JIS Z 2801

SOCKET EURO+KS 2P 10A 250V~ 1M

- 2P Euro
- 10A 250V~, type VM20
- in accordance with IEC 60884-1, CEE7
- screw contacts 1.5-2.5 mm²
- KS build-in child protection - shuttered live contacts
- antibacterial protection in accordance with JIS Z 2801



KM11AW

↓ Ad: 1dB
24V 500 mA max
IEC 60169-2 male

VTIČNICA TV KONČNA 1dB 1M

- TV končna
- frekvenčni pas 5÷2400 MHz
- dušenje < 1 dB
- ustreza EN 50083-1
- vijačna priključitev
- antibakterijska zaščita skladna z JIS Z 2801

SOCKET TV END-LINE 1dB 1M

- TV end-line
- frequency range 5÷2400 MHz
- reduction < 1 dB
- in accordance with EN 50083-1
- screw contacts
- antibacterial protection in accordance with JIS Z 2801



KM35AW

ADAPTER KS 1M

- KS keystone pritrditveni standard
- AMP, Avaya, Brandrex, FMT, Mfico, Tyco, ...
- komunikacijski modul ni vgrajen
- antibakterijska zaščita skladna z JIS Z 2801

ADAPTER KS 1M

- KS keystone fixing standard
- AMP, Avaya, Brandrex, FMT, Mfico, Tyco, ...
- communication module not included
- antibacterial protection in accordance with JIS Z 2801





OS20AW

OKVIR SOFT 2M

- dekorativni okvir SOFT 2M
- ustreza EN 60669-1
- antibakterijska zaščita skladna z JIS Z 2801

COVER PLATE SOFT 2M

- decorative cover plate SOFT 2M
- in accordance with EN 60669-1
- antibacterial protection in accordance with JIS Z 2801



OS24AW

OKVIR SOFT 2x2M

- dekorativni okvir SOFT 2x2M
- horizontalna ali vertikalna vgradnja
- ustreza EN 60669-1
- antibakterijska zaščita skladna z JIS Z 2801

COVER PLATE SOFT 2x2M

- decorative cover plate SOFT 2x2M
- horizontal or vertical mounting
- in accordance with EN 60669-1
- antibacterial protection in accordance with JIS Z 2801



OS26AW

OKVIR SOFT 3x2M

- dekorativni okvir SOFT 3x2M
- horizontalna ali vertikalna vgradnja
- ustreza EN 60669-1
- antibakterijska zaščita skladna z JIS Z 2801

COVER PLATE SOFT 3x2M

- decorative cover plate SOFT 3x2M
- horizontal or vertical mounting
- in accordance with EN 60669-1
- antibacterial protection in accordance with JIS Z 2801



OS30AW

OKVIR SOFT 3M

- dekorativni okvir SOFT 3M
- ustreza EN 60669-1
- antibakterijska zaščita skladna z JIS Z 2801

COVER PLATE SOFT 3M

- decorative cover plate SOFT 3M
- antibacterial protection in accordance with JIS Z 2801
- in accordance with EN 60669-1




OS40AW

OKVIR SOFT 4M

- dekorativni okvir SOFT 4M
- ustreza EN 60669-1
- antibakterijska zaščita skladna z JIS Z 2801

COVER PLATE SOFT 4M

- decorative cover plate SOFT 4M
- in accordance with EN 60669-1
- antibacterial protection in accordance with JIS Z 2801



OS70AW

OKVIR SOFT 7M

- dekorativni okvir SOFT 7M
- ustreza EN 60669-1
- antibakterijska zaščita skladna z JIS Z 2801

COVER PLATE SOFT 7M

- decorative cover plate SOFT 7M
- in accordance with EN 60669-1
- antibacterial protection in accordance with JIS Z 2801

les
wood

WB bambus
bamboo



WM javor
maple



WW oreh
walnut



WE wenge
wenge










Narava je edinstvena in dragocena, kot naši okvirji, med katerimi ni enakega.

Reklamacij glede različnosti izgleda in medsebojnega razlikovanja pri leseni
okvirjih ne moremo upoštevati.

Nature is unique and precious, as our decorative cover plates where no two are the same.

Complaints about wooden decorative cover plate's diverse appearance and differentiation
cannot be considered.

C O V E R P L A T E S P U R E O P

kovina
metalMH kovano jeklo
hammered steelMS satinirano srebro
satin silversteklo
glassGW ledeno bela
ice whiteGY ledeno sive
ice greyME zarjavelo železo
etched ironMN satiniran nikelj
satin nickelGG ledeno zelena
ice greenGB ledeno modra
ice blue



tip type	naziv description	velikost size	barva colour
OP13	OKVIR PURE COVER PLATE PURE	1/3M	MH kovano jeklo hammered steel
OP20	OKVIR PURE COVER PLATE PURE	2M	ME zarjavelo železo etched iron
OP23	OKVIR PURE COVER PLATE PURE	2/3M	MS satinirano srebro satin silver
.	.	.	MN satiniran nikelj satin nickel
.	.	.	
			WB bambus bamboo
			WW oreh walnut
			WM javor maple
			WE wenge wenge
			GW ledeno bela ice white
			GG ledeno zelena ice green
			GY ledeno siva ice grey
			GB ledeno modra ice blue



OP20MH
OP20ME
OP20MS
OP20MN


OP20WB
OP20WW
OP20WM
OP20WE
OP20GW
OP20GG
OP20GY
OP20GB

OKVIR PURE 2M

- dekorativni okvir PURE 2M
- ustreza EN 60669-1
- samo v kombinaciji z nosilcem NM24 ali NM25

COVER PLATE PURE 2M

- decorative cover plate PURE 2M
- in accordance with EN 60669-1
- only in combination with mounting frame NM24 or NM25



OP24MH
OP24ME
OP24MS
OP24MN

OP24WB
OP24WW
OP24WM
OP24WE
OP24GW
OP24GG
OP24GY
OP24GB

OKVIR PURE 2x2M

- dekorativni okvir PURE 2x2M
- horizontalna ali vertikalna vgradnja
- ustreza EN 60669-1
- samo v kombinaciji z nosilcema NM24 ali NM25

COVER PLATE PURE 2x2M

- decorative cover plate PURE 2x2M
- horizontal or vertical mounting
- in accordance with EN 60669-1
- only in combination with mounting frames NM24 or NM25



OP26MH
OP26ME
OP26MS
OP26MN

OP26WB
OP26WW
OP26WM
OP26WE
OP26GW
OP26GG
OP26GY
OP26GB

OKVIR PURE 3x2M

- dekorativni okvir PURE 3x2M
- horizontalna ali vertikalna vgradnja
- ustreza EN 60669-1
- samo v kombinaciji z nosilci NM24 ali NM25

COVER PLATE PURE 3x2M

- decorative cover plate PURE 3x2M
- horizontal or vertical mounting
- in accordance with EN 60669-1
- only in combination with mounting frames NM24 or NM25

COVER PLATES PURE OP




OP30MH
OP30ME
OP30MS
OP30MN

OP30WB
OP30WW
OP30WM
OP30WE
OP30GW
OP30GG
OP30GY
OP30GB

OKVIR PURE 3M

- dekorativni okvir PURE 3M
- ustreza EN 60669-1
COVER PLATE PURE 3M
- decorative cover plate PURE 3M
- in accordance with EN 60669-1




OP40MH
OP40ME
OP40MS
OP40MN

OP40WB
OP40WW
OP40WM
OP40WE
OP40GW
OP40GG
OP40GY
OP40GB

OKVIR PURE 4M

- dekorativni okvir PURE 4M
- ustreza EN 60669-1
COVER PLATE PURE 4M
- decorative cover plate PURE 4M
- in accordance with EN 60669-1



OP70MH
OP70ME
OP70MS
OP70MN

OP70WB
OP70WW
OP70WM
OP70WE
OP70GW
OP70GG
OP70GY
OP70GB

OKVIR PURE 7M

- dekorativni okvir PURE 7M
- ustreza EN 60669-1
COVER PLATE PURE 7M
- decorative cover plate PURE 7M
- in accordance with EN 60669-1



OP13MH
OP13ME
OP13MS
OP13MN

OP13WB
OP13WW
OP13WM
OP13WE
OP13GW
OP13GG
OP13GY
OP13GB

OKVIR PURE 1/3M

- dekorativni okvir PURE 1/3M
- ustreza EN 60669-1
COVER PLATE PURE 1/3M
- decorative cover plate PURE 1/3M
- in accordance with EN 60669-1



OP23MH
OP23ME
OP23MS
OP23MN


OP23WB
OP23WW
OP23WM
OP23WE
OP23GW
OP23GG
OP23GY
OP23GB

OKVIR PURE 2/3M

- dekorativni okvir PURE 2/3M
- ustreza EN 60669-1
COVER PLATE PURE 2/3M
- decorative cover plate PURE 2/3M
- in accordance with EN 60669-1

basic
basic


PW bela-sijaj
polar white



ES srebrna-mat
elox silver



IW bež-sijaj
ivory white



SB črna-mat
soft touch black




line


COVER PLATES LINE OL

dekor
decor

SG zlata-mat
sand gold




IB modra-mat
impulse blue




SE kamen emerald
stone emerald



NG črna-sijaj
night black




MG zelena-mat
mint green



SW kamen beli
stone white





tip type	naziv description	velikost size	barva colour			
OL10	OKVIR LINE COVER PLATE LINE	1/2M	PW	bela-sijaj polar white	SG	zlata-mat sand gold
OL13	OKVIR LINE COVER PLATE LINE	1/3M	IW	bež-sijaj ivory white	NB	črna-sijaj night black
OL20	OKVIR LINE COVER PLATE LINE	2M	ES	srebrena-mat elox silver	IB	modra-mat impulse blue
.	.	.	SB	črna-mat soft touch black	MG	zelena-mat mint green
.	.	.				



OL20PW	OL20SG
OL20IW	OL20NB
OL20ES	OL20IB
OL20SB	OL20MG
	OL20SE
	OL20SW

OKVIR LINE 2M


- dekorativni okvir LINE 2M
 - ustreza EN 60669-1
- COVER PLATE LINE 2M**
- decorative cover plate LINE 2M
 - in accordance with EN 60669-1



OL24PW	OL24SG
OL24IW	OL24NB
OL24ES	OL24IB
OL24SB	OL24MG
	OL24SE
	OL24SW

OKVIR LINE 2x2M

- dekorativni okvir LINE 2x2M
 - horizontalna ali vertikalna vgradnja
 - ustreza EN 60669-1
- COVER PLATE LINE 2x2M**
- decorative cover plate LINE 2x2M
 - horizontal or vertical mounting
 - in accordance with EN 60669-1



OL26PW	OL26SG
OL26IW	OL26NB
OL26ES	OL26IB
OL26SB	OL26MG
	OL26SE
	OL26SW

OKVIR LINE 3x2M

- dekorativni okvir LINE 3x2M
 - horizontalna ali vertikalna vgradnja
 - ustreza EN 60669-1
- COVER PLATE LINE 3x2M**
- decorative cover plate LINE 3x2M
 - horizontal or vertical mounting
 - in accordance with EN 60669-1



OL28PW	OL28SG
OL28IW	OL28NB
OL28ES	OL28IB
OL28SB	OL28MG
	OL28SE
	OL28SW

OKVIR LINE 4x2M

- dekorativni okvir LINE 4x2M
 - horizontalna ali vertikalna vgradnja
 - ustreza EN 60669-1
- COVER PLATE LINE 4x2M**
- decorative cover plate LINE 4x2M
 - horizontal or vertical mounting
 - in accordance with EN 60669-1

COVER PLATES LINE OL



OL30PW
OL30IW
OL30ES
OL30SB

OL30SG
OL30NB
OL30IB
OL30MG
OL30SE
OL30SW

OKVIR LINE 3M

- dekorativni okvir LINE 3M
 - ustreza EN 60669-1
- COVER PLATE LINE 3M**
- decorative cover plate LINE 3M
 - in accordance with EN 60669-1




OL40PW
OL40IW
OL40ES
OL40SB

OL40SG
OL40NB
OL40IB
OL40MG
OL40SE
OL40SW

OKVIR LINE 4M

- dekorativni okvir LINE 4M
 - ustreza EN 60669-1
- COVER PLATE LINE 4M**
- decorative cover plate LINE 4M
 - in accordance with EN 60669-1




OL70PW
OL70IW
OL70ES
OL70SB

OL70SG
OL70NB
OL70IB
OL70MG
OL70SE
OL70SW

OKVIR LINE 7M

- dekorativni okvir LINE 7M
 - ustreza EN 60669-1
- COVER PLATE LINE 7M**
- decorative cover plate LINE 7M
 - in accordance with EN 60669-1



OL10PW
OL10IW
OL10ES
OL10SB

OL10SG
OL10NB
OL10IB
OL10MG
OL10SE
OL10SW

OKVIR LINE 1/2M

- dekorativni okvir LINE 1/2M
 - ustreza EN 60669-1
- COVER PLATE LINE 1/2M**
- decorative cover plate LINE 1/2M
 - in accordance with EN 60669-1



OL13PW
OL13IW
OL13ES
OL13SB

OL13SG
OL13NB
OL13IB
OL13MG
OL13SE
OL13SW

OKVIR LINE 1/3M

- dekorativni okvir LINE 1/3M
 - ustreza EN 60669-1
- COVER PLATE LINE 1/3M**
- decorative cover plate LINE 1/3M
 - in accordance with EN 60669-1



OL23PW
OL23IW
OL23ES
OL23SB


OL23SG
OL23NB
OL23IB
OL23MG
OL23SE
OL23SW

OKVIR LINE 2/3M


- dekorativni okvir LINE 2/3M
 - ustreza EN 60669-1
- COVER PLATE LINE 2/3M**
- decorative cover plate LINE 2/3M
 - in accordance with EN 60669-1

basic
basic


PW bela-sijaj
polar white




ES srebrna-mat
elox silver



IW bež-sijaj
ivory white



SB črna-mat
soft touch black




soft

C O V E R P L A T E S S O F T O S

dekor
decor

SG zlata-mat
sand gold



NG črna-sijaj
night black



WP smreka
spruce




WW oreh
walnut



WE wenge
wenge



MODUL



tip type	naziv description	velikost size	barva colour
OS10	OKVIR SOFT COVER PLATE SOFT	1/2M	PW bela-sijaj polar white
OS13	OKVIR SOFT COVER PLATE SOFT	1/3M	IW bež-sijaj ivory white
OS20	OKVIR SOFT COVER PLATE SOFT	2M	ES srebrna-mat elox silver
.	.	.	SB črna-mat soft touch black
.	.	.	



OS20PW	OS20SG
OS20IW	OS20NB
OS20ES	OS20WP
OS20SB	OS20WW

OKVIR SOFT 2M

- dekorativni okvir SOFT 2M
 - ustreza EN 60669-1
- COVER PLATE SOFT 2M**
- decorative cover plate SOFT 2M
 - in accordance with EN 60669-1



OS24PW	OS24SG
OS24IW	OS24NB
OS24ES	OS24WP
OS24SB	OS24WW

OKVIR SOFT 2x2M

- dekorativni okvir SOFT 2x2M
 - horizontalna ali vertikalna vgradnja
 - ustreza EN 60669-1
- COVER PLATE SOFT 2x2M**
- decorative cover plate SOFT 2x2M
 - horizontal or vertical mounting
 - in accordance with EN 60669-1



OS26PW	OS26SG
OS26IW	OS26NB
OS26ES	OS26WP
OS26SB	OS26WW

OKVIR SOFT 3x2M

- dekorativni okvir SOFT 3x2M
 - horizontalna ali vertikalna vgradnja
 - ustreza EN 60669-1
- COVER PLATE SOFT 3x2M**
- decorative cover plate SOFT 3x2M
 - horizontal or vertical mounting
 - in accordance with EN 60669-1



OS28PW	OS28SG
OS28IW	OS28NB
OS28ES	OS28WP
OS28SB	OS28WW

OKVIR SOFT 4x2M

- dekorativni okvir SOFT 4x2M
 - horizontalna ali vertikalna vgradnja
 - ustreza EN 60669-1
- COVER PLATE SOFT 4x2M**
- decorative cover plate SOFT 4x2M
 - horizontal or vertical mounting
 - in accordance with EN 60669-1

soft

C O V E R P L A T E S S O F T O S



OS30PW
OS30IW
OS30ES
OS30SB

OS30SG
OS30NB
OS30WP
OS30WW
OS30WE

OKVIR SOFT 3M

- dekorativni okvir SOFT 3M
- ustreza EN 60669-1
- COVER PLATE SOFT 3M**
- decorative cover plate SOFT 3M
- in accordance with EN 60669-1




OS40PW
OS40IW
OS40ES
OS40SB

OS40SG
OS40NB
OS40WP
OS40WW
OS40WE

OKVIR SOFT 4M

- dekorativni okvir SOFT 4M
- ustreza EN 60669-1
- COVER PLATE SOFT 4M**
- decorative cover plate SOFT 4M
- in accordance with EN 60669-1



OS70PW
OS70IW
OS70ES
OS70SB

OS70SG
OS70NB
OS70WP
OS70WW
OS70WE

OKVIR SOFT 7M

- dekorativni okvir SOFT 7M
- ustreza EN 60669-1
- COVER PLATE SOFT 7M**
- decorative cover plate SOFT 7M
- in accordance with EN 60669-1



OS72PW
OS72IW
OS72ES
OS72SB

OS70SG
OS70NB
OS70WP
OS70WW
OS70WE

OKVIR SOFT 2x7M

- dekorativni okvir SOFT 2x7M z napisno ploščico
- ustreza EN 60669-1
- COVER PLATE SOFT 2x7M**
- decorative cover plate SOFT 2x7M with inscription plate
- in accordance with EN 60669-1



OS10PW
OS10IW
OS10ES
OS10SB

OS10SG
OS10NB
OS10WP
OS10WW
OS10WE

OKVIR SOFT 1/2M

- dekorativni okvir SOFT 1/2M
- ustreza EN 60669-1
- COVER PLATE SOFT 1/2M**
- decorative cover plate SOFT 1/2M
- in accordance with EN 60669-1



OS13PW
OS13IW
OS13ES
OS13SB

OS13SG
OS13NB
OS13WP
OS13WW
OS13WE

OKVIR SOFT 1/3M

- dekorativni okvir SOFT 1/3M
- ustreza EN 60669-1
- COVER PLATE SOFT 1/3M**
- decorative cover plate SOFT 1/3M
- in accordance with EN 60669-1



OS23PW
OS23IW
OS23ES
OS23SB

OS23SG
OS23NB
OS23WP
OS23WW
OS23WE

OKVIR SOFT 2/3M

- dekorativni okvir SOFT 2/3M
- ustreza EN 60669-1
- COVER PLATE SOFT 2/3M**
- decorative cover plate SOFT 2/3M
- in accordance with EN 60669-1

**LASERSKI TISK NA OKVIRJE**

- laserski tisk poljubne grafike
- izdelava po naročilu
- primerne za okvirje OL, OS

LASER PRINT ON COVER PLATES


- laser print of any graphics
- made on request
- suitable for cover plates OL, OS

**DEKORACIJE OKVIRJEV**

- vzorci in barve po izbiri
- izdelava po naročilu
- primerne za okvirje OL, OS

COVER PLATES DECORATIONS


- customised textures and colours
- made on request
- suitable for cover plates OL, OS



F R A M E S

line
A x Bsoft
A x BPURE
A x B

2M




80 x 80 mm

84 x 84 mm

93 x 90 mm

2x2M




151 x 80 mm

155 x 84 mm

164 x 90 mm

3x2M




222 x 80 mm

226 x 84 mm

235 x 90 mm

4x2M




293 x 80 mm

297 x 84 mm



3M




122 x 80 mm

122 x 84 mm

134 x 90 mm

4M




149 x 80 mm

144 x 84 mm

157 x 90 mm

7M




207 x 80 mm

212 x 84 mm

224 x 90 mm


2x7M



212 x 158 mm




1/2M



80 x 80 mm

84 x 84 mm

1/3M




122 x 80 mm

122 x 84 mm

134 x 90 mm

2/3M




122 x 80 mm

122 x 84 mm


134 x 90 mm

K O M B I N A T O R I K A

E O D U L



C O M B I N A T I O N S






NM30

tip type	naziv description	velikost size
NM10	NOSILEC S KREMPELJCI MOUNTING FRAME WITH CLAWS	1/2M
NM11	NOSILEC BREZ VIJAKOV MOUNTING FRAME WITHOUT SCREWS	1/2M
NM20	NOSILEC S KREMPELJCI MOUNTING FRAME WITH CLAWS	2M

**NOSILEC S KREMPELJCI 2M**

NM20

- nosilec 2M s krempeljci
- montaža v doze Ø60 (DE..) s krempeljci
- možno horizontalno ali vertikalno nizanje 2x2M, 3x2M in 4x2M
- primeren za sestavo z okvirji LINE in SOFT
- ustreza EN 60669-1


**MOUNTING FRAME WITH CLAWS 2M**

- mounting frame 2M with claws
- for mounting on boxes Ø60 (DE..) with claws
- possible horizontal or vertical combinations 2x2M, 3x2M and 4x2M
- suitable for assembling with cover plates LINE and SOFT
- in accordance with EN 60669-1



NM21

- nosilec 2M brez vijakov in brez krempeljev
- montaža v doze Ø60 (HE.., BE..) z vijaki
- možno horizontalno ali vertikalno nizanje 2x2M, 3x2M in 4x2M
- primeren za sestavo z okvirji LINE in SOFT
- ustreza EN 60669-1


**MOUNTING FRAME WITHOUT SCREWS 2M**

- mounting frame 2M without screws and without claws
- for mounting on boxes Ø60 (HE.., BE..) with screws
- possible horizontal or vertical combinations 2x2M, 3x2M and 4x2M
- suitable for assembling with cover plates LINE and SOFT
- in accordance with EN 60669-1




NM24

- kovinski nosilec 2M s krempeljci - toga izvedba
- montaža v doze Ø60 (DE..) s krempeljci
- možno horizontalno ali vertikalno nizanje 2x2M, 3x2M in 4x2M
- primeren za sestavo z okvirji PURE, LINE in SOFT
- ustreza EN 60669-1


**MOUNTING FRAME METAL WITH CLAWS 2M**

- metal mounting frame 2M with claws - stiff version
- for mounting on boxes Ø60 (DE..) with claws
- possible horizontal or vertical combinations 2x2M, 3x2M and 4x2M
- suitable for assembling with cover plates PURE, LINE and SOFT
- in accordance with EN 60669-1



NM25

- kovinski nosilec brez vijakov in brez krempeljev - toga izvedba
- montaža v doze Ø60 (HE.., BE..) z vijaki
- možno horizontalno ali vertikalno nizanje 2x2M, 3x2M in 4x2M
- primeren za sestavo z okvirji PURE, LINE in SOFT
- ustreza EN 60669-1

**MOUNTING FRAME METAL WITHOUT SCREWS 2M**

- metal mounting frame 2M without screws and without claws - stiff version
- for mounting in boxes Ø60 (HE.., BE..) with screws
- possible horizontal or vertical combinations 2x2M, 3x2M and 4x2M
- suitable for assembling with cover plates PURE, LINE and SOFT
- in accordance with EN 60669-1

M O U N T I N G F R A M E S N M




NM30

NOSILEC Z VIJAKI 3M

- nosilec 3M z vijaki
- montaža v pravokotne doze velikosti 3M
- primeren za sestavo z okvirji PURE, LINE in SOFT
- ustreza EN 60669-1

MOUNTING FRAME WITH SCREWS 3M

- mounting frame 3M with screws
- for mounting on rectangular boxes 3M
- suitable for assembling with cover plates PURE, LINE and SOFT
- in accordance with EN 60669-1




NM40

NOSILEC Z VIJAKI 4M

- nosilec 4M z vijaki
- montaža v pravokotne doze velikosti 4M
- primeren za sestavo z okvirji PURE, LINE in SOFT
- ustreza EN 60669-1

MOUNTING FRAME WITH SCREWS 4M

- mounting frame 4M with screws
- for mounting on rectangular boxes 4M
- suitable for assembling with cover plates PURE, LINE and SOFT
- in accordance with EN 60669-1




NM70

NOSILEC Z VIJAKI 7M

- nosilec 7M z vijaki
- montaža v pravokotne doze velikosti 7M
- primeren za sestavo z okvirji PURE, LINE in SOFT
- ustreza EN 60669-1

MOUNTING FRAME WITH SCREWS 7M

- mounting frame 7M with screws
- for mounting on rectangular boxes 7M
- suitable for assembling with cover plates PURE, LINE and SOFT
- in accordance with EN 60669-1




NM72

NOSILEC Z VIJAKI 2x7M

- nosilec 2x7M z vijaki
- montaža v pravokotne doze velikosti 2x7M
- primeren za sestavo z okvirjem SOFT OS72
- ustreza EN 60669-1

MOUNTING FRAME WITH SCREWS 2x7M

- mounting frame 2x7M with screws
- for mounting on rectangular boxes 2x7M
- suitable for assembling with cover plate SOFT OS72
- in accordance with EN 60669-1






NM10

NOSILEC S KREMPELJCI 1/2M

- nosilec 1/2M s kремпелјци
- монтажа в дозе Ø60 (DE..) с крепелјци
- primeren za sestavo z okvirji LINE in SOFT
- ustreza EN 60669-1

MOUNTING FRAME WITH CLAWS 1/2M

- mounting frame 1/2M with claws
- for mounting on boxes Ø60 (DE..) with claws
- suitable for assembling with cover plates LINE and SOFT
- in accordance with EN 60669-1




NM11

NOSILEC BREZ VIJAKOV 1/2M

- nosilec 1/2M brez vijakov in brez krempeljev
- монтажа в дозе Ø60 (HE.., BE..) z vijaki
- primeren za sestavo z okvirji LINE in SOFT
- ustreza EN 60669-1

MOUNTING FRAME WITHOUT SCREWS 1/2M

- mounting frame 1/2M without screws and without claws
- for mounting on boxes Ø60 (HE.., BE..) with screws
- suitable for assembling with cover plates LINE and SOFT
- in accordance with EN 60669-1





NM23

NOSILEC S KREMPELJCI 2/3M

- nosilec 2/3M s kремпелјци
- монтажа в дозе Ø60 (DE..) с крепелјци
- primeren za sestavo z okvirji PURE, LINE in SOFT
- ustreza EN 60669-1

MOUNTING FRAME WITH CLAWS 2/3M

- mounting frame 2/3M with claws
- for mounting on boxes Ø60 (DE..) with claws
- suitable for assembling with cover plates PURE, LINE and SOFT
- in accordance with EN 60669-1




NM32

NOSILEC Z VIJAKI 2/3M

- nosilec 2/3M z vijaki
- монтажа в прavokotne doze velikosti 3M
- primeren za sestavo z okvirji PURE, LINE in SOFT
- ustreza EN 60669-1

MOUNTING FRAME WITH SCREWS 2/3M


- mounting frame 2/3M with screws
- for mounting on rectangular boxes 3M
- suitable for assembling with cover plates PURE, LINE and SOFT
- in accordance with EN 60669-1



M O U N T I N G F R A M E S N M

E O D U L

TEM



KATALOG /
CATALOGUE

D O Z E



OKROGLE DOZE
ROUND BOXES



134

PRAVOKOTNE DOZE
RECTANGULAR BOXES



142

RAZVODNE DOZE
JUNCTION BOXES



150

PRIBOR ZA OŽIČENJE
WIRING ACCESSORIES



152



DE12



HE11



BE10

tip type	naziv description	velikost size
DE10	DOZA OKROGLA ZA ZID ROUND BOX BRICK	SM60-01
HE10	DOZA OKROGLA ZA VOTLE STENE ROUND BOX HOLLOW WALL	SM68X40
BE10	DOZA OKROGLA ZA BETON ROUND BOX CONCRETE	
.	.	.
.	.	.


DOZA OKROGLA ZA ZID SM60-01



DE10

- Ø60, globina 40mm
- 650°C, 500V~
- ustreza IEC 60670-1
- "halogen free"

ROUND BOX BRICK SM60-01
 - Ø60, depth 40mm
 - 650°C, 500V~
 - in accordance with IEC 60670-1
 - halogen free




DOZA OKROGLA ZA ZID GLOBOKA SM60-06



DE11

- Ø60, globina 60mm
- 650°C, 500V~
- ustreza IEC 60670-1
- "halogen free"

ROUND BOX BRICK DEEP SM60-06
 - Ø60, depth 60mm
 - 650°C, 500V~
 - in accordance with IEC 60670-1
 - halogen free



VEZNI ČLEN DOZE ZA ZID SM60-03



DE30

- za vertikalno povezavo doz SM60-06 ali SM60-01 na razdaljo 91 mm
- ustreza IEC 60670-1
- "halogen free"

COMBI-CLIP SM60-03
 - for vertical fitting of boxes SM60-06 or SM60-01 on distance 91 mm
 - in accordance with IEC 60670-1
 - halogen free




VEZNI ČLEN DOZE ZA ZID SM60-04



DE31

- za horizontalno povezavo doz SM60-06 ali SM60-01 na razdaljo 71mm
- ustreza IEC 60670-1
- "halogen free"

COMBI-CLIP SM60-04
 - for horizontal fitting of boxes SM60-06 or SM60-01 on
 - distance 71mm
 - in accordance with IEC 60670-1
 - halogen free



R O U N D

B O X E S

D O Z E

DOZA OKROGLA ZA ZID MD65-46




DE12

- Ø65, globina 46mm
- 650°C, 500V~
- ustreza IEC 60670-1
- "halogen free"

ROUND BOX BRICK MD65-46

- Ø65, depth 46mm
- 650°C, 500V~
- in accordance with IEC 60670-1
- halogen free



DOZA OKROGLA ZA ZID GLOBOKA MD65-60




DE13

- Ø65/60, globina 62mm
- 650°C, 500V~
- ustreza IEC 60670-1
- "halogen free"

ROUND BOX BRICK DEEP MD65-60

- Ø65/60, depth 62mm
- 650°C, 500V~
- in accordance with IEC 60670-1
- halogen free



PODALJŠEK DOZE ZA ZID MD65-46




DE14

- Ø65/60, globina 17mm
- 650°C, 500V~
- ustreza IEC 60670-1
- "halogen free"

ADDITIONAL PIECE FOR MD65-46

- Ø65/60, depth 17mm
- 650°C, 500V~
- in accordance with IEC 60670-1
- halogen free




VEZNI ČLEN DOZE ZA ZID MD65-71



DE32

- za povezavo doz MD65 na razdaljo 71 mm
- ustreza IEC 60670-1
- "halogen free"




COMBI-CLIP MD65-71

- for fitting of boxes MD65 on distance 71mm
- in accordance with IEC 60670-1
- halogen free



DE33

- za povezavo doz MD65 na razdaljo 91mm
- ustreza IEC 60670-1
- "halogen free"



COMBI-CLIP MD65-91


- for fitting of boxes MD65 on distance 91mm
- in accordance with IEC 60670-1
- halogen free

POKROV DOZE ZAŠČITNI 60



DE20

- zaščitni pokrov doze Ø60 za DE13, DE14
- ustreza IEC 60670-1
- za zaščito pri ometavanju



BOX COVER PROTECTIVE 60

- protective cover for box Ø60 for DE13, DE14
- in accordance with IEC 60670-1
- box protection during plastering



DE21

- zaščitni pokrov doze Ø65 za DE12
- ustreza IEC 60670-1
- za zaščito pri ometavanju




BOX COVER PROTECTIVE 65

- protective cover for box Ø65 for DE12
- in accordance with IEC 60670-1
- box protection during plastering



DE22

- dekorativni pokrov doze Ø60
- ustreza IEC 60670-1
- "halogen free"









BOX COVER DECORATIVE SM60







- decorative cover for boxes Ø60
- in accordance with IEC 60670-1
- halogen free

navodila za montažo /
assembly instructions


DE10,11

razdalja med dozami /
distance between boxes: 71mmrazdalja med dozami /
distance between boxes: 91mm

DE12,13

* za okvirje PURE je minimalna razdalja
med dozami 100mm* for PURE cover plates the minimum distance between
boxes is 100mm

R O U N D B O X E S






HE10

DOZA OKROGLA ZA VOTLE STENE SM68x40

- Ø60, globina 40mm
- vgradnja v izvrtino Ø68
- 850°C, 400V~
- ustreza IEC 60670-1
- montaža s krempeljci
- "halogen free"

ROUND BOX HOLLOW WALL SM68x40

- Ø60, depth 40mm
- cutting hole Ø68
- 850°C, 400V~
- in accordance with IEC 60670-1
- mounting with claws
- halogen free




HE11

DOZA OKROGLA ZA VOTLE STENE SM68x55

- Ø60, globina 55mm
- vgradnja v izvrtino Ø68
- 850°C, 400V~
- ustreza IEC 60670-1
- montaža s krempeljci
- "halogen free"

ROUND BOX HOLLOW WALL SM68x55

- Ø60, depth 55mm
- cutting hole Ø68
- 850°C, 400V~
- in accordance with IEC 60670-1
- mounting with claws
- halogen free




BE10

DOZA OKROGLA ZA BETON

- Ø60mm, globina 49mm
- 650°C, 500V~
- ustreza IEC 60670-1
- "halogen free"

ROUND BOX CONCRETE

- Ø60mm, depth 49mm
- 650°C, 500V~
- in accordance with IEC 60670-1
- halogen free




BE11

DOZA OKROGLA ZA BETON GLOBOKA

- Ø60mm, globina 58mm
- 650°C, 500V~
- ustreza IEC 60670-1
- "halogen free"

ROUND BOX CONCRETE DEEP

- Ø60mm, depth 58mm
- 650°C, 500V~
- in accordance with IEC 60670-1
- halogen free




BE20

- za utrditev doze z distančnim profilom BM82 v nasprotno steno
- ustreza IEC 60670-1
- "halogen free"

COUNTER BOX SUPPORT CONCRETE

- to support concrete boxes with discance profile BM82 for extreme loads
- in accordance with IEC 60670-1
- halogen free




BE21

UVODNICA DOZE ZA BETON 16

- za utrditev instalacijske cevi
- ustreza IEC 60670-1
- "halogen free"

PIPE STOPPER CONCRETE BOX 16

- for firming installation pipe to box
- in accordance with IEC 60670-1
- halogen free




R O U N D

B O X E S

votle stene / hollow walls





beton / concrete




navodila za montažo /
assembly instructions


HE10,11









razdalja med dozami /
distance between boxes: 71mm



razdalja med dozami /
distance between boxes: 91mm



BE10



* za okvirje PURE je min. razdalja me dozami 100mm


* for PURE cover plates the minimum distance between boxes is 100mm

D O Z E

vølle stene / hollow walls



beton / concrete



HE10,11



BE10,11



NM21



NM25



2M

2xHE10,11



2xBE10,11



2xNM21



2xNM25



2x2M

2xHE10,11



2xBE10,11



2xNM21 2xNM25



3xHE10,11



3xBE10,11



3xNM21



3xNM25



3x2M


3xHE10,11



3xBE10,11



3xNM21 3xNM25



4xHE10,11



4xBE10,11



4xNM21



4xNM25



4x2M

4xHE10,11



4xBE10,11



4xNM21



4xNM25



HE10,11



BE10,11



NM11

1/2M

HE10,11




BE10,11



NM32


2/3M

R O U N D B O X E S




navodila za montažo /
assembly instructions

1




D O Z E


2



3



4





DM30



HM30



BM30


tip type	naziv description	velikost size
DM30	DOZA PRAVOKOTNA ZA ZID RECTANGULAR BOX BRICK	PM3
HM30	DOZA PRAVOKOTNA ZA VOTLE STENE RECTANGULAR BOX HOLLOW WALL	VM3
BM30	DOZA PRAVOKOTNA ZA BETON RECTANGULAR BOX CONCRETE	BM3
.	.	.
.	.	.
.	.	.

DOZA PRAVOKOTNA ZA ZID PM3

DM30

- velikost 3M, globina 49mm
- 650°C, 400V~
- ustreza IEC 60670-1
- "halogen free"


RECTANGULAR BOX BRICK PM3
 - size 3M, depth 49mm
 - 650°C, 400V~
 - in accordance with IEC 60670-1
 - halogen free

**DOZA PRAVOKOTNA ZA ZID PM3-65**

DM31

- velikost 3M, globina 65mm
- 650°C, 400V~
- ustreza IEC 60670-1
- "halogen free"


RECTANGULAR BOX BRICK PM3-65
 - size 3M, depth 65mm
 - 650°C, 400V~
 - in accordance with IEC 60670-1
 - halogen free

**DOZA PRAVOKOTNA ZA ZID PM4**

DM40

- velikosti 4M, globina 49mm
- 650°C, 400V~
- ustreza IEC 60670-1
- "halogen free"


RECTANGULAR BOX BRICK PM4
 - size 4M, depth 49mm
 - 650°C, 400V~
 - in accordance with IEC 60670-1
 - halogen free

**DOZA PRAVOKOTNA ZA ZID PM4-65**

DM41

- velikosti 4M, globina 65mm
- 650°C, 400V~
- ustreza IEC 60670-1
- "halogen free"

RECTANGULAR BOX BRICK PM4-65
 - size 4M, depth 65mm
 - 650°C, 400V~
 - in accordance with IEC 60670-1
 - halogen free



RECTANGULAR BOXES

DOZE




DM70

DOZA PRAVOKOTNA ZA ZID PM7

- velikost 7M, globina 49mm
- 650°C, 400V~
- ustreza IEC 60670-1
- "halogen free"

RECTANGULAR BOX BRICK PM7

- size 7M, depth 49mm
- 650°C, 400V~
- in accordance with IEC 60670-1
- halogen free




DM71

DOZA PRAVOKOTNA ZA ZID PM7-65

- velikost 7M, globina 65mm
- 650°C, 400V~
- ustreza IEC 60670-1
- "halogen free"

RECTANGULAR BOX BRICK PM7-65

- size 7M, depth 65mm
- 650°C, 400V~
- in accordance with IEC 60670-1
- halogen free




DM72

DOZA PRAVOKOTNA ZA ZID PM72-65

- velikost 2x7M, globina 64mm
- 650°C, 400V~
- ustreza IEC 60670-1
- "halogen free"

RECTANGULAR BOX BRICK PM72-65

- size 2x7M, depth 64mm
- 650°C, 400V~
- in accordance with IEC 60670-1
- halogen free






DM80

VEZNI ČLEN DOZE PM

- za vertikalno (B) in horizontalno (A) sestavo doz PM3, PM4 in PM7
- primeren za dekorativne okvirje Line in Soft (za PURE ni primeren)

DISTANCE PIECE FOR BOX PM

- for vertical (B) and horizontal (A) fitting of boxes PM3, PM4 and PM7
- suitable for Line and Soft decorative cover plates (not for PURE)






DM33

POKROV DOZE ZAŠČITNI PM3

- zaščitni pokrov doze PM3
- ustreza IEC 60670-1
- "halogen free"
- za zaščito pri ometavanju

BOX COVER PROTECTIVE PM3

- protective cover for box PM3
- in accordance with IEC 60670-1
- halogen free
- box protection during plastering




DM34

POKROV DOZE DEKORATIVNI PM3

- dekorativni pokrov doze 3M
- vijaka priložena
- ustreza IEC 60670-1
- "halogen free"

BOX COVER DECORATIVE PM3

- decorative cover for boxes 3M
- screws are included
- in accordance with IEC 60670-1
- halogen free




DM43

POKROV DOZE ZAŠČITNI PM4

- zaščitni pokrov doze PM4
- ustreza IEC 60670-1
- "halogen free"
- za zaščito pri ometavanju

BOX COVER PROTECTIVE PM4

- protective cover for box PM4
- in accordance with IEC 60670-1
- halogen free
- box protection during plastering




DM44

POKROV DOZE DEKORATIVNI PM4

- dekorativni pokrov doze 4M
- vijaka priložena
- ustreza IEC 60670-1
- "halogen free"

BOX COVER DECORATIVE PM4

- decorative cover for boxes 4M
- screws are included
- in accordance with IEC 60670-1
- halogen free




DM73

POKROV DOZE ZAŠČITNI PM7

- zaščitni pokrov doze PM7
- ustreza IEC 60670-1
- "halogen free"
- za zaščito pri ometavanju

BOX COVER PROTECTIVE PM7

- protective cover for box PM7
- in accordance with IEC 60670-1
- halogen free
- box protection during plastering




DM74

POKROV DOZE DEKORATIVNI PM7

- dekorativni pokrov doze 7M
- vijaka priložena
- ustreza IEC 60670-1
- "halogen free"

BOX COVER DECORATIVE PM7

- decorative cover for boxes 7M
- screws are included
- in accordance with IEC 60670-1
- halogen free



RECTANGULAR BOXES


POKROV DOZE DEKORATIVNI PM72

DM75

- dekorativni pokrov doze 2x7M
- vijaki priloženi
- ustreza IEC 60670-1

BOX COVER DECORATIVE PM72

- decorative cover for boxes 2x7M
- screws are included
- in accordance with IEC 60670-1



DOZE




HM30

DOZA PRAVOKOTNA ZA VOTLE STENE VM3

- velikost 3M, globina 49mm
- vgradnja v izvrtino 2xØ68/45mm
- 850°C, 400V~
- ustreza IEC 60670-1
- "halogen free"

RECTANGULAR BOX HOLLOW WALL VM3

- size 3M, depth 49mm
- cutting hole 2xØ68/45mm
- 850°C, 400V~
- in accordance with IEC 60670-1
- halogen free




HM40

DOZA PRAVOKOTNA ZA VOTLE STENE VM4

- velikost 4M, globina 49mm
- vgradnja v izvrtino 2xØ68/70mm
- 850°C, 400V~
- ustreza IEC 60670-1
- "halogen free"

RECTANGULAR BOX HOLLOW WALL VM4

- size 4M, depth 49mm
- cutting hole 2xØ68/70mm
- 850°C, 400V~
- in accordance with IEC 60670-1
- halogen free




HM70

DOZA PRAVOKOTNA ZA VOTLE STENE VM7

- velikost 7M, globina 49mm
- vgradnja v izvrtino 2xØ68/120mm
- 850°C, 400V~
- ustreza IEC 60670-1
- "halogen free"

RECTANGULAR BOX HOLLOW WALL VM7

- size 7M, depth 49mm
- cutting hole 2xØ68/120mm
- 850°C, 400V~
- in accordance with IEC 60670-1
- halogen free




HM72

DOZA PRAVOKOTNA ZA VOTLE STENE VM72

- velikost 2x7M, globina 63mm
- 850°C, 400V~
- ustreza IEC 60670-1
- "halogen free"

RECTANGULAR BOX HOLLOW WALL VM72

- size 2x7M, depth 63mm
- 850°C, 400V~
- in accordance with IEC 60670-1
- halogen free



RECTANGULAR BOXES

DOZE




BM30

DOZA PRAVOKOTNA ZA BETON BM3

- velikost 3M, globina 60mm
- 650°C, 400V~
- ustreza IEC 60670-1
- "halogen free"

RECTANGULAR BOX CONCRETE BM3

- size 3M, depth 60mm
- 650°C, 400V~
- in accordance with IEC 60670-1
- halogen free




BM40

DOZA PRAVOKOTNA ZA BETON BM4

- velikost 4M, globina 60mm
- 650°C, 400V~
- ustreza IEC 60670-1
- "halogen free"

RECTANGULAR BOX CONCRETE BM4

- size 4M, depth 60mm
- 650°C, 400V~
- in accordance with IEC 60670-1
- halogen free




BM70

DOZA PRAVOKOTNA ZA BETON BM7

- velikost 7M, globina 60mm
- 650°C, 400V~
- ustreza IEC 60670-1
- "halogen free"

RECTANGULAR BOX CONCRETE BM7

- size 7m, depth 60mm
- 650°C, 400V~
- in accordance with IEC 60670-1
- halogen free




BM80

PRITRDILNI ČLEN DOZ BM

- za hitro pritrditev pravokotnih doz BM na armaturno mrežo
- primerno za palice do premera Ø8mm

FIXING COMBI-CLIP BM

- for fast fixation of BM rectangular boxes on reinforcing bar
- suitable for bar diameter up to Ø8mm




BM82

DISTANČNI PROFIL ZA DOZE

- za utrditev doz BM skupaj z nosilcem doze za beton v nasprotno steno
- dolžina l=1m, premer Ø20mm

DISTANCE PROFILE FOR BOXES BM


- to support boxes BM with counter box support on opposite wall
- length l=1m, diameter Ø20mm






opeka / brick	votle stene / hollow walls	beton / concrete
DM30	NM30	3M
HM30		
BM30		
DM40	NM40	4M
HM40		
BM40		
DM70	NM70	7M
HM70		
BM70		
DM72	NM72	2x7M
HM72		
DM30	NM32	2/3M
HM30		
BM30		

RECTANGULAR BOXES



navodila za montažo /
assembly instructions






DW10

RAZVODNA DOZA OKROGLA ZA ZID DSM78

- Ø78, globina 40mm
- 650°C, 500V~
- ustreza IEC 60670-1 in IEC 60670-22
- "halogen free"

CONNECTION ROUND BOX BRICK DSM78

- Ø78, depth 40mm
- 650°C, 500V~
- in accordance with IEC 60670-1 and IEC 60670-22
- halogen free




HW10

RAZVODNA DOZA OKROGLA ZA VOTLE STENE SM78x45

- Ø78, globina 45mm
- vgradnja v izvritino Ø80
- 850°C, 400V~
- ustreza IEC 60670-1 in IEC 60670-22
- montaža s krempeljci
- "halogen free"

CONNECTION ROUND BOX HOLLOW WALL SM78x45

- Ø78, depth 45mm
- cutting hole Ø80
- 850°C, 400V~
- in accordance with IEC 60670-1 and IEC 60670-22
- mounting with claws
- halogen free




DE23

POKROV DOZE DEKORATIVNI SM78

- dekorativni pokrov doze Ø78
- ustreza IEC 60670-1 and IEC 60670-22
- "halogen free"

BOX COVER DECORATIVE SM78

- decorative cover for boxes Ø78
- in accordance with IEC 60670-1 and IEC 60670-22
- halogen free




DE24

POKROV DOZE ZAŠČITNI 78

- zaščitni pokrov doze Ø78
- ustreza IEC 60670-1 in IEC 60670-22
- "halogen free"

BOX COVER PROTECTIVE 78

- protective cover for box Ø78
- in accordance with IEC 60670-1 and IEC 60670-22
- halogen free




HW20

RAZVODNA DOZA KVADRATNA ZA ZID SM105x105

- 105x105mm, globina 50mm
- vgradnja v izvritino s priložencem šablono
- 850°C, 400V~
- ustreza IEC 60670-1 in IEC 60670-22
- montaža s krempeljci
- "halogen free"

CONNECTION SQUARE BOX BRICK SM105x105

- size 105x105mm, depth 50mm
- cutting hole according to attached template
- 850°C, 400V~
- in accordance with IEC 60670-1 and IEC 60670-22
- mounting with claws
- halogen free



J U N C T I O N B O X E S

D O Z E



UW10

tip type	naziv description	tehnični opis technical data	velikost size	barva colour
UW10	ENOREDNE SPONKE ZAPRTE 1 ROW TERMINAL BLOCKS	2x2.5mm ²	10P	<input checked="" type="checkbox"/> TS prozorna transparent
UW11	ENOREDNE SPONKE ZAPRTE 1 ROW TERMINAL BLOCKS	2x4mm ²	10P	<input type="checkbox"/> CO barvne colour
UW12	ENOREDNE SPONKE ZAPRTE 1 ROW TERMINAL BLOCKS	2x6mm ²	10P	<input type="checkbox"/> WH bela white
.	.	.	.	<input type="checkbox"/> GY siva grey
.	.	.	.	
.	.	.	.	

ENOREDNE SPONKE ZAPRTE




- 450V~; 2x2.5mm² ÷ 2x6mm²
- termoplast PC, prozorne
- število polov: 10

1 ROW TERMINAL BLOCKS CLOSED

- 450V~; 2x2.5mm² ÷ 2x6mm²
- thermoplast PC, transparent
- number of poles: 10

UW10TS	(NS12)	2x2.5mm ²	10P
UW11TS	(NS12)	2x4mm ²	10P
UW12TS	(NS12)	2x6mm ²	10P



ENOREDNE SPONKE




- 450V~; 2x2.5mm² ÷ 2x6mm²
- termoplast PA
- na voljo v različnih barvah
- število polov: 12


1 ROW TERMINAL BLOCKS

- 450V~; 2x2.5mm² ÷ 2x6mm²
- thermoplast PA
- available in different colours
- number of poles: 12

UW15CO	(NS12)	2x2.5mm ²	12P
UW16CO	(NS12)	2x4mm ²	12P
UW17CO	(NS12)	2x6mm ²	12P



DVOREDNE SPONKE PP



- 450 V~; 1 mm² ÷ 16 mm²
- termoplast polipropilen PP, bele
- za uporabo do 80°C
- število polov: 12

2 ROW TERMINAL BLOCKS PP


- 450V~, 1mm² ÷ 16mm²
- thermoplast polypropylene PP, white
- for temperatures up to 80°C
- number of poles: 12

	A	B	C	D	E
UW29WHPP	1.0-4.0mm ²	24 A	450 V		94,9
UW30WHPP	1.5-6.0mm ²	32 A	450 V		116,5
UW31WHPP	2.5-10mm ²	41 A	450 V		133,8
UW32WHPP	4-16mm ²	76 A	450 V		174,5
				20,7	25
				15	11

WIRING ACCESSORIES

D O Z E


DVOREDNE SPONKE PA



- 450 V~; 1 mm² ÷ 16 mm²
- termoplast poliamid PA, bele
- za uporabo do 110°C
- število polov: 12

2 ROW TERMINAL BLOCKS PA

- 450V~; 1mm² ÷ 16mm²
- thermoplast polyamide PA, white
- for temperatures up to 110°C
- number of poles: 12



UW25WHPA	1.0-4.0mm ²	24 A	450 V	
UW26WHPA	1.5-6.0mm ²	32 A	450 V	
UW27WHPA	2.5-10mm ²	41 A	450 V	
UW28WHPA	4-16mm ²	76 A	450 V	

A	B	C	D	E
93,6	13,4	16,2	8	6,4
117	15	18,6	10	7,3
132,8	17,3	22,2	11,5	10
173,9	20,8	25,2	15	11

BREZVIJAČNE SPONKE




- 24A 450V~, termoplast PA, sive
- število polov: 3÷8
- brezvijačni kontakti 0.5 ÷ 1.5mm², za trde žice
- ustreza EN 60998-1

PLUG-IN WIRE CONNECTORS

- 24A 450V~, thermoplast PA, grey
- number of poles: 3÷8
- plug-in contacts 0.5÷1.5mm², for rigide wires
- in accordance with EN 60998-1

UW40GY	PC153	1.5mm ²	3P	
UW41GY	PC155	1.5mm ²	5P	
UW42GY	PC158	1.5mm ²	8P	

A	B	C
12	18	9
17	18	9
26	18	9



BREZVIJAČNE SPONKE




- 24A 450V~, termoplast PA, sive
- število polov: 3÷5
- brezvijačni kontakti 1.5 ÷ 2.5mm², za trde žice
- ustreza EN 60998-1

PLUG-IN WIRE CONNECTORS

- 24A 450V~, thermoplast PA, grey
- number of poles: 3÷5
- plug-in contacts 1.5÷2.5mm², for rigide wires
- in accordance with EN 60998-1

UW45GY	PC253	2.5mm ²	3P	
UW46GY	PC254	2.5mm ²	4P	
UW47GY	PC255	2.5mm ²	5P	

A	B	C
14	19	9
17	19	9
21	19	9



BREZVIJAČNE SPONKE




- 24A 450V~, termoplast PA, sive
- število polov: 2 (trda žica)+1 (mehka žica)
- brezvijačni kontakti 1.5 ÷ 2.5mm²
- ustreza EN 60998-1

PLUG-IN WIRE CONNECTOR

- 24A 450V~, thermoplast PA, grey
- number of poles: 2 (rigide wire)+1 (soft wire)
- plug-in contacts 1.5÷2.5mm²
- in accordance with EN 60998-1

UW50WH	PC302	2.5mm ²	2/1P	
--------	-------	--------------------	------	--



TEM



KATALOG /
CATALOGUE

distribucija



OHIŠJA CUBO IP20 AC
BOXES CUBO IP20 AC



156

OHIŠJA CUBO IP55 AQ
BOXES CUBO IP55 AQ



157

PARAPETNI KANALI ALUMINIJSKI MA
TRUNKING SYSTEM ALUMINIUM MA



158

TALNE DOZE MT
FLOOR BOXES MT



163





RAZVODNE OMARICE MO
DISTRIBUTION BOARDS MO



166



tip type	naziv description	tehnični opis technical data	velikost size	barva colour
AC11	OHIŠJE NO CUBO Z DNOM <i>SURFACE MOUNT BOX WITH BACK SIDE COVER</i>	IP20	1M	<input type="checkbox"/> PW bela-sijaj polar white
AC21	OHIŠJE NO CUBO Z DNOM <i>SURFACE MOUNT BOX WITH BACK SIDE COVER</i>	IP20	2M	<input checked="" type="checkbox"/> ES srebrna-mat elox silver
AC41	OHIŠJE NO CUBO Z DNOM <i>SURFACE MOUNT BOX WITH BACK SIDE COVER</i>	IP20	4M	<input type="checkbox"/> IW bež-sijaj ivory white

OHIŠJE NO CUBO Z DNOM IP20 1M**OHIŠJE NO CUBO Z DNOM IP20 2M****OHIŠJE NO CUBO Z DNOM IP20 4M****OHIŠJE NO CUBO Z DNOM IP20 6M**

B O X E S C U B O I P 5 5 A Q



tip type	naziv description	tehnični opis technical data	velikost size	barva colour
AQ20	OHIŠJE NO CUBO OUTDOOR SURFACE MOUNT BOX	IP55	2M	<input type="checkbox"/> PW bela sijaj polar white
AQ22	OHIŠJE NO CUBO OUTDOOR SURFACE MOUNT BOX	IP55	2x2M	<input checked="" type="checkbox"/> GY siva grey
AQ30	OHIŠJE NO CUBO OUTDOOR SURFACE MOUNT BOX	IP55	3M	
AQ31	OHIŠJE NO CUBO OUTDOOR SURFACE MOUNT BOX	IP55	3M	

OHIŠJE NO CUBO IP55 2M



AQ20PW
 AQ20GY

- ohišje IP55 2M
- za nadomestno pritridlev
- IP55 za vgradnjo v vlažne prostore
- ustreza CEI 23-48, EN 60670



BOX NO CUBO IP55 2M
- box IP55 2M
- for surface mounting
- IP55 for usage in humid areas
- in accordance with CEI 23-48, EN 60670



AQ22PW
 AQ22GY

- ohišje IP55 2x2M
- za nadomestno pritridlev
- IP55 za vgradnjo v vlažne prostore
- ustreza CEI 23-48, EN 60670



BOX NO CUBO IP55 2x2M
- box IP55 2x2M
- for surface mounting
- IP55 for usage in humid areas
- in accordance with CEI 23-48, EN 60670



AQ30PW
 AQ30GY

- ohišje IP55 3M
- za nadomestno pritridlev
- IP55 za vgradnjo v vlažne prostore
- ustreza CEI 23-48, EN 60670



BOX NO CUBO IP55 3M
- box IP55 3M
- for surface mounting
- IP55 for usage in humid areas
- in accordance with CEI 23-48, EN 60670








AQ31PW
 AQ31GY

- ohišje IP55 3M
- za podometno pritridlev
- IP55 za vgradnjo v vlažne prostore
- ustreza CEI 23-48, EN 60670



BOX PO CUBO IP55 3M
- box IP55 3M
- for flush mounting
- IP55 for usage in humid areas
- in accordance with CEI 23-48, EN 60670





distribucija

ADAPTER MA 92			
	RT10	- adapter za pritrdiritev nosilcev 2/3M, 4M ali 7M Modul na kanal MA brez doze - vsak nosilec potrebuje dva adapterja - ustreza EN 50085-1	
	RT12ES RT12PW	- dekorativni okvir MA 2/3M - ustreza EN 50085-1 COVER PLATE MA 92 2/3M - decorative cover plate MA 2/3M - in accordance with EN 50085-1	
	RT14ES RT14PW	- dekorativni okvir MA 4M - ustreza EN 50085-1 COVER PLATE MA 92 4M - decorative cover plate MA 4M - in accordance with EN 50085-1	
	RT17ES RT17PW	- dekorativni okvir MA 7M - ustreza EN 50085-1 COVER PLATE MA 92 7M - decorative cover plate MA 7M - in accordance with EN 50085-1	

TRUNKING SYSTEM ALUMINIUM

distribucija




- RT20ES
- RT20PW

OSNOVA KANALA MA 130x65

- osnova kanala iz ekstrudiranega aluminija
- višina 130mm, dolžina 2m
- DIN letev 35mm na dnu
- ustreza EN 50085-1

TRUNKING BASE MA 130x65

- *trunking base from extruded aluminium*
- *height 130mm, lenght 2m*
- *DIN - rail 35mm shape on bottom*
- *in accordance with EN 50085-1*




- RT21ES
- RT21PW

OSNOVA KANALA MA 165x65

- osnova kanala iz ekstrudiranega aluminija
- višina 165mm, dolžina 2m
- DIN letev 35mm na dnu
- ustreza EN 50085-1

TRUNKING BASE MA 165x65

- *trunking base from extruded aluminium*
- *height 165mm, lenght 2m*
- *DIN - rail 35mm shape on bottom*
- *in accordance with EN 50085-1*




- RT25ES
- RT25PW

POKROV KANALA MA 92

- pokrov kanala iz ekstrudiranega aluminija
- višina 92mm, dolžina 2m
- ustreza EN 50085-1

FRONT COVER MA 92

- *front cover from extruded aluminium*
- *height 92mm, lenght 2m*
- *in accordance with EN 50085-1*




RT30

PREGRADA MA 43

- pregrada kanala iz ekstrudiranega polimera
- globina 43mm, dolžina 2m
- ustreza EN 50085-1

CABLE SHELF MA 43

- *cable shelf from extruded polymer*
- *depth 43mm, lenght 2m*
- *in accordance with EN 50085-1*




RT31

PREGRADA MA 43 AL

- pregrada kanala iz ekstrudiranega aluminija
- globina 43mm, dolžina 2m
- ustreza EN 50085-1

CABLE SHELF MA 43 AL

- *cable shelf from extruded aluminium*
- *depth 43mm, lenght 2m*
- *in accordance with EN 50085-1*




RT32

PREGRADA MA 43 AL DVOJNA

- dvojna pregrada kanala iz ekstrudiranega aluminija
- globina 43mm, dolžina 2m
- ustreza EN 50085-1

CABLE SHELF MA 43 AL DOUBLE

- *double cable shelf from extruded aluminium*
- *depth 43mm, lenght 2m*
- *in accordance with EN 50085-1*





RT35ES
 RT35PW

KONČNI ELEMENT MA 130x65

- končni element iz polimera
- višina 130mm
- ustreza EN 50085-1

STOP END MA 130x65

- stop end element from polymer
- height 130mm
- in accordance with EN 50085-1



RT36ES
 RT36PW

KONČNI ELEMENT MA 165x65

- končni element iz kovine
- višina 165mm
- ustreza EN 50085-1

STOP END MA 165x65

- stop end element from metal
- height 165mm
- in accordance with EN 50085-1



RT38

SET RAVNI VEZNI ELEMENT MA 65

- vezni element iz polimera
- set vsebuje 2 vezna elementa in vijke
- ustreza EN 50085-1

SET JOINING PIECE MA 65

- joining piece from polymer
- set contains two pieces and screws
- in accordance with EN 50085-1



RT40ES
 RT40PW

UNIVERZALNI KOT MA 130x65

- univerzalni kotni element
- višina 130mm
- ustreza EN 50085-1

UNIVERSAL CORNER MA 130x65

- universal corner element
- height 130mm
- in accordance with EN 50085-1



RT41ES
 RT41PW

UNIVERZALNI KOT MA 165x65

- univerzalni kotni element
- višina 165mm
- ustreza EN 50085-1

UNIVERSAL CORNER MA 165x65

- universal corner element
- height 165mm
- in accordance with EN 50085-1




RT42

OZEMLJITVENA SPONKA MA 2x A6.3

- ozemljitvena sponka za ozemljitev osnove
in pokrova kanala
- ustreza EN 50085-1

EARTHING PIECE MA 2x A6.3

- earthing piece for earthing of trunking base
and front cover
- in accordance with EN 50085-1



TRUNKING SYSTEM ALUMINIUM




■ RT43ES
□ RT43PW

L KOTNI ELEMENT MA 130x65

- univerzalni L kotni element iz aluminija
- višina 130mm, dolžina 400mm
- ustreza EN 50085-1

L-BEND MA 130x65

- universal L bend element from aluminium
- height 130mm, lenght 400mm
- in accordance with EN 50085-1




■ RT44ES
□ RT44PW

L KOTNI ELEMENT MA 165x65

- univerzalni L kotni element iz aluminija
- višina 165mm, dolžina 400mm
- vezava na MA 130x65
- ustreza EN 50085-1

L-BEND MA 165x65

- universal L bend element from aluminium
- height 165mm, lenght 400mm
- connection on MA 130x65
- in accordance with EN 50085-1




■ RT45ES
□ RT45PW

T ELEMENT MA 130x65

- univerzalni T kotni element iz aluminija
- višina 130mm, dolžina 400mm
- ustreza EN 50085-1

T-BEND MA 130x65

- universal T bend element from aluminium
- height 130mm, lenght 400mm
- in accordance with EN 50085-1




■ RT46ES
□ RT46PW

T ELEMENT MA 165x65

- univerzalni T kotni element iz aluminija
- višina 165mm, dolžina 400mm
- vezava na MA 130x65
- ustreza EN 50085-1

T-BEND MA 165x65

- universal T bend element from aluminium
- height 165mm, lenght 400mm
- connection on MA 130x65
- in accordance with EN 50085-1



MA je modularni sistem za velikosti:
2M, 4M, 7M

MA trunking is based on modular system making 2M, 4M or 7M combinations of elements




Modul vsebuje tudi elemente pripravljene za hitro montažo

In Modul we provide special elements for quick installation



Adapter MA omogoča natančno pozicioniranje na rob kanala

With Adapter MA exact positioning without extra effort is provided



Montaža brez doze pomeni več prostora za kable, DIN letev oblika EN-60715

Mounted without box means more space for cables, DIN-rail base shape EN-60715



NOSILEC STEBRIČKA MA ENOJNI 130x65



- RT50ES
- RT50PW

FIXING PLATE MA SINGLE 130x65

- nosilec za pritrditev kanala MA130 v tla in/ali v strop prostora
- ustreza EN 50085-1
- fixing plate for fixing trunking base MA130 on the floor and/or on the ceiling
- in accordance with EN 50085-1



- RT51ES
- RT51PW

NOSILEC STEBRIČKA MA DVOJNI 130x65

- nosilec za pritrditev dveh kanalov MA130 v tla in/ali v strop prostora
- ustreza EN 50085-1

FIXING PLATE MA DOUBLE 130x65

- fixing plate for fixing two trunking bases MA130 on the floor and/or on the ceiling
- in accordance with EN 50085-1




STEBRIČEK MA 130x65x500

- RT52ES
- RT52PW

SERVICE POST MA 130x65x500

- instalacijski stebriček MA
- višina 500mm
- nosilca 7M vgrajen
- ustreza EN 50085-1
- service post MA
- height 500mm
- mounting frame 7M included
- in accordance with EN 50085-1



- RT53ES
- RT53PW

STEBRIČEK MA DVOJNI 130x130x500

- instalacijski stebriček MA dvojni
- višina 500mm
- nosilca 7M vgrajena
- ustreza EN 50085-1

SERVICE POST MA DOUBLE 130x130x500

- service post MA double
- height 500mm
- mounting frames 7M included
- in accordance with EN 50085-1

Presek vodnika / Cable intersection mm ²	Uporabni presek kablov / Cable cross-section (mm ²)				
	1 vodnik / 1 wire	2 vodnika / 2 wires	3 vodniki / 3 wires	4 vodniki / 4 wires	5 vodnikov / 5 wires
1,5	44	111	121	144	169
2,5	49	133	157	169	211
4	58	169	183	211	256
6	68	196	225	256	307

Kapaciteta kanala / Trunk capacity				
kanal / Trunk	MA 130x65 prazen / empty	MA 130x65 z Modul opremo / with Modul switches and sockets	MA 165x65 prazen / empty	MA 130x65 z Modul opremo / with Modul switches and sockets
kapaciteta capacity	7600 mm ²	5500 mm ²	9900 mm ²	7800 mm ²
max ø	54 mm	2x42 mm	54 mm	2x42 mm



F L O O R B O X E S M T



RB33

tip type	naziv description	tehnični opis technical data
RB30	TALNA DOZA <i>FLOOR BOX</i>	MT 7
RB31	PODSTAVEK TALNE DOZE <i>FLOOR BOX FLANGE</i>	MT 7
RB33	TALNA DOZA <i>FLOOR BOX</i>	MT 14
.	.	.
.	.	.
.	.	.

	RB30	RB33	RB36	RB40	RB43	RB46
a	170	260	350	170	260	350
b	260	260	260	260	260	260
X	140	230	320	140	230	320
Y	230	230	230	230	230	230



	RB31	RB34	RB37	RB41	RB44	RB47
A	250	340	430	250	340	430
B	340	340	340	340	340	340
C	95-125	95-125	95-125	125-150	125-150	125-150



RB30

TALNA DOZA MT 7

- talna doza MT 7
- kovinska, barva srebrna RAL 9006
- nosilec MODUL 7M vgrajen
- vgradna mera 140x230mm, globina min 95mm
- debelina talne obloge pokrova do 10mm
- ustreza EN 50085-1 in EN 50085-2-2

FLOOR BOX MT 7

- floor box MT 7
- metal, colour silver RAL 9006
- mounting frame MODUL 7M included
- mounting dimensions 140x230mm, depth min 95mm
- floor lining thickness up to 10mm
- in accordance with EN 50085-1 and EN 50085-2-2



RB40

TALNA DOZA MT 7 H=88mm

- talna doza MT 7
- kovinska, barva srebrna RAL 9006
- nosilec MODUL 7M vgrajen
- vgradna mera 140x230mm, globina min 120mm
- debelina talne obloge pokrova do 10mm
- ustreza EN 50085-1 in EN 50085-2-2

FLOOR BOX MT 7 H=88mm

- floor box MT 7
- metal, colour silver RAL 9006
- mounting frame MODUL 7M included
- mounting dimensions 140x230mm, depth min 120mm
- floor lining thickness up to 10mm
- in accordance with EN 50085-1 and EN 50085-2-2



RB31

PODSTAVEK TALNE DOZE MT 7

- podstavek talne doze za pokrov MT 7
- kovinski, cinkan
- za vgradnjo v tlak ali dvojni pod
- nastavljiva višina 95-125mm
- ustreza EN 50085-1 in EN 50085-2-2

FLOOR BOX FLANGE MT 7

- floor box flange for box cover MT 7
- metal, galvanized
- for installation in a floor or double floor
- adjustable height 95-125mm
- in accordance with EN 50085-1 and EN 50085-2-2



RB41

PODSTAVEK TALNE DOZE MT 7 H=88mm

- podstavek talne doze za pokrov MT 7 H=88mm
- kovinski, cinkan
- za vgradnjo v tlak ali dvojni pod
- nastavljiva višina 125-150mm
- ustreza EN 50085-1 in EN 50085-2-2

FLOOR BOX FLANGE MT 7 H=88mm

- floor box flange for box cover MT 7 H=88mm
- metal, galvanized
- for installation in a floor or double floor
- adjustable height 125-150mm
- in accordance with EN 50085-1 and EN 50085-2-2



RB33

TALNA DOZA MT 14

- floor box MT 14
- metal, colour silver RAL 9006
- mounting frames MODUL 2x7M included
- mounting dimensions 230x230mm, depth min 95mm
- floor lining thickness up to 10mm
- in accordance with EN 50085-1 and EN 50085-2-2

FLOOR BOX MT 14

- floor box MT 14
- metal, colour silver RAL 9006
- mounting frame MODUL 7M included
- mounting dimensions 140x230mm, depth min 95mm
- floor lining thickness up to 10mm
- in accordance with EN 50085-1 and EN 50085-2-2



RB43


TALNA DOZA MT 14 H=88mm

- talna doza MT 14
- kovinska, barva srebrna RAL 9006
- nosilca MODUL 2x7M vgrajena
- vgradna mera 230x230mm, globina min 120mm
- debelina talne obloge pokrova do 10mm
- ustreza EN 50085-1 in EN 50085-2-2

FLOOR BOX MT 14 H=88mm

- floor box MT 14
- metal, colour silver RAL 9006
- mounting frames MODUL 2x7M included
- mounting dimensions 230x230mm, depth min 120mm
- floor lining thickness up to 10mm
- in accordance with EN 50085-1 and EN 50085-2-2

F L O O R B O X E S M T




RB34

PODSTAVEK TALNE DOZE MT 14

- podstavek talne doze za pokrov MT 14
- kovinski, cinkan
- za vgradnjo v tlak ali dvojni pod
- nastavljiva visina 95-125mm
- ustreza EN 50085-1 in EN 50085-2-2

FLOOR BOX FLANGE MT 14

- floor box flange for box cover MT 14
- metal, galvanized
- for installation in a floor or double floor
- adjustable height 95-125mm
- in accordance with EN 50085-1 and EN 50085-2-2



RB44

PODSTAVEK TALNE DOZE MT 14 H=88mm

- podstavek talne doze za pokrov MT 14 H=88mm
- kovinski, cinkan
- za vgradnjo v tlak ali dvojni pod
- nastavljiva visina 125-150mm
- ustreza EN 50085-1 in EN 50085-2-2

FLOOR BOX FLANGE MT 14 H=88mm

- floor box flange for box cover MT 14 H=88mm
- metal, galvanized
- for installation in a floor or double floor
- adjustable height 125-150mm
- in accordance with EN 50085-1 and EN 50085-2-2



RB36

TALNA DOZA MT 21

- talna doza MT 21
- kovinska, barva srebrna RAL 9006
- nosilci MODUL 3x7M vgrajeni
- vgradna mera 320x230mm, globina min 95mm
- debelina talne obloge pokrova do 10mm
- ustreza EN 50085-1 in EN 50085-2-2

FLOOR BOX MT 21

- floor box MT 21
- metal, colour silver RAL 9006
- mounting frames MODUL 3x7M included
- mounting dimensions 320x230mm, depth min 95mm
- floor lining thickness up to 10mm
- in accordance with EN 50085-1 and EN 50085-2-2



RB46

TALNA DOZA MT 21 H=88mm

- talna doza MT 21
- kovinska, barva srebrna RAL 9006
- nosilci MODUL 3x7M vgrajeni
- vgradna mera 320x230mm, globina min 120mm
- debelina talne obloge pokrova do 10mm
- ustreza EN 50085-1 in EN 50085-2-2

FLOOR BOX MT 21 H=88mm

- floor box MT 21
- metal, colour silver RAL 9006
- mounting frames MODUL 3x7M included
- mounting dimensions 320x230mm, depth min 120mm
- floor lining thickness up to 10mm
- in accordance with EN 50085-1 and EN 50085-2-2



RB37

PODSTAVEK TALNE DOZE MT 21

- podstavek talne doze za pokrov MT 21
- kovinski, cinkan
- za vgradnjo v tlak ali dvojni pod
- nastavljiva visina 95-125mm
- ustreza EN 50085-1 in EN 50085-2-2

FLOOR BOX FLANGE MT 21

- floor box flange for box cover MT 21
- metal, galvanized
- for installation in a floor or double floor
- adjustable height 95-125mm
- in accordance with EN 50085-1 and EN 50085-2-2




RB47

PODSTAVEK TALNE DOZE MT 21 H=88mm

- podstavek talne doze za pokrov MT 21 H=88mm
- kovinski, cinkan
- za vgradnjo v tlak ali dvojni pod
- nastavljiva visina 125-150mm
- ustreza EN 50085-1 in EN 50085-2-2

FLOOR BOX FLANGE MT 21 H=88mm

- floor box flange for box cover MT 21 H=88mm
- metal, galvanized
- for installation in a floor or double floor
- adjustable height 125-150mm
- in accordance with EN 50085-1 and EN 50085-2-2



RB20

tip type	naziv description	tehnični opis technical data
RB10	ADAPTER ZA DIN LETEV ADAPTER FOR DIN RAIL	35mm 1M
RB11	ADAPTER ZA DIN LETEV ADAPTER FOR DIN RAIL	35mm 2M
RB20	RAZVODNA OMARICA DISTRIBUTION BOX	MO 12+2
.	.	.


ADAPTER ZA DIN LETEV 35mm 1M

RB10

- adapter MODUL 1M
- za DIN letev 35mm
- ustreza EN 50022

ADAPTER FOR DIN RAIL 35mm 1M

- adapter MODUL 1M
- for DIN rail 35mm
- in accordance with EN 50022


**ADAPTER ZA DIN LETEV 35mm 2M**

RB11

- adapter MODUL 2M
- za DIN letev 35mm
- ustreza EN 50022

ADAPTER FOR DIN RAIL 35mm 2M

- adapter MODUL 2M
- for DIN rail 35mm
- in accordance with EN 50022





RB20

RAZVODNA OMARICA MO 12+2


- razvodna omarica MO enoredna 12+2MU
- 400V~, razred zaščite II, IP40
- kovinska vratca in okvir, barva bela RAL 9016
- ozemljitvene in ničelne sponke priložene
- za vgradnjo v zid
- ustreza EN 60670-1 in IEC 60670-24

DISTRIBUTION BOX MO 12+2

- distribution box MO single row 12+2MU
- 400V~, Class II, IP40
- metal leveling frame and door, colour white RAL 9016
- neutral and earth conductor terminals enclosed
- for brick wall mounting
- in accordance with EN 60670-1 and IEC 60670-24

RB20VO

- za vgradnjo v votle stene
- for hollow wall mounting



RB21


- razvodna omarica MO dvoredna 24+4MU
- 400V~, razred zaščite II, IP40
- kovinska vratca in okvir, barva bela RAL 9016
- ozemljitvene in ničelne sponke priložene
- za vgradnjo v zid
- ustreza EN 60670-1 in IEC 60670-24

DISTRIBUTION BOX MO 24+4

- distribution box MO double row 24+4MU
- 400V~, Class II, IP40
- metal leveling frame and door, colour white RAL 9016
- neutral and earth conductor terminals enclosed
- for brick wall mounting
- in accordance with EN 60670-1 and IEC 60670-24

RB21VO

- za vgradnjo v votle stene
- for hollow wall mounting



RB22


- razvodna omarica MO triredna 36+6MU
- 400V~, razred zaščite II, IP40
- kovinska vratca in okvir, barva bela RAL 9016
- ozemljitvene in ničelne sponke priložene
- za vgradnjo v zid
- ustreza EN 60670-1 in IEC 60670-24

DISTRIBUTION BOX MO 36+6

- distribution box MO triple row 36+6 MU
- 400V~, Class II, IP40
- metal leveling frame and door, colour white RAL 9016
- neutral and earth conductor terminals enclosed
- for brick wall mounting
- in accordance with EN 60670-1 and IEC 60670-24

RB22VO

- za vgradnjo v votle stene
- for hollow wall mounting



RB23



- razvodna omarica MO štiriredna 48+8MU
- 400V~, razred zaščite II, IP40
- kovinska vratca in okvir, barva bela RAL 9016
- ozemljitvene in ničelne sponke priložene
- za vgradnjo v zid
- ustreza EN 60670-1 in IEC 60670-24

DISTRIBUTION BOX MO 48+8

- distribution box MO quad row 48+8 MU
- 400V~, Class II, IP40
- metal leveling frame and door, colour white RAL 9016
- neutral and earth conductor terminals enclosed
- for brick wall mounting
- in accordance with EN 60670-1 and IEC 60670-24

RB23VO

- za vgradnjo v votle stene
- for hollow wall mounting



	RB20 RB20VO	RB21 RB21VO	RB22 RB22VO	RB23 RB23VO
x	314	314	314	314
y	314	414	539	724



ekonomik®



Planned for excellence
Style is essential



ERGO

METAL

SOFT

Nevtralen, kompakten, eleganten dizajn se prilagodi v vsako okolje v katerem bivate ali delate. V interierju ne izstopa temveč z njim harmonično zaživi.

A neutral, compact, elegant design is adjustable to every working or living area. It does not stick out from the interior, but rather harmonically fits into it.





Načrtovano za odličnost Bistven je slog



Čista linija ekonomik je nežno zaobljena premišljena ergonomija posebej za vas.

A pure line is slightly curved - well considered ergonomics especially for you.



Izbirate lahko med sijajno refleksnimi površinami in sodobnim kovinskim izgledom.

You can choose between shiny reflective surfaces and modern metallic look.



Mehkost oblike bo našla prostor v modernih in klasičnih interierjih.

The softness of the form will find its place in modern as well as in classic interiors.

HARMONY

REFLEX

UV PROTECT

Želje so različne. Zato smo za vas pozorno izbrali možnosti, ki vam nudijo pravi odgovor. Nevtralna paleta barv bo le dopolnila vaš ambient - ne bo vas omejeval.

Desires can be very different. Therefore we have carefully selected possibilities for you, which can offer you the right answer. A neutral palette of colours will only complement your ambient - it will not restrict it.

Press and the world will spring to life
Colourful landscape between walls



Refleksne občutke vam nudijo sijajni polimerni materiali v beli in biserno beli (beige) barvi.

Shiny polymer materials in white and beige colours enable reflective mood.



Moderen in nevtralen je tudi izbrani dekorativni kovinski nanos.

Selected decorative metallic coat is at the same time modern and neutral.

Pritisnite in svet bo zaživel Barvita pokrajina med stenami




Za vse vas, ki se želite igrati s pastelnimi barvami je rešitev Ekonomik Color.

For those who want to play with pastel colours Ekonomik Color represents a perfect solution.



Robustnost in visoka odpornost na zunanje vplive (UV) je zagotovljena z duroplastičnim materialom (Color).

Robustness and high resistance to external effects (UV) are secured by duroplastic materials (Color line).



VERTICAL

HORIZONTAL

SAVE SPACE



S sestavljanjem prihranite prostor na steni. Ko imate malo prostora, je navpično prava odločitev.

With combining you save space on the wall. When faced with a limited space, »vertically« is the right decision.




Kombinirajte kot sami želite.

Combine as you please.



Vidni elementi se enostavno demontirajo. Hvaležni vam bodo tudi pleskarski mojstri.

Visible elements can be easily taken apart. Painters will be grateful to you.



Prolonge your day with a touch
Simplified living


Z dotikom si podaljšamo dan Poenostavljeni bivanje

Ekonomik je rešitev za sistem standardnih okroglih doz. Z njim lahko načrtujete tako enostavne kot tudi zahtevnejše inštalacije, novogradnje in adaptacije. Sistem odlikujejo brezvijačni kontakti, ki vam prihranijo čas pri vgradnji elementov.

Ekonomik is a solution for the system of standardized round installations boxes. It can be used for simple as well as more demanding installations, new buildings and adaptations. The system is characterised by plug-in contacts which save time during installation of elements.

Dobro počutje v varnem zavetju

Popolno zaupanje v dobro konstrukcijo




S skrbnim načrtovanjem smo poskrbeli, da so elementi pod napetostjo zaščiteni pred dotikom. Osnovno pritrjevanje mehanizmov s krempeljci ① lahko dodatno utrdite z vijaki ②. Ta način je še posebej primeren za varno in zanesljivo pritrditev vtičnice.

By careful planning elements under voltage have been protected against touching. Basic fixing of mechanisms with fixing claws ① allows additional strengthening with screws ②. This manner is especially appropriate for safe and reliable fixing of sockets.

SIMPLE


FAST

FLEX



Dobro premišljena konstrukcija stikala omogoča enostavno osvetlitev tudi naknadno.

A well-planned switch construction makes easy illumination possible also subsequently.



Brezvijačni kontakti omogočajo hitro in zanesljivo priključitev vodnikov. Na isti kontakt lahko pritrdite dva vodnika različnih premerov.

Plug-in contacts enable quick and reliable attachment of wires. Two wires of different diameters can be attached to the same contact.

Sestavljive doze vam bodo olajšale delo. Prave razdalje so vam zagotovljene.

Easy-fitting installation boxes will make your work easier. Proper lengths are guaranteed.



Stikala so preizkušena po mednarodnih standardih, ki zagotavljajo varnost in dolgo življenjsko dobo.

Switches were tested according to international standards which guarantee safety and long life span.



Za zanesljivost preklopa skrbijo kontakti iz srebrne zlitine (AgNi).


Contacts made of silver alloy (Ag-Ni) guarantee safe switching.

Feeling well in a safe shelter Total confidence in a good construction

SAFE

THRUST

CERTIFIED



Krempeljci omogočajo globljo pritrditev (tudi preko keramičnih ploščic ipd.).

Fixing claws enable deeper fixing (also through ceramic tiles, etc.)



Vsa stikala imajo jasno identifikacijo z zadnje strani.

All switches have a clear identification in the back.

TEM



KATALOG /
CATALOGUE

ekonomik



STIKALA SE
SWITCHES SE



180

TIPKE TE
BUTTONS TE



184

INDIKACIJA IA
ILLUMINATION IA



185

VTIČNICE VE
SOCKETS VE



187

KOMUNIKACIJE KE
COMMUNICATIONS KE



191

POKROVI PE
COVERS PE



195

ELEKTRONIKA EE
ELECTRONICS EE



196

PRIBOR AE
ACCESSORIES AE



201

OKVIRJI OE
SURROUNDS OE



203


tip type	naziv description	tehnični opis technical data	barva colour	opcijski opis 1 optional data 1	opcijski opis 2 optional data 2
SE10	STIKALO ENOPOLNO SWITCH 1WAY	10AX 250V~	<input type="checkbox"/> PW bela-sijaj polar white	NT nevral neutral	50
SE11	TIPKALO ENOPOLNO PUSH BUTTON 1WAY	10A 250V~	<input checked="" type="checkbox"/> IW bež-sijaj ivory white		51
SE22	STIKALO DVOPOLNO SWITCH 2POLE	16AX 250V~	<input type="checkbox"/> ES srebrna-mat elox silver	IN indikator indicator	03
.	.	.	<input type="checkbox"/> CO beli duroplast white thermoset		04
.	.	.	<input checked="" type="checkbox"/> NB črna-sijaj night black		.

STIKALO ENOPOLNO 10AX 250V~



SE10

- 10AX 250V~, tip SE10
 - ustreza EN 60669-1
 - brezvijačna pritrditev vodnikov 1.5-2.5mm²
- SWITCH 1WAY 10AX 250V~**
- 10AX 250V~, type SE10
 - in accordance with EN 60669-1
 - plug-in contacts 1.5-2.5mm²




TIPKALO ENOPOLNO 10A 250V~



SE11

- 10A 250V~, tip SE11
 - ustreza EN 60669-1
 - brezvijačna pritrditev vodnikov 1.5-2.5mm²
- PUSH BUTTON 1WAY 10A 250V~**
- 10A 250V~, type SE11
 - in accordance with EN 60669-1
 - plug-in contacts 1.5-2.5mm²




STIKALO DVOPOLNO 16AX 250V~



SE22

- 16AX 250V~, tip SE22
 - ustreza EN 60669-1
 - vijačna pritrditev vodnikov 1.5-2.5mm²
 - samo v kombinaciji s tipko TE10_NT03
- SWITCH 2POLE 16AX 250V~**
- 16AX 250V~, type SE22
 - in accordance with EN 60669-1
 - screw contacts 1.5-2.5mm²
 - only in combination with button TE10_NT03




STIKALO SERIJSKO 10AX 250V~



SE50

- 10AX 250V~, tip SE50
 - ustreza EN 60669-1
 - brezvijačna pritrditev vodnikov 1.5-2.5mm²
- SWITCH 2GANG-1WAY 10AX 250V~**
- 10AX 250V~, type SE50
 - in accordance with EN 60669-1
 - plug-in contacts 1.5-2.5mm²





S W I T C H E S S E



TIPKALO SERIJSKO 10A 250V~

SE51



- 10A 250V~, tip SE51
- ustreza EN 60669-1
- brezvijačna pritridlev vodnikov 1.5-2.5mm²
- PUSH BUTTON 2GANG-1WAY 10A 250V~**
- 10A 250V~, type SE51
- in accordance with EN 60669-1
- plug-in contacts 1.5-2.5mm²



STIKALO ŽALUZIJSKO 10AX 250V~

SE52



- 10AX 250V~, tip SE52
- ustreza EN 60669-1
- brezvijačna pritridlev vodnikov 1.5-2.5mm²
- z mehansko blokado hkratnega vklopa



TIPKALO ŽALUZIJSKO 10A 250V~

SE53

- 10A 250V~, tip SE53
- ustreza EN 60669-1
- brezvijačna pritridlev vodnikov 1.5-2.5mm²
- z mehansko blokado hkratnega vklopa





STIKALO MENJALNO 10AX 250V~

SE60

- 10AX 250V~, tip SE60
- ustreza EN 60669-1
- brezvijačna pritridlev vodnikov 1.5-2.5mm²

SWITCH 2WAY 10AX 250V~

- 10AX 250V~, type SE60
- in accordance with EN 60669-1
- plug-in contacts 1.5-2.5mm²





STIKALO DVOJNO MENJALNO 10AX 250V~

SE63

- 10AX 250V~, tip SE63
- ustreza EN 60669-1
- brezvijačna pritridlev vodnikov 1.5-2.5mm²

SWITCH DOUBLE 2WAY 10AX 250V~

- 10AX 250V~, type SE63
- in accordance with EN 60669-1
- plug-in contacts 1.5-2.5mm²





STIKALO KRŽNO 10AX 250V~

SE70

- 10AX 250V~, tip SE70
- ustreza EN 60669-1
- brezvijačna pritridlev vodnikov 1.5-2.5mm²

SWITCH INTERMEDIATE 10AX 250V~

- 10AX 250V~, type SE70
- in accordance with EN 60669-1
- plug-in contacts 1.5-2.5mm²






- SE10PW
- SE10IW
- SE10ES
- SE10CO
- SE10NB

STIKALO ENOPOLNO 10AX 250V~


- 10AX 250V~, tip SE10
- ustreza EN 60669-1
- brezvijačna pritridlev vodnikov 1.5-2.5mm²
- SWITCH 1WAY 10AX 250V~**
- 10AX 250V~, type SE10
- in accordance with EN 60669-1
- plug-in contacts 1.5-2.5mm²



- SE10PWIN
- SE10IWIN
- SE10ESIN
- SE10COIN
- SE10NBIN

STIKALO ENOPOLNO 10AX 250V~ _ IN

- IN indikator
- 10AX 250V~, tip SE10
- ustreza EN 60669-1
- brezvijačna pritridlev vodnikov 1.5-2.5mm²
- SWITCH 1WAY 10AX 250V~ _ IN**
- IN indicator
- 10AX 250V~, type SE10
- in accordance with EN 60669-1
- plug-in contacts 1.5-2.5mm²



- SE11PW
- SE11IW
- SE11ES
- SE11CO
- SE11NB

TIPKALO ENOPOLNO 10A 250V~

- 10A 250V~, tip SE11
- ustreza EN 60669-1
- brezvijačna pritridlev vodnikov 1.5-2.5mm²
- PUSH BUTTON 1WAY 10A 250V~**
- 10A 250V~, type SE11
- in accordance with EN 60669-1
- plug-in contacts 1.5-2.5mm²



- SE11PWTI50
- SE11IWTI50
- SE11ESTI50
- SE11COTI50
- SE11NBTI50

TIPKALO ENOPOLNO 10A 250V~ _ TI 50


- TI 50 indikator zvonec+tливка
- 10A 250V~, tip SE11
- ustreza EN 60669-1
- brezvijačna pritridlev vodnikov 1.5-2.5mm²
- PUSH BUTTON 1WAY 10A 250V~ _ TI 50**
- TI 50 indicator bell+neon lamp
- 10A 250V~, type SE11
- in accordance with EN 60669-1
- plug-in contacts 1.5-2.5mm²



- SE11PWTI51
- SE11IWTI51
- SE11ESTI51
- SE11COTI51
- SE11NBTI51

TIPKALO ENOPOLNO 10A 250V~ _ TI 51

- TI 51 indikator luč+tливка
- 10A 250V~, tip SE11
- ustreza EN 60669-1
- brezvijačna pritridlev vodnikov 1.5-2.5mm²
- PUSH BUTTON 1WAY 10A 250V~ _ TI 51**
- TI 51 indicator light+neon lamp
- 10A 250V~, type SE11
- in accordance with EN 60669-1
- plug-in contacts 1.5-2.5mm²



- SE11PWIL
- SE11IWIL
- SE11ESIL
- SE11COIL
- SE11NBIL

TIPKALO ENOPOLNO 10A 250V~ _ IL

- IL napisna ploščica
- 10A 250V~, tip SE11
- ustreza EN 60669-1
- brezvijačna pritridlev vodnikov 1.5-2.5mm²
- PUSH BUTTON 1WAY 10A 250V~ _ IL**
- IL inscription plate
- 10A 250V~, type SE11
- in accordance with EN 60669-1
- plug-in contacts 1.5-2.5mm²




- SE22PWIN03
- SE22IWIN03
- SE22ESIN03
- SE22COIL
- SE22NBIN03

STIKALO DVOPOLNO 16AX 250V~ _ IN 03

- NT 03 neutral 0-1
- 16AX 250V~, tip SE22
- ustreza EN 60669-1
- vijačna pritridlev vodnikov 1.5-2.5mm²
- SWITCH 2POLE 16AX 250V~ _ IN 03**
- NT 03 neutral 0-1
- 16AX 250V~, type SE22
- in accordance with EN 60669-1
- screw contacts 1.5-2.5mm²




S W I T C H E S S E



- SE50PW
- SE50IW
- SE50ES
- SE50CO
- SE50NB

STIKALO SERIJSKO 10AX 250V~

- 10AX 250V~, tip SE50
- ustreza EN 60669-1
- brezvijačna pritridlej vodnikov 1.5-2.5mm²
- SWITCH 2GANG-1WAY 10AX 250V~**
- 10AX 250V~, type SE50
- in accordance with EN 60669-1
- plug-in contacts 1.5-2.5mm²



- SE51PW
- SE51IW
- SE51ES
- SE51CO
- SE51NB

TIPKALO SERIJSKO 10A 250V~

- 10A 250V~, tip SE51
- ustreza EN 60669-1
- brezvijačna pritridlej vodnikov 1.5-2.5mm²
- PUSH BUTTON 2GANG-1WAY 10A 250V~**
- 10A 250V~, type SE51
- in accordance with EN 60669-1
- plug-in contacts 1.5-2.5mm²



- SE52PWNT09
- SE52IWNT09
- SE52ESNT09
- SE52CONT09
- SE52NBNT09

STIKALO ŽALUZIJSKO 10AX 250V~ _ NT 09

- NT 09 nevtral gor-dol
- 10AX 250V~, tip SE52
- ustreza EN 60669-1
- brezvijačna pritridlej vodnikov 1.5-2.5mm²
- z mehansko blokado hkratnega vklopa

**SWITCH SHUTTERS 10AX 250V~ _ NT 09**

- NT 09 neutral up-down
- 10AX 250V~, type SE52
- in accordance with EN 60669-1
- plug-in contacts 1.5-2.5mm²
- with mechanical interlock

TIPKALO ŽALUZIJSKO 10A 250V~ _ NT 09

- NT 09 nevtral gor-dol
- 10A 250V~, tip SE53
- ustreza EN 60669-1
- brezvijačna pritridlej vodnikov 1.5-2.5mm²
- z mehansko blokado hkratnega vklopa

**PUSH BUTTON SHUTTERS 10A 250V~ _ NT 09**

- NT 09 neutral up-down
- 10A 250V~, type SE53
- in accordance with EN 60669-1
- plug-in contacts 1.5-2.5mm²
- with mechanical interlock

STIKALO MENJALNO 10AX 250V~


- 10AX 250V~, tip SE60
- ustreza EN 60669-1
- brezvijačna pritridlej vodnikov 1.5-2.5mm²

**SWITCH 2WAY 10AX 250V~**

- 10AX 250V~, type SE60
- in accordance with EN 60669-1
- plug-in contacts 1.5-2.5mm²



- SE60PW
- SE60IW
- SE60ES
- SE60CO
- SE60NB



- SE63PW
- SE63IW
- SE63ES
- SE63CO
- SE63NB

STIKALO DVOJNO MENJALNO 10AX 250V~

- 10AX 250V~, tip SE63
- ustreza EN 60669-1
- brezvijačna pritridlej vodnikov 1.5-2.5mm²

**SWITCH DOUBLE 2WAY 10AX 250V~**

- 10AX 250V~, type SE63
- in accordance with EN 60669-1
- plug-in contacts 1.5-2.5mm²





- SE70PW
- SE70IW
- SE70ES
- SE70CO
- SE70NB

STIKALO KRIŽNO 10AX 250V~

- 10AX 250V~, tip SE70
- ustreza EN 60669-1
- brezvijačna pritridlej vodnikov 1.5-2.5mm²





**SWITCH INTERMEDIATE 10AX 250V~**



- 10AX 250V~, type SE70
- in accordance with EN 60669-1
- plug-in contacts 1.5-2.5mm²



ekonomik

				
TE11	PW	NT	09	
tip type	naziv description	barva colour	opcijski opis 1 optional data 1	opcijski opis 2 optional data 2
TE10	TIPKA NAVADNA BUTTON 1GANG	<input type="checkbox"/> PW bela-sijaj polar white	NT nevtral neutral	 50
TE11	TIPKA SERIJSKA BUTTON 2GANG	<input type="checkbox"/> IW bež-sijaj ivory white		 51
.	.	<input type="checkbox"/> ES srebrna-mat elox silver	IN indikator indicator	0 03
.	.	<input type="checkbox"/> CO beli duroplast white thermoset		
		<input checked="" type="checkbox"/> NB črna-sijaj night black		 04

	TIPKA NAVADNA - tipka skupaj z nosilcem BUTTON 1GANG - button together with carrier	
	TIPKA INDIKATOR - tipka skupaj z nosilcem BUTTON INDICATOR - button together with carrier	
	TIPKA Z NAPISNO PLOŠČICO - tipka skupaj z nosilcem, z napisno ploščico BUTTON WITH INSCRIPTION PLATE - button together with carrier, with inscription plate	
	TIPKA SERIJSKA - tipka serijska skupaj z nosilcem BUTTON 2GANG - button 2gang together with carrier	














IA20	WH		
tip type	naziv <i>description</i>	tehnični opis <i>technical data</i>	barva <i>colour</i>
IA10	TLIVKA <i>NEON LAMP</i>	230V~ 0,34W	<input type="checkbox"/> WH bela <i>white</i>
IA20	SIJALKA LED <i>LED LAMP</i>	230V~ 0,40W	<input checked="" type="checkbox"/> BL modra <i>blue</i>
IA21	SIJALKA LED <i>LED LAMP</i>	24V AC/DC 0,20W	<input checked="" type="checkbox"/> RD rdeča <i>red</i>
.	.	.	<input checked="" type="checkbox"/> GR zelena <i>green</i>
.	.	.	<input checked="" type="checkbox"/> OR oranžna <i>orange</i>
<hr/>			
TLIVKA 230V~ 0,34W			
	<input checked="" type="checkbox"/> IA10OR		
<ul style="list-style-type: none"> - za indikacijo, osvetlitev ali stalno osvetlitev stikala - v kombinaciji s tipko z indikatorjem <p>NEON LAMP 230V~ 0,34W</p> <ul style="list-style-type: none"> - for indication, illumination or constant illumination of switch - in combination with button with indicator 			
<hr/>			
SIJALKA LED 230V AC/DC 0,40W			
	<input type="checkbox"/> IA20WH <input checked="" type="checkbox"/> IA20GR <input checked="" type="checkbox"/> IA20RD <input checked="" type="checkbox"/> IA20BL		
<ul style="list-style-type: none"> - za indikacijo, osvetlitev ali stalno osvetlitev stikala - v kombinaciji s tipko z indikatorjem <p>LED LAMP 230V AC/DC 0,40W</p> <ul style="list-style-type: none"> - for indication, illumination or constant illumination of switch - in combination with button with indicator 			
<hr/>			
SIJALKA LED 24V AC/DC 0,20W			
	<input type="checkbox"/> IA21WH <input checked="" type="checkbox"/> IA21RD		
<ul style="list-style-type: none"> - za indikacijo, osvetlitev ali stalno osvetlitev stikala - v kombinaciji s tipko z indikatorjem <p>LED LAMP 24V AC/DC 0,20W</p> <ul style="list-style-type: none"> - for indication, illumination or constant illumination of switch - in combination with button with indicator 			
<hr/>			
SIJALKA LED 12V AC/DC 0,10W			
	<input type="checkbox"/> IA22WH <input checked="" type="checkbox"/> IA22RD		
<ul style="list-style-type: none"> - za indikacijo, osvetlitev ali stalno osvetlitev stikala - v kombinaciji s tipko z indikatorjem <p>LED LAMP 12V AC/DC 0,10W</p> <ul style="list-style-type: none"> - for indication, illumination or constant illumination of switch - in combination with button with indicator 			


* Indikacija /
Indication

Osvetitev /
Illumination

* Stalna osvetitev /
Illumination always on



* vezave primerne za varčne (CFL, LED) sijalke /
wiring scheme for compact fluid lamp (CFL, LED)



S O C K E T S V E

VE11	PT	XO	KS	
tip type	naziv description	tehnični opis technical data	opcijski opis 1 optional data 1	opcijski opis 2 optional data 2
VE10	VTIČNICA SCHUKO SOCKET SCHUKO	2P+E 16A 250V~	XO brez okvirja without cover plate	KS otroška zaščita child protection
VE11	VTIČNICA SCHUKO+POKROV SOCKET SCHUKO+COVER	2P+E 16A 250V~		
VE12	VTIČNICA SCHUKO SOCKET SCHUKO	2P+E 16A 250V~ BV	KS otroška zaščita child protection	
.	.	.		
barva colour				
<input type="checkbox"/> PW bela-sijaj polar white	<input checked="" type="checkbox"/> PT bela+prozorna white+transparent	<input type="checkbox"/> PP bela+bela white+white		
<input checked="" type="checkbox"/> IW bež-sijaj ivory white	<input checked="" type="checkbox"/> IT bež+prozorna ivory+transparent	<input checked="" type="checkbox"/> II bež+bež ivory+ivory		
<input type="checkbox"/> ES srebrna-mat elox silver	<input checked="" type="checkbox"/> ST srebrna+prozorna silver+transparent	<input type="checkbox"/> SS srebrna+srebrna silver+silver		
<input type="checkbox"/> CO beli duroplast white thermoset	<input checked="" type="checkbox"/> CT bela+prozorna white+transparent	<input type="checkbox"/> BB črna+črna black+black		
<input checked="" type="checkbox"/> NB črna-sijaj night black	<input checked="" type="checkbox"/> BT črna+prozorna black+transparent	<input checked="" type="checkbox"/> RR rdeča+rdeča red+red		
<input checked="" type="checkbox"/> RD rdeča red	<input checked="" type="checkbox"/> RT rdeča+prozorna red+transparent	<input checked="" type="checkbox"/> GG zelena+zelena green+green		
<input type="checkbox"/> GR zelena green	<input checked="" type="checkbox"/> GT zelena+prozorna green+transparent	<input checked="" type="checkbox"/> OO oranžna+oranžna orange+orange		
<input type="checkbox"/> OR oranžna orange	<input checked="" type="checkbox"/> OT oranžna+prozorna orange+transparent			




schuko - ustreza EN 60884-1, CEE7 (list III)

schuko - in accordance with EN 60884-1, CEE7 (standard sheet III)

• vijačna pritrditev vodnikov
screw contacts• BV brezvijačna pritrditev vodnikov
BV plug-in contacts

francoska - ustreza NF C 61-314 (list V)

French - in accordance with NF C 61-314 (standard sheet V)

• vijačna pritrditev vodnikov
screw contacts• BV brezvijačna pritrditev vodnikov
BV plug-in contacts

VTIČNICA SCHUKO 2P+E 16A 250V~ _ XO



- VE10PWXO
- VE10IWXO
- VE10ESXO
- VE10COXO
- VE10NBXO
- VE10RDXO
- VE10GRXO
- VE10ORXO

- vijačna pritrditev vodnikov 1.5-2.5mm²

- XO brez okvirja

- 2P+E schuko

- 16A 250V~, tip VE10



SOCKET SCHUKO 2P+E 16A 250V~ _ XO

- screw contacts 1.5-2.5mm²

- XO without surround

- 2P+E schuko

- 16A 250V~, type VE10



- VE11PTXO
- VE11ITXO
- VE11STXO
- VE11BTXO

VTIČNICA SCHUKO+POKROV 2P+E 16A 250V~ _ XO

- vijačna pritrditev vodnikov 1.5-2.5mm²

- XO brez okvirja

- 2P+E schuko+pokrov

- 16A 250V~, tip VE11



SOCKET SCHUKO+COVER 2P+E 16A 250V~ _ XO

- screw contacts 1.5-2.5mm²

- XO without surround

- 2P+E schuko+cover

- 16A 250V~, type VE11



- VE12PWXO
- VE12IWXO
- VE12ESXO
- VE12COXO
- VE12NBXO
- VE12RDXO
- VE12GRXO
- VE12ORXO

VTIČNICA SCHUKO 2P+E 16A 250V~ BV _ XO

- BV brezvijačna pritrditev vodnikov 1.5-2.5mm²

- XO brez okvirja

- 2P+E schuko

- 16A 250V~, tip VE12



SOCKET SCHUKO 2P+E 16A 250V~ BV _ XO

- BV plug-in contacts 1.5-2.5mm²

- XO without surround

- 2P+E schuko+cover

- 16A 250V~, type VE12



- VE13PTXO
- VE13ITXO
- VE13STXO
- VE13BTXO

- VE13PPXO

VTIČNICA SCHUKO+POKROV 2P+E 16A 250V~ BV _ XO

- BV brezvijačna pritrditev vodnikov 1.5-2.5mm²

- XO brez okvirja

- 2P+E schuko+pokrov

- 16A 250V~, tip VE13



SOCKET SCHUKO+COVER 2P+E 16A 250V~ BV _ XO

- BV plug-in contacts 1.5-2.5mm²

- XO without surround

- 2P+E schuko+cover

- 16A 250V~, type VE13



- VE10PW
- VE10IW
- VE10ES
- VE10CO
- VE10NB

- vijačna pritrditev vodnikov 1.5-2.5mm²

- 2P+E schuko

- 16A 250V~, tip VE10



SOCKET SCHUKO 2P+E 16A 250V~

- screw contacts 1.5-2.5mm²

- 2P+E schuko

- 16A 250V~, type VE10



- VE11PT
- VE11IT
- VE11ST
- VE11CT
- VE11BT

VTIČNICA SCHUKO+POKROV 2P+E 16A 250V~

- vijačna pritrditev vodnikov 1.5-2.5mm²

- 2P+E schuko+ pokrov

- 16A 250V~, tip VE11



SOCKET SCHUKO+COVER 2P+E 16A 250V~

- screw contacts 1.5-2.5mm²

- 2P+E schuko+cover

- 16A 250V~, type VE11



- VE12PW
- VE12IW
- VE12ES
- VE12CO
- VE12NB

- BV brezvijačna pritrditev vodnikov 1.5-2.5mm²

- 2P+E schuko

- 16A 250V~, tip VE12



SOCKET SCHUKO 2P+E 16A 250V~ BV

- BV plug-in contacts 1.5-2.5mm²

- 2P+E schuko

- 16A 250V~, type VE12



- VE13PT
- VE13IT
- VE13ST
- VE13CT
- VE13BT

VTIČNICA SCHUKO+POKROV 2P+E 16A 250V~ BV

- BV brezvijačna pritrditev vodnikov 1.5-2.5mm²

- 2P+E schuko+pokrov

- 16A 250V~, tip VE13




SOCKET SCHUKO+COVER 2P+E 16A 250V~ BV

- BV plug-in contacts 1.5-2.5mm²

- 2P+E schuko+cover

- 16A 250V~, type VE13


S O C K E T S V E



- VE40PWXO
 VE40IWXO
 VE40ESXO
 VE40COXO
 VE40NBXO
 VE40RDXO
 VE40GRXO
 VE40ORXO

VTIČNICA FRANCOSKA 2P+E 16A 250V~ _ XO


- vijačna pritrditev vodnikov 1.5-2.5mm²
- XO brez okvirja
- 2P+E francoška
- 16A 250V~, tip VE40



- VE41PTXO
 VE41ITXO
 VE41STXO
 VE41PTXO
 VE41BTXO
 VE41PPXO

VTIČNICA FRANCOSKA+POKROV 2P+E 16A 250V~ _ XO


- vijačna pritrditev vodnikov 1.5-2.5mm²
- XO brez okvirja
- 2P+E francoška+pokrov
- 16A 250V~, tip VE41



- VE42PWXO
 VE42IWXO
 VE42ESXO
 VE42COXO
 VE42NBXO
 VE42RDXO
 VE42GRXO
 VE42ORXO

VTIČNICA FRANCOSKA 2P+E 16A 250V~ BV _ XO

- BV brezvijačna pritrditev vodnikov 1.5-2.5mm²
- XO brez okvirja
- 2P+E francoška
- 16A 250V~, tip VE42



- VE43PTXO
 VE43ITXO
 VE43STXO
 VE43PTXO
 VE43BTXO
 VE43PPXO

VTIČNICA FRANCOSKA+POKROV 2P+E 16A 250V~ BV _ XO

- BV brezvijačna pritrditev vodnikov 1.5-2.5mm²
- XO brez okvirja
- 2P+E francoška+pokrov
- 16A 250V~, tip VE43



- VE40PW
 VE40IW
 VE40ES
 VE40CO
 VE40NB

VTIČNICA FRANCOSKA 2P+E 16A 250V~

- vijačna pritrditev vodnikov 1.5-2.5mm²
- 2P+E francoška
- 16A 250V~, tip VE40



- VE41PT
 VE41IT
 VE41ST
 VE41CT
 VE41BT

VTIČNICA FRANCOSKA+POKROV 2P+E 16A 250V~

- vijačna pritrditev vodnikov 1.5-2.5mm²
- 2P+E francoška+pokrov
- 16A 250V~, tip VE41



- VE42PW
 VE42IW
 VE42ES
 VE42CO
 VE42NB

VTIČNICA FRANCOSKA 2P+E 16A 250V~ BV

- BV brezvijačna pritrditev vodnikov 1.5-2.5mm²
- 2P+E francoška
- 16A 250V~, tip VE42



- VE43PT
 VE43IT
 VE43ST
 VE43CT
 VE43BT

VTIČNICA FRANCOSKA+KS+POKROV 2P+E 16A 250V~ BV

- BV brezvijačna pritrditev vodnikov 1.5-2.5mm²
- 2P+E francoška+pokrov
- 16A 250V~, tip VE43



ekonomik



- VE16PWKS
- VE16IWKS
- VE16ESKS
- VE16NBKS

VTIČNICA SCHUKO DVOJNA 2P+E 16A 250V~

- 2P+E schuko dvojna
- 16A 250V~, tip VE16
- ustreza IEC 60884-1, CEE7
- vijačna pritrditev vodnikov 1.5-2.5 mm²
- KS vgrajena otroška zaščita pred dotikom kontaktov

SOCKET SCHUKO DOUBLE 2P+E 16A 250V~

- 2P+E schuko double
- 16A 250V~, type VE16
- in accordance with IEC 60884-1, CEE7
- screw contacts 1.5-2.5 mm²
- KS build-in child protection – shuttered live contacts




- VE46PWKS
- VE46IWKS
- VE46ESKS
- VE46NBKS

VTIČNICA FRANCOSKA DVOJNA 2P+E 16A 250V~

- 2P+E francoska dvojna
- 16A 250V~, tip VE46
- ustreza IEC 60884-1, CEE7; NF C 61-314, CSN 33 2318; PN-E 93201
- vijačna pritrditev vodnikov 1.5-2.5 mm²
- KS vgrajena otroška zaščita pred dotikom kontaktov

SOCKET FRENCH DOUBLE 2P+E 16A 250V~

- 2P+E French double
- 16A 250V~, type VE46
- in accordance with IEC 60884-1, CEE7; NF C 61-314, CSN 33 2318; PN-E 93201
- screw contacts 1.5-2.5 mm²
- KS build-in child protection – shuttered live contacts




- VE30PW
- VE30IW
- VE30ES
- VE30NB

VTIČNICA 2P 16A 250V~

- 2P brez ozemljivvenega kontakta
- 16A 250V~
- ustreza EN 60884-1, CEE7 (list I)
- vijačna pritrditev vodnikov 1.5-2.5mm²

SOCKET 2P 16A 250V~

- 2P without earthing contact
- 16A 250V~
- in accordance with EN 60884-1, CEE7 (standard sheet I)
- screw contacts 1.5-2.5mm²



COMMUNICATIONS KE



tip type	naziv description	tehnični opis technical data	barva colour
KE11	VTIČNICA TV-R KONČNA SOCKET TV-R END-LINE	2dB	<input type="checkbox"/> PW bela-sijaj polar white
KE12	VTIČNICA TV-R PREHODNA SOCKET TV-R THROUGHPASS	8,5dB	<input checked="" type="checkbox"/> IW bež-sijaj ivory white
KE16	VTIČNICA SAT-TV-R KONČNA SOCKET SAT-TV-R END-LINE	3dB	<input type="checkbox"/> ES srebrna-mat elox silver
.	.	.	<input type="checkbox"/> CO beli duroplast white thermoset
.	.	.	<input checked="" type="checkbox"/> NB črna-sijaj night black

VTIČNICA TV-R KONČNA 2dB




KE11

2 dB ← ↗ 7,5 dB

- TV-R končna
- frekvenčni pas 5÷862MHz
- dušenje: R-7.5dB, TV-2dB
- ustreza EN 50083-1
- vijačna priključitev

- SOCKET TV-R END-LINE 2dB**
- TV-R end-line
 - frequency range 5÷862MHz
 - reduction: R-7.5dB, TV-2dB
 - in accordance with EN 50083-1
 - screw contacts




KE12

8,5 dB ← ↗ 12,5 dB
2 dB

- TV-R prehodna vtičnica
- frekvenčni pas 5÷862MHz
- dušenje: R-12.5dB, TV-8.5dB, prehod-2dB
- ustreza EN 50083-1
- vijačna priključitev

- SOCKET TV-R TROUGHPASS 8,5dB**
- TV-R troughpass
 - frequency range 5÷862MHz
 - reduction: R-12.5dB, TV-8.5dB, trough-2dB
 - in accordance with EN 50083-1
 - screw contacts




KE16

3 dB ← ↗ 1 dB
1,5 dB

- SAT-TV-R končna
- frekvenčni pas 5÷2400MHz
- dušenje: R-1dB, TV-1.5dB, SAT-3dB
- vgradnja v dozo Ø60 s krempeljci ali vijaki
- ustreza EN 50083-1
- vijačna pritrditev vodnikov


- SOCKET SAT-TV-R END-LINE 3dB**
- SAT-TV-R end-line
 - frequency range 5÷2400MHz
 - reduction: R-1dB, TV-1.5dB, SAT-3dB
 - for mounting in round box Ø60 with claws or screws
 - in accordance with EN 50083-1
 - screw contacts



KE36

- KS keystone pritrditveni standard
- RJ11 6/4
- ustreza IEC 60603-7

- SOCKET TEL KS RJ11 6/4**
- KS keystone fixing standard
 - RJ11 6/4
 - in accordance with IEC 60603-7






KE37

VTIČNICA CAT5e KS RJ45 8/8

- KS keystone pritrditveni standard
- CAT5e, RJ45 8/8
- ustreza IEC 60603-7

SOCKET CAT5e KS RJ45 8/8
- KS keystone fixing standard
- CAT5e, RJ45 8/8
- in accordance with IEC 60603-7




KE38

VTIČNICA TEL KS DVOJNA 2x RJ11 6/4

- KS keystone pritrditveni standard
- 2x RJ11 6/4
- ustreza IEC 60603-7

SOCKET TEL KS DOUBLE 2x RJ11 6/4
- KS keystone fixing standard
- 2x RJ11 6/4
- in accordance with IEC 60603-7




KE39

VTIČNICA CAT5e KS DVOJNA 2x RJ45 8/8

- KS keystone pritrditveni standard
- 2x CAT5e, RJ45 8/8
- ustreza IEC 60603-7

SOCKET CAT5e KS DOUBLE 2x RJ45 8/8
- KS keystone fixing standard
- 2x CAT5e, RJ45 8/8
- in accordance with IEC 60603-7




KE45

ADAPTER KS ENOJNI

- KS keystone pritrditveni standard - enojni
- AMP, Avaya, Brandrex, FMT, Mfico, Tyco, ...
- komunikacijski modul ni vgrajen

ADAPTER KS SINGLE

- KS keystone fixing standard - single
- AMP, Avaya, Brandrex, FMT, Mfico, Tyco, ...
- communication module not included




KE46

ADAPTER KS DVOJNI

- KS keystone pritrditveni standard - dvojni
- AMP, Tyco, ...
- komunikacijski modul ni vgrajen

ADAPTER KS DOUBLE

- KS keystone fixing standard - double
- AMP, Tyco, ...
- communication module not included




KE47

ADAPTER PD DVOJNI

- PD Panduit MiniCOM pritrditveni standard - dvojni
- komunikacijski modul ni vgrajen

ADAPTER PD DOUBLE

- PD Panduit Mini-COM fixing standard - double
- communication module not included





- KE10PW
- KE10IW
- KE10ES
- KE10CO
- KE10NB

VTIČNICA TV OSNOVNA 0dB

- TV osnovna
- dušenje 0dB
- konektor zadaj – F standard

SOCKET TV BASIC 0dB

- TV basic
- reduction 0dB
- back connector – F standard



- KE11PW
- KE11IW
- KE11ES
- KE11CO
- KE11NB

VTIČNICA TV-R KONČNA 2dB

- TV-R končna
- frekvenčni pas 5÷862 MHz
- dušenje: R-7.5dB, TV-2dB
- ustreza EN 50083-1
- vijačna priključitev

SOCKET TV-R END-LINE 2dB

- TV-R end-line
- frequency range 5÷862 MHz
- reduction: R-7.5dB, TV-2dB
- in accordance with EN 50083-1
- screw contact



- KE12PW
- KE12IW
- KE12ES
- KE12CO
- KE12NB

VTIČNICA TV-R PREHODNA 8,5dB

- TV-R prehodna
- frekvenčni pas 5÷862 MHz
- dušenje: R-12.5dB, TV-8.5dB, prehod-2dB
- ustreza EN 50083-1
- vijačna priključitev

SOCKET TV-R TROUGHPASS 8,5dB

- TV-R troughpass
- frequency range 5÷862 MHz
- reduction: R-12.5dB, TV-8.5dB, trough-2dB
- in accordance with EN 50083-1
- screw contacts



- KE16PW
- KE16IW
- KE16ES
- KE16CO
- KE16NB

VTIČNICA SAT-TV-R KONČNA 3dB

- SAT-TV-R končna
- frekvenčni pas 5÷2400 MHz
- dušenje: R-1dB, TV-1.5dB, SAT-3dB
- ustreza EN 50083-1
- vijačna priključitev

SOCKET SAT-TV-R END-LINE 3dB

- SAT-TV-R end-line
- frequency range 5÷2400 MHz
- reduction: R-1dB, TV-1.5dB, SAT-3dB
- in accordance with EN 50083-1
- screw contacts



- KE22PW
- KE22IW
- KE22ES
- KE22CO
- KE22NB

VTIČNICA AVDIO 2xRCA

- avdio 2xRCA
- pritrdirtev vodnikov s spajkanjem

SOCKET AUDIO 2xRCA

- audio 2xRCA
- soldering connection of cable



- KE23PW
- KE23IW
- KE23ES
- KE23CO
- KE23NB


VTIČNICA AVDIO ZVOČNIŠKA

- avdio 2x Ø4mm
- za priklop zvočniškega vodnika, vtiča Ø4mm ali viličastega kabel čevlja
- pritrdirtev vodnikov zadaj s spajkanjem

SOCKET AUDIO LOUDSPEAKERS

- audio 2x Ø4mm
- to accommodate speaker wire, banana plug Ø4mm or spades
- soldering connection of cable at the back side





- KE36PW
- KE36IW
- KE36ES
- KE36CO
- KE36NB

VTIČNICA TEL KS RJ11 6/4

- KS keystone pritrditveni standard
 - RJ11 6/4
 - ustreza IEC 60603-7
- SOCKET TEL KS RJ11 6/4**
- KS keystone fixing standard
 - RJ11 6/4
 - in accordance with IEC 60603-7



- KE37PW
- KE37IW
- KE37ES
- KE37CO
- KE37NB

VTIČNICA CAT5e KS RJ45 8/8

- KS keystone pritrditveni standard
 - CAT5e, RJ45 8/8
 - ustreza IEC 60603-7
- SOCKET CAT5e KS RJ45 8/8**
- KS keystone fixing standard
 - CAT5e, RJ45 8/8
 - in accordance with IEC 60603-7



- KE38PW
- KE38IW
- KE38ES
- KE38CO
- KE38NB

VTIČNICA TEL KS DVOJNA 2x RJ11 6/4

- KS keystone pritrditveni standard
 - 2x RJ11, 6/4
 - ustreza IEC 60603-7
- SOCKET TEL KS DOUBLE 2x RJ11 6/4**
- KS keystone fixing standard
 - 2x RJ11, 6/4
 - in accordance with IEC 60603-7



- KE39PW
- KE39IW
- KE39ES
- KE39CO
- KE39NB

VTIČNICA CAT5e KS DVOJNA 2x RJ45 8/8


- KS keystone pritrditveni standard
 - 2x CAT5e, RJ45 8/8
 - ustreza IEC 60603-7
- SOCKET CAT5e KS DOUBLE 2x RJ45 8/8**
- KS keystone fixing standard
 - 2x CAT5e, RJ45 8/8
 - in accordance with IEC 60603-7




- KE35PW
- KE35IW
- KE35ES
- KE35CO
- KE35NB

VTIČNICA TEL LT RJ11 6/4

- TEL LT vijak
 - vijačna pritrditev vodnikov
 - RJ11 6/4
 - ustreza IEC 60603-7
- SOCKET TEL LT RJ11 6/4**
- TEL LT screw
 - screw contacts
 - RJ11 6/4
 - in accordance with IEC 60603-7





tip type	naziv description	tehnični opis technical data	barva colour
PE10	POKROV TV-R COVER TV-R	2P/3P	<input type="checkbox"/> PW bela-sijaj <i>polar white</i>
PE20	POKROV KS ENOJNI COVER KS SINGLE		<input type="checkbox"/> IW bež-sijaj <i>ivory white</i>
PE21	POKROV KS DVOJNJI COVER KS DOUBLE		<input type="checkbox"/> ES srebrna-mat <i>elox silver</i>
.	.		<input type="checkbox"/> CO beli duroplast <i>white thermoset</i>
.	.		<input checked="" type="checkbox"/> NB črna-sijaj <i>night black</i>

POKROV TV-R 2P/3P




- PE10PW
- PE10IW
- PE10ES
- PE10CO
- PE10NB

- TV-R pokrov, 2P ali 3P z vijakom
COVER TV-R 2P/3P
- TV-R cover, 2P or 3P with screw



POKROV KS ENOJNI




- PE20PW
- PE20IW
- PE20ES
- PE20CO
- PE20NB

- KS pokrov enojni
COVER KS SINGLE
- KS cover single



POKROV KS DVOJNJI




- PE21PW
- PE21IW
- PE21ES
- PE21NB

- KS pokrov dvojni
COVER KS DOUBLE
- KS cover double



POKROV TAE/TDO



- PE30PW
- PE30IW
- PE30ES
- PE30NB

- TAE ali TDO pokrov z vijakom
COVER TAE/TDO
- TAE or TDO cover with screw









POKROV IR STIKALO



- PE32PW
- PE32IW
- PE32ES
- PE32NB

- pokrov IR stikalo
COVER IR SWITCH
- cover IR switch





tip type	naziv description	tehnični opis technical data	barva colour
EE15	ZATEMNILNIK ROTACIJSKI MEN DIMMER ROTATIVE 2WAY	RL 400W	<input type="checkbox"/> PW bela-sijaj polar white
EE16	ZATEMNILNIK ROTACIJSKI MEN DIMMER ROTATIVE 2WAY	RLC 400W	<input checked="" type="checkbox"/> IW bež-sijaj ivory white
EE19	ZATEMNILNIK ROTACIJSKI MEN DIMMER ROTATIVE 2WAY	LED 100W	<input type="checkbox"/> ES srebrna-mat elox silver
.	.	.	<input type="checkbox"/> CO beli duroplast white thermoset
.	.	.	<input type="checkbox"/> NB črna-sijaj night black

ZATEMNILNIK ROTACIJSKI MEN RL 400W



EE15

- rotacijski z menjalnim stikalom
- breme RL, 40W - 400W
- možna vezava z menjalnim stikalom
- vezava večih zatemnilnikov ni dovoljena
- ustreza EN 60669-1 in EN 60669-2-1
- brezvijačna pritridlev vodnikov 1.5mm²
- napajanje 230V~ 50Hz
- premer nastavka gumba Ø6mm
- zamenljiva varovalka vključena

DIMMER ROTATIVE 2WAY RL 400W

- rotation control with 2-way switch
- load RL, 40W - 400W
- 2-way switch combination is possible
- more dimmers combination is not allowed
- in accordance with EN 60669-1 and EN 60669-2-1
- plug-in contacts 1.5mm²
- supply 230V~ 50Hz
- button inner diameter Ø6mm
- replaceable fuse included

ZATEMNILNIK ROTACIJSKI MEN RLC 400W



EE16

- rotacijski z menjalnim stikalom
- breme RLC, 20W - 400W
- možna vezava z menjalnim stikalom
- vezava večih zatemnilnikov ni dovoljena
- ustreza EN 60669-1 in EN 60669-2-1
- brezvijačna pritridlev vodnikov 1.5mm²
- napajanje 230V~ 50Hz
- premer nastavka gumba Ø6mm
- elektronska varovalka

DIMMER ROTATIVE 2WAY RLC 400W

- rotation control with 2-way switch
- load RLC, 20W - 400W
- 2-way switch combination is possible
- more dimmers combination is not allowed
- in accordance with EN 60669-1 and EN 60669-2-1
- plug-in contacts 1.5mm²
- button inner diameter Ø6mm
- supply 230V~ 50Hz
- electronic fuse



EE19

ZATEMNILNIK ROTACIJSKI MEN LED 100W

- rotacijski z menjalnim stikalom
- breme: LED, 0-100W (max. 10 LED sijalk) GLS, 10-250W
- možna vezava z menjalnim stikalom
- vezava večih zatemnilnikov ni dovoljena
- ustreza EN 60669-1 in EN 60669-2-1
- brezvijačna pritridlev vodnikov 1,5 mm²
- napajanje 230V~ 50 Hz
- zamenljiva varovalka vključena
- premer nastavka gumba Ø6mm

DIMMER ROTATIVE 2WAY LED 100W

- rotation control with 2-way switch
- load: LED, 0-100W (max. 10 LEDs) GLS, 10-250W
- 2-way switch combination is possible
- more dimmers combination is not allowed
- in accordance with EN 60669-1 and EN 60669-2-1
- plug-in contacts 1.5mm²
- supply 230V~ 50Hz
- replaceable fuse included
- button inner diameter Ø6mm

IR STIKALO 5A 250V~

- EE32A1
 EE32A2

- IR infrardeče stikalo
- napajanje: 230V~ ±10 % 50Hz
- rele: 5A / 250V~ izhod za omejen tok z visokim uporom za zero crossing
- stopnja varnosti: IP40
- presek žic pri stičniku: 0,75 - 2,5 mm²
- kot zaznavanja: do 110° pri 20°C
- območje zaznavanja: približno 8 m pri 20°C
- nastavljivost časovnega trajanja: od približno 5 s do 12 min
- nastavljivost osvetlitve: od približno 5 do 200 LUX
- temperatura delovanja: od 0°C do +40°C
- ni primeren za vgradnjo v doze, globine 45 mm
- samo za notranjo uporabo

IR SWITCH 5A 250V~

- IR infrared switch
- supply voltage: 230V~ ±10 % 50Hz
- relay: 5A / 250V~ output for limited current with high resistance for zero crossing
- protection rating: IP40
- cross-section of wires at the contact terminal: 0.75 - 2.5 mm²
- detection angle: up to 110° at 20°C
- detection area: approx. 8 m at 20°C
- adjustability of duration: from approx. 5 s to 12 min
- adjustability of brightness: from approx. 5 to 200 LUX
- operating temperature: from 0°C to +40°C
- not suitable for installation in 45 mm deep boxes
- only for indoor usage

ZATEMNILNIK ROTACIJSKI MEN RL 400W

- EE15PW
 EE15IW
 EE15ES
 EE15CO
 EE15NB

- rotacijski z menjalnim stikaloma
- breme RL, 40W - 400W
- možna vezava z menjalnim stikaloma
- vezava večih zatemnilnikov ni dovoljena
- ustreza EN 60669-1 in EN 60669-2-1
- brezvijačna pritridlev vodnikov 1.5mm²
- napajanje 230V~ 50Hz
- zamenljiva varovalka vključena

DIMMER ROTATIVE 2WAY RL 400W

- rotation control with 2-way switch
- load RL, 40W - 400W
- 2-way switch combination is possible
- more dimmers combination is not allowed
- in accordance with EN 60669-1 and EN 60669-2-1
- plug-in contacts 1.5mm²
- supply 230V~ 50Hz
- replaceable fuse included



ekonomik



- EE16PW
- EE16IW
- EE16ES
- EE16CO
- EE16NB


ZATEMNILNIK ROTACIJSKI MEN RLC 400W

- rotacijski z menjalnim stikalom
- breme RLC, 20W - 400W
- možna vezava z menjalnim stikalom
- vezava večih zatemnilnikov ni dovoljena
- ustreza EN 60669-1 in EN 60669-2-1
- brezvijačna pritridlev vodnikov 1.5mm²
- napajanje 230V~ 50Hz
- elektronska varovalka



DIMMER ROTATIVE 2WAY RLC 400W

- rotation control with 2-way switch
- load RLC, 20W - 400W
- 2-way switch combination is possible
- more dimmers combination is not allowed
- in accordance with EN 60669-1 and EN 60669-2-1
- plug-in contacts 1.5mm²
- supply 230V~ 50Hz
- electronic fuse



- EE19PW
- EE19IW
- EE19ES
- EE19CO
- EE19NB


ZATEMNILNIK ROTACIJSKI MEN LED 100W

- rotacijski z menjalnim stikalom
- breme: LED, 0-100W (max. 10 LED sijalk) GLS, 10-250W
- možna vezava z menjalnim stikalom
- vezava več zatemnilnikov ni dovoljena
- ustreza EN 60669-1 in EN 60669-2-1
- brezvijačna pritridlev vodnikov 1,5 mm²
- napajanje 230V~ 50 Hz
- zamenljiva varovalka vključena



DIMMER ROTATIVE 2WAY LED 100W

- rotation control with 2-way switch
- load: LED, 0-100W (max. 10 LEDs) GLS, 10-250W
- 2-way switch combination is possible
- more dimmers combination is not allowed
- in accordance with EN 60669-1 and EN 60669-2-1
- plug-in contacts 1.5mm²
- supply 230V~ 50Hz
- replaceable fuse included



- EE32PW
- EE32IW
- EE32ES
- EE32CO
- EE32NB

IR STIKALO 5A 230V~


- IR infrardeče stikalo
- napajanje: 230V~ ±10 % 50Hz
- rele: 5A / 250V~ izhod za omejen tok z visokim uporom za zero crossing
- stopnja varnosti: IP40
- presek žic pri stičniku: 0,75 - 2,5 mm²
- kot zaznavanja: do 110° pri 20°C
- območje zaznavanja: približno 8 m pri 20°C
- nastavljivost časovnega trajanja: od približno 5 s do 12 min
- nastavljivost osvetlitve: od približno 5 do 200 LUX
- temperatura delovanja: od 0°C do +40°C
- ni primeren za vgradnjo v doze, globine 45 mm
- samo za notranjo uporabo




IR SWITCH 5A 230V~

- IR infrared switch
- supply voltage: 230V~ ±10 % 50Hz
- relay: 5A / 250V~ output for limited current with high resistance for zero crossing
- protection rating: IP40
- cross-section of wires at the contact terminal: 0.75 - 2.5 mm²
- detection angle: up to 110° at 20°C
- detection area: approx. 8 m at 20°C
- adjustability of duration: from approx. 5 s to 12 min
- adjustability of brightness: from approx. 5 to 200 LUX
- operating temperature: from 0°C to +40°C
- not suitable for installation in 45 mm deep boxes
- only for indoor usage


EE15, EE16, EE19




EE15, EE16, EE19




EE15, EE16, EE19




EE15, EE16, EE19




EE16, EE19



EE16, EE19




EE15 (40÷400W)



1 - žarnica z žarilno nitko /
incandescent lamp

2 - halogenska žarnica /
halogen lamp


EE16 (20÷400W)






3 - klasični transformator /
classical transformer

4 - elektronski transformator /
electronic transformer

EE19 (GLS 10÷250W ; LED 0÷100W)




5 - zatemnilna LED sijalka /
dimmable LED lamp




	
PE41	PW
tip type	naziv description
PE41	POKROV ZATEMNILNO STIKALO <i>COVER DIMMER</i>
	barva colour
	<input type="checkbox"/> PW bela-sijaj <i>polar white</i>
	<input type="checkbox"/> IW bež-sijaj <i>ivory white</i>
	<input type="checkbox"/> ES srebrna-mat <i>elox silver</i>
	<input type="checkbox"/> CO beli duroplast <i>white thermoset</i>
	<input checked="" type="checkbox"/> NB črna-sijaj <i>night black</i>


POKROV ZATEMNILNO STIKALO Ø6



- PE41PW
- PE41IW
- PE41ES
- PE41CO
- PE41NB

- pokrov zatemnilno stikalo Ø6mm
 - za EE15, EE16, EE19
- COVER DIMMER Ø6**
- cover dimmer Ø6mm
 - for EE15, EE16, EE19





tip type	naziv description	barva colour
AE10	POLNILO BLANK	<input type="checkbox"/> PW bela-sijaj polar white
AE20	PRIKLJUČEK PETPOLNI STALNI 3P+N+E 5X4mm ² CONNECTION BOX 3P+N+E 5X4mm ²	<input type="checkbox"/> IW bež-sijaj ivory white
AE30	OHIŠJE NO 1 SURFACE MOUNT BOX	<input type="checkbox"/> ES srebrna-mat elox silver
.	.	<input type="checkbox"/> CO beli duroplast white thermoset
.	.	<input checked="" type="checkbox"/> NB črna-sijaj night black

POLNILO



- AE10PW
- AE10IW
- AE10ES
- AE10CO
- AE10NB

- za pokrivanje praznih odprtin

BLANK

- for filling up empty spaces



PRIKLJUČEK PETPOLNI STALNI 3P+N+E 5x4mm²



- AE20PW
- AE20IW

- 3P+N+E stalni priključek

- 16A 400V~

- ustreza VDE 0601-1:2000


- vijačna pritrditev vodnikov 1.5-4mm²

CONNECTION BOX 5POLE 3P+N+E 5x4mm²

- 3P+N+E connection box
- 16A 400V~
- in accordance with VDE 0606-1:2000
- screw contacts 1.5-4mm²



OHIŠJE NO 1







- AE30PW
- AE30IW

- nadomestno ohišje

SURFACE MOUNT BOX 1

- surface mounting box






AE50PW
 AE50TS

STENSKI ŠČITNIK

- ščitnik stene okoli stikala ali vtičnice

WALL PROTECTION

- protects surface around socket or switch




AE51PW
 AE51IW


OTROŠKA ZAŠČITA KS

- KS otroška zaščita pred dotikom kontaktov

CHILD PROTECTION KS

- KS additional child protection insert - shuttered live contacts






OE10

PW


tip type	naziv description	barva colour
OE10	OKVIR EKONOMIK 1 <i>SURROUND EKONOMIK 1</i>	<input type="checkbox"/> PW bela-sijaj <i>polar white</i>
OE20	OKVIR EKONOMIK 2 HORIZONTALNI <i>SURROUND EKONOMIK 2 HORIZONTAL</i>	<input type="checkbox"/> IW bež-sijaj <i>ivory white</i>
OE30	OKVIR EKONOMIK 3 HORIZONTALNI <i>SURROUND EKONOMIK 3 HORIZONTAL</i>	<input type="checkbox"/> ES srebrna-mat <i>elox silver</i>
.	.	<input type="checkbox"/> CO beli duroplast <i>white thermoset</i>
.	.	<input checked="" type="checkbox"/> NB črna-sijaj <i>night black</i>

**OKVIR EKONOMIK 1**


- OE10PW
 - OE10IW
 - OE10ES
 - OE10CO
 - OE10NB
- SURROUND EKONOMIK 1**
*- dekorativni enojni okvir
- ustreza EN 60669-1*

**OKVIR EKONOMIK 2 HORIZONTALNI**


- OE20PW
 - OE20IW
 - OE20ES
 - OE20CO
 - OE20NB
- SURROUND EKONOMIK 2 HORIZONTAL**
*- dekorativni dvojni horizontalni okvir
- ustreza EN 60669-1*

**OKVIR EKONOMIK 2 VERTIKALNI**

- OE21PW
 - OE21IW
 - OE21ES
 - OE21CO
 - OE21NB
- SURROUND EKONOMIK 2 VERTICAL**
*- dekorativni dvojni vertikalni okvir
- ustreza EN 60669-1*

**OKVIR EKONOMIK 3 HORIZONTALNI**

- OE30PW
 - OE30IW
 - OE30ES
 - OE30CO
 - OE30NB
- SURROUND EKONOMIK 3 HORIZONTAL**
*- dekorativni trojni horizontalni okvir
- ustreza EN 60669-1*






- OE31PW
- OE31IW
- OE31ES
- OE31CO
- OE31NB

OKVIR EKONOMIK 3 VERTIKALNI

- dekorativni trojni vertikalni okvir
- ustreza EN 60669-1

SURROUND EKONOMIK 3 VERTICAL

- decorative surround 3-gang vertical
- in accordance with EN 60669-1




- OE40PW
- OE40IW
- OE40ES
- OE40NB

OKVIR EKONOMIK 4 HORIZONTALNI

- dekorativni četvorni horizontalni okvir
- ustreza EN 60669-1

SURROUND EKONOMIK 4 HORIZONTAL

- decorative surround 4-gang horizontal
- in accordance with EN 60669-1




- OE41PW
- OE41IW
- OE41ES
- OE41NB

OKVIR EKONOMIK 4 VERTIKALNI

- dekorativni četvorni vertikalni okvir
- ustreza EN 60669-1

SURROUND EKONOMIK 4 VERTICAL

- decorative surround 4-gang vertical
- in accordance with EN 60669-1



DEKORATIVNI OKVIRČKI COLOR / COLOR DECORATIVE FRAMES



OE90GR	ZELENA / GREEN	OE90YL	RUMENA / YELLOW	OE90MB	MET. MODRA / MET. BLUE
OE90BL	MODRA / BLUE	OE90WH	BELA / WHITE	OE90BZ	BRON / BRONZE
OE90VO	VIJOLA / VIOLET	OE90GY	SIVA / GREY	OE90CR	SREBRNA / SILVER
OE90PI	ROZA / PINK	OE90BK	ČRNA / BLACK	OE90GO	ZLATA / GOLD
OE90RD	RDEČA / RED				



TEM



KATALOG / CATALOGUE

fontana

STIKALA SF
SWITCHES SF

208

VTIČNICE VF
SOCKETS VF

210

SETI CF
SETS CF

211

PŘIBOR AF
ACCESSORIES AF

213

tip type	naziv description	tehnični opis technical data	barva colour	opcijski opis 1 optional data 1
SF10	STIKALO ENOPOLNO SWITCH 1WAY	IP44 10AX 250V~	<input type="checkbox"/> PW bela-mat white-mat	TI tlivka+indikator neon lamp+indication
SF11	TIPKALO ENOPOLNO PUSH BUTTON 1WAY	IP44 10A 250V~	<input checked="" type="checkbox"/> GY siva-mat grey-mat	
SF20	STIKALO DVOPOLNO SWITCH 2POLE	IP44 10AX 250V~		
.	.	.		
.	.	.		



SF10PW
 SF10GY

STIKALO ENOPOLNO IP44 10AX 250V~

- 10AX 250V~, tip SF10
- ustreza EN 60669-1
- brezvijačna pritrditev vodnikov 1.5-2.5mm²
- SWITCH 1WAY IP44 10AX 250V~**
- 10AX 250V~, type SF10
- in accordance with EN 60669-1
- plug-in contacts 1.5-2.5mm²



SF11PWTI
 SF11GYTI

STIKALO ENOPOLNO IP44 10AX 250V~ _ TI

- TI indikator+tlivka
- 10AX 250V~, tip SF10
- ustreza EN 60669-1
- brezvijačna pritrditev vodnikov 1.5-2.5mm²
- SWITCH 1WAY IP44 10AX 250V~ _ TI**
- TI indicator+neon lamp
- 10AX 250V~, type SF10
- in accordance with EN 60669-1
- plug-in contacts 1.5-2.5mm²



SF20PWTI
 SF20GYTI

TIPKALO ENOPOLNO IP44 10A 250V~ _ TI

- TI indikator+tlivka
- 10A 250V~, tip SF11
- ustreza EN 60669-1
- brezvijačna pritrditev vodnikov 1.5-2.5mm²
- PUSH BUTTON 1WAY IP44 10A 250V~ _ TI**
- TI indicator+neon lamp
- 10A 250V~, type SF11
- in accordance with EN 60669-1
- plug-in contacts 1.5-2.5mm²



SF10PWTI
 SF10GYTI

STIKALO DVOPOLNO IP44 10AX 250V~

- 10AX 250V~, tip SF20
- ustreza EN 60669-1
- brezvijačna pritrditev vodnikov 1.5-2.5mm²
- SWITCH 2POLE IP44 10AX 250V~**
- 10AX 250V~, type SF20
- in accordance with EN 60669-1
- plug-in contacts 1.5-2.5mm²



S W I T C H E S S F



SF50PW
 SF50GY

STIKALO SERIJSKO IP44 10AX 250V~

- 10AX 250V~, tip SF50
 - ustreza EN 60669-1
 - brezvijačna pritrditev vodnikov 1.5-2.5mm²
- SWITCH 2GANG-1WAY IP44 10AX 250V~**
- 10AX 250V~, type SF50
 - in accordance with EN 60669-1
 - plug-in contacts 1.5-2.5mm²



SF51PW
 SF51GY

TIPKALO SERIJSKO IP44 10A 250V~

- 10A 250V~, tip SF51
 - ustreza EN 60669-1
 - brezvijačna pritrditev vodnikov 1.5-2.5mm²
- PUSH BUTTON 2GANG-1WAY IP44 10A 250V~**
- 10A 250V~, type SF51
 - in accordance with EN 60669-1
 - plug-in contacts 1.5-2.5mm²



SF60PW
 SF60GY

STIKALO MENJALNO IP44 10AX 250V~

- 10AX 250V~, tip SF60
 - ustreza EN 60669-1
 - brezvijačna pritrditev vodnikov 1.5-2.5mm²
- SWITCH 2WAY IP44 10AX 250V~**
- 10AX 250V~, type SF60
 - in accordance with EN 60669-1
 - plug-in contacts 1.5-2.5mm²



SF60PWTI
 SF60GYTI

STIKALO MENJALNO IP44 10AX 250V~ _ TI

- TI indikator+tlivka
 - 10AX 250V~, tip SF60
 - ustreza EN 60669-1
 - brezvijačna pritrditev vodnikov 1.5-2.5mm²
- SWITCH 2WAY IP44 10AX 250V~ _ TI**
- TI indicator+neon lamp
 - 10AX 250V~, type SF60
 - in accordance with EN 60669-1
 - plug-in contacts 1.5-2.5mm²



SF63PW
 SF63GY

STIKALO DVOJNO MENJALNO IP44 10AX 250V~


- 10AX 250V~, tip SF63
 - ustreza EN 60669-1
 - brezvijačna pritrditev vodnikov 1.5-2.5mm²
- SWITCH 2WAY DOUBLE IP44 10AX 250V~**
- 10AX 250V~, type SF63
 - in accordance with EN 60669-1
 - plug-in contacts 1.5-2.5mm²



SF70PW
 SF70GY

STIKALO KRIŽNO IP44 10AX 250V~


- 10AX 250V~, tip SF70
 - ustreza EN 60669-1
 - brezvijačna pritrditev vodnikov 1.5-2.5mm²
- SWITCH INTERMEDIATE IP44 10AX 250V~**
- 10AX 250V~, type SF70
 - in accordance with EN 60669-1
 - plug-in contacts 1.5-2.5mm²




V T I Č N I C E V F
S O C K E T S

	
VF10	PW
tip type	naziv description
VF10	VTIČNICA SCHUKO+POKROV SOCKET SCHUKO+COVER
	tehniční opis technical data
	IP44 2P+E 16A 250V~
	barva colour
	<input type="checkbox"/> PW bela-mat white-mat
	<input checked="" type="checkbox"/> GY siva-mat grey-mat

	VTIČNICA SCHUKO+POKROV IP44 2P+E 16A 250V~ <input type="checkbox"/> VF10PW <input checked="" type="checkbox"/> VF10GY <ul style="list-style-type: none"> - vijačna prírďitev vodnikov 1.5-2.5mm² - 2P+E schuko+ покров - 16A 250V~, tip VF10 - ustreza EN 60884-1, CEE7 SOCKET SCHUKO+COVER IP44 2P+E 16A 250V~ <ul style="list-style-type: none"> - screw contacts 1.5-2.5mm² - 2P+E schuko+cover - 16A 250V~, type VF10 - in accordance with EN 60884-1, CEE7 	
	VTIČNICA SCHUKO+POKROV IP44 2P+E 16A 250V~ BV <input type="checkbox"/> VF12PW <input checked="" type="checkbox"/> VF12GY <ul style="list-style-type: none"> - BV brezvijačna prírďitev vodnikov 1.5-2.5mm² - 2P+E schuko+ покров - 16A 250V~, tip VF12 - ustreza EN 60884-1, CEE7 SOCKET SCHUKO+COVER IP44 2P+E 16A 250V~ BV <ul style="list-style-type: none"> - BV plug-in contacts 1.5-2.5mm² - 2P+E schuko+cover - 16A 250V~, type VF12 - in accordance with EN 60884-1, CEE7 	





tip type	naziv description	tehnični opis technical data	barva colour
CF10	SET VTIČNICA SCHUKO DVOJNA HORIZ SOCKET SET SCHUKO DOUBLE HORIZ	2x 2P+E 16A 250V~ IP44	<input type="checkbox"/> PW bela-mat white-mat
CF11	SET VTIČNICA SCHUKO DVOJNA VERT SOCKET SET SCHUKO DOUBLE VERT	2x 2P+E 16A 250V~ IP44	<input checked="" type="checkbox"/> GY siva-mat grey-mat
CF12	SET VTIČNICA SCH + STIKALO MEN HORIZ SOCKET SCH+SWITCH 2WAY HORIZ	16A + 10A 250V~ IP44	.
.	.	.	.

SET VTIČNICA SCHUKO DVOJNI HORIZONTALNI IP44 2x 2P+E 16A 250V~



CF10PW
 CF10GY

SOCKET SET SCHUKO DOUBLE HORIZONTAL IP44 2x 2P+E 16A 250V~
 - vijačna pritrditev vodnikov 1.5-2.5mm²
 - 2x 2P+E schuko+pokrov horizontalni
 - 16A 250V~, tip CF10
 - ustreza EN 60884-1, CEE7



SET VTIČNICA SCHUKO DVOJNI VERTIKALNI IP44 2x 2P+E 16A 250V~



CF11PW
 CF11GY

SOCKET SET SCHUKO DOUBLE VERTICAL IP44 2x 2P+E 16A 250V~
 - vijačna pritrditev vodnikov 1.5-2.5mm²
 - 2x 2P+E schuko+cover vertical
 - 16A 250V~, type CF11
 - in accordance with EN 60884-1, CEE7



SET VTIČNICA SCH + STIKALO MEN HORIZONTALNI IP44 16A + 10AX 250V~



CF12PW
 CF12GY

SOCKET SCH+SWITCH SET 2WAY HORIZONTAL IP44 16A + 10AX 250V~
 - vijačna (vtičnica), brezvijačna (stikalo) pritrditev vodnikov 1.5-2.5mm²
 - 2P+E schuko+cover + stikalo menjalno horizontalni
 - 16A + 10AX 250V~, tip CF12
 - ustreza EN 60884-1, CEE7, EN 60669-1





CF13PW
 CF13GY

SET VTIČNICA SCH + STIKALO MEN VERTIKALNI IP44 16A + 10AX 250V~

- vijačna (vtičnica), brezvijačna (stikalo) pritridlev vodnikov 1.5-2.5mm²
- 2P+E schuko+pokrov + stikalo menjalno vertikalni
- 16A + 10AX 250V~, tip CF13
- ustreza EN 60884-1, CEE7, EN 60669-1

SOCKET SCH+SWITCH 2WAY SET VERTICAL IP44 16A + 10AX 250V~

- screw (socket), plug-in (switch)
- contacts 1.5-2.5mm²*
- 2P+E schuko+cover + switch 2-way vertical
- 16A + 10AX 250V~, type CF13
- in accordance with EN 60884-1, CEE7, EN 60669-1



CF14PW
 CF14GY

SET VTIČNICA SCHUKO DVOJNI HORIZONTALNI IP44 2x 2P+E 16A 250V~BV

- BV brezvijačna pritridlev vodnikov 1.5-2.5mm²
- 2x 2P+E schuko+pokrov horizontalna
- 16A 250V~, tip CF14
- ustreza EN 60884-1, CEE7

SOCKET SET SCHUKO DOUBLE HORIZONTAL IP44 2x 2P+E 16A 250V~ BV

- BV plug-in contacts 1.5-2.5mm²
- 2x 2P+E schuko+cover horizontal
- 16A 250V~, type CF14
- in accordance with EN 60884-1, CEE7



CF15PW
 CF15GY

SET VTIČNICA SCHUKO DVOJNI VERTIKALNI IP44 2x 2P+E 16A 250V~ BV

- BV brezvijačna pritridlev vodnikov 1.5-2.5mm²
- 2x 2P+E schuko+pokrov vertikalna
- 16A 250V~, tip CF15
- ustreza EN 60884-1, CEE7

SOCKET SET SCHUKO DOUBLE VERTICAL IP44 2x 2P+E 16A 250V~ BV

- BV plug-in contacts 1.5-2.5mm²
- 2x 2P+E schuko+cover vertical
- 16A 250V~, type CF15
- in accordance with EN 60884-1, CEE7



CF16PW
 CF16GY

SET VTIČNICA SCH + STIKALO MEN HORIZONTALNI IP44 16A + 10AX 250V~ BV

- BV brezvijačna pritridlev vodnikov 1.5-2.5mm²
- 2P+E schuko+pokrov + stikalo menjalno horizontalni
- 16A + 10AX 250V~, tip CF16
- ustreza EN 60884-1, CEE7, EN 60669-1

SOCKET+SWITCH SET SCH+2WAY HORIZONTAL IP44 16A + 10AX 250V~ BV

- BV plug-in contacts 1.5-2.5mm²
- 2P+E schuko+cover + switch 2-way horizontal
- 16A + 10AX 250V~, type CF16
- in accordance with EN 60884-1, CEE7, EN 60669-1



CF17PW
 CF17GY

SET VTIČNICA SCH+STIKALO MEN VERTIKALNI IP44 16A + 10AX 250V~ BV

- BV brezvijačna pritridlev vodnikov 1.5-2.5mm²
- 2P+E schuko+pokrov + stikalo menjalno vertikalni
- 16A + 10AX 250V~, tip CF17
- ustreza EN 60884-1, CEE7, EN 60669-1

SOCKET SCH+SWITCH 2WAY SET VERTICAL IP44 16A + 10AX 250V~ BV

- BV plug-in contacts 1.5-2.5mm²
- 2P+E schuko+cover + switch 2-way vertical
- 16A + 10AX 250V~, type CF17
- in accordance with EN 60884-1, CEE7, EN 60669-1



P R I B O R A F
A C C E S S O R I E S



tip type	naziv description	tehnični opis technical data	barva colour
AF10	RAZVODNICA DISTRIBUTION BOX	IP44 RN01	<input type="checkbox"/> PW bela-mat white-mat
AF20	RAZVODNICA DISTRIBUTION BOX	IP55 NDO1	<input checked="" type="checkbox"/> GY siva-mat grey-mat


RAZVODNICA IP44 RN01



AF10PW
 AF10GY

- nadomestna razvodnica IP44
- 16A 400V~
- ustreza EN 60309-1

DISTRIBUTION BOX IP44 RN01
 - surface mounting distribution box IP44
 - 16A 400V~
 - In accordance with EN 60309-1





RAZVODNICA IP55 ND01




AF20PW
 AF20GY

- nadomestna razvodnica IP55
- uvodnice priložene
- ustreza EN 60309-1


DISTRIBUTION BOX IP55 ND01
 - surface mounting connection box IP55
 - glands included
 - in accordance with EN 60309-1




CF10
CF14



CF11
CF15



CF12
CF16



CF13
CF17

M O D U L

šifra	opis izdelka	stran	šifra	opis izdelka	stran		
STIKALA SM							
SM10	STIKALO ENOPOLNO 16AX 250V~ 1M	64	KA10	KONEKTOR KS CAT3 RJ11 6/4	84		
SM11	TIPKALO ENOPOLNO 16A 250V~ 1M	64	KA11	KONEKTOR KS CAT5e RJ45 8/8	84		
SM12	STIKALO ENOPOLNO 20AX 250V~ 1M	64	KA12	KONEKTOR KS CAT5eS RJ45 8/8	84		
SM20	STIKALO DVOPOLNO 16AX 250V~ 1M	64	KA15	KONEKTOR KS CAT6 SCHRACK RJ45 8/8	84		
SM40	STIKALO ŽALUZIJSKO 1-0-2 16AX 250V~ 1M	65	KA16	KONEKTOR KS CAT6S SCHRACK RJ45 8/8	84		
SM41	TIPKALO ŽALUZIJSKO 1-0-2 16A 250V~ 1M	65	KA17	KONEKTOR KS CAT6a SCHRACK RJ45 8/8	84		
SM60	STIKALO MENJALNO 16AX 250V~ 1M	65	KA18	KONEKTOR SLIM KS CAT6S SCHRACK RJ45 8/8	85		
SM61	TIPKALO MENJALNO 16A 250V~ 1M	65	KA27	KONEKTOR KS HDMI	85		
SM70	STIKALO KRIŽNO 16AX 250V~ 1M	65	KOMUNIKACIJSKI PRIBOR KA				
SM10--	STIKALO ENOPOLNO 16AX 250V~ 1M	66	EM10--	ZATEMNILNIK ROTACIJSKI RL 300W 1M	86		
SM10--IN	STIKALO ENOPOLNO 16AX 250V~ 1M IN	66	EM21	ZATEMNILNIK VGRADNI RLC 300W	88		
SM11--	TIPKALO ENOPOLNO 16A 250V~ 1M	66	EM22	ZATEMNILNIK VGRADNI R 500W	88		
SM11--IN01	TIPKALO ENOPOLNO 16A 250V~ 1M IN 01	66	EM25--	STIKALO ZATEMNILNIK UNIVEZALNI RLC 0-300W 2M	90		
SM11--IN02	TIPKALO ENOPOLNO 16A 250V~ 1M IN 02	67	EM26--	TIPKALO UPRAVLJALNO 2M	92		
SM20--NT03	STIKALO DVOPOLNO 16AX 250V~ 1M NT 03	67	EM27	FILTER OMREŽNIH MOTENJ	92		
SM20--IN	STIKALO DVOPOLNO 16AX 250V~ 1M IN	67	EM25PPOL20	SET STIKALO / ZATEMNILNIK UNIVERZALNI RLC 0-300W 2M PP OL20	92		
SM40--NT10	STIKALO ŽALUZIJSKO 1-0-2 16AX 250V~ 1M NT 10	67	EM31--	IR STIKALO 5A 230V~ 1M	93		
SM41--NT10	TIPKALO ŽALUZIJSKO 1-0-2 16A 250V~ 1M NT 10	67	EM32--	IR STIKALO 5A 230V~ 2M	93		
SM60--	STIKALO MENJALNO 16AX 250V~ 1M	67	EM37--	TERMOSTAT OSNOVNI 6A 230V~ 2M	95		
SM61--	TIPKALO MENJALNO 16A 250V~ 1M	68	EM40--	KARTIČNO STIKALO OSNOVNO 3A 250V~ 3M	96		
SM62--CD	TIPKALO MENJALNO Z VRVICO 16A 250V~ 1M CD	68	EM47	KARTICA ISO	96		
SM70--	STIKALO KRIŽNO 16AX 250V~ 1M	68	EM44--	KARTIČNO STIKALO ZA VARČEVANJE Z ENERGIJO 3M	97		
TIPKE TM							
TM11--	TIPKA 1M	69	EM49	RELE ENOTA ZA KARTIČNO STIKALO 2x16A 250V~	97		
TM11--IN	TIPKA 1M IN	69	EM45	RAZDELILNIK SPL-1	97		
TM12--	TIPKA 2M	69	EM60--	VTIČNICA ZA BRIVNIK 2,5A 230V~ /15A 110V~ 3M	98		
TM12--IN	TIPKA 2M IN	69	EM65--	POLNILNIK USB 5V 1A 2M	98		
TM13--IL	TIPKA Z NAPISNO PLOŠČICO 2M	70	EM55	LED ZASILNA SVETILKA 250V~ 0,9W, NiMh 3h 7M	99		
TM15--	TIPKA 1M DVOPOLNA	70	EM50--	SVETILKA LED ENOBARVNA 230V~ 0,8W 2M	100		
TM21--	POLNILO 1M	70	EM51--	SVETILKA LED DVOBARVNA 230V~ 2x0,4W 2M	100		
TM22--	POLNILO 2M	70	EM52--	SVETILKA LED 3D DVOBARVNA 230V~ 2x0,4W 2M	100		
TM31--	UVODNICA 1M	70	EM70--	STIKALO NA PRSTNI OTDIS ARX1, 3A/12V 2M	101		
INDIKACIJA IA							
IA10--	TLIVKA 230V~ 0,34W	72	EM80--	STIKALO BREZDODIČNO 10A 240V~	102		
IA20--	SIJALKA LED 230V~ AC/DC 0,4W	72	EM81--	STIKALO BREZDODIČNO UPRAVLJALNO	102		
IA21--	SIJALKA LED 24V AC/DC 0,2W	72	EM90--	BRENČAČ 8VA 230V~ 1M	103		
IA22--	SIJALKA LED 12V AC/DC 0,10W	72	EM91--	BRENČAČ 8VA 12V 1M	103		
VTIČNICE VM							
VM10--	VTIČNICA SCHUKO+KS 2P+E 16A 250V~ 2M	74	EM92--	ZVONEC 8VA 230V~ 1M	103		
VM11--	VTIČNICA SCHUKO+KS +POKROV 2P+E 16A 250V~ 2M	74	EM93--	ZVONEC 8VA 12V 1M	103		
VM20--	VTIČNICA EURO+KS 2P 10A 250V~ 1M	75	EM95--	REGULATOR GLASNOSTI ZA 100V AVDIO LINIU 35W 2M	104		
VM40--	VTIČNICA FRANCOSKA+KS 2P+E 16A 250V~ 2M	75	EM96--	REGULATOR GLASNOSTI NIZKOHMSKI 4-8 Ω 35W 2M	104		
VM41--	VTIČNICA FRANCOSKA+KS +POKROV 2P+E 16A 250V~ 2M	75	SETI CM				
VM30--	VTIČNICA ITALIJANSKA P17/11+KS 2P+E 16A 250V~ 1M	75	CM10--	SET VTIČNIC 2x SCHUKO 2P+E 16A 250V~ 4M	105		
VM31--	VTIČNICA SCHUKO/ITA P17/11+KS 2P+E 16A 250V~ 2M	75	CM11--	SET VTIČNIC 3x SCHUKO 2P+E 16A 250V~ 7M	105		
VM32--	VTIČNICA SCHUKO/ITA P30+KS 2P+E 16A 250V~ 2M	76	CM15	SET VEZNIVOK BARVNI 3x1,5mm2 1M	106		
VM33--	VTIČNICA ITALIJANSKA P11+KS 2P+E 10A 250V~ 1M	76	CM16	SET VEZNIVOK BARVNI 3x2,5mm2 2M	106		
VM21--	VTIČNICA EURO/AMERIŠKA+KS 2P 16A 250V~ 1M	76	CM17	SET VIJAKOV 3,5x20	106		
VM51--	VTIČNICA BRITANSKA BS 546+KS 2P+E 15A 250V~ 2M	76	CM18	SET VIJAKOV 3,5x35	106		
VM52--	VTIČNICA BRITANSKA BS 1363+KS 2P+E 13A 250V~ 2M	76	CM19	SET VIJAKOV 3,5x50	106		
VM80	PRENAPETOSTNA ZAŠČITA MPE MINI 275V/50Hz	76	CM22--	SET ZA STIKALA IP44 2M	106		
KOMUNIKACIJE KM							
KM10--	VTIČNICA TV OSNOVNA 0dB 1M	78	CM23--	SET ZA VTIČNICE IP44 2M	106		
KM20--	VTIČNICA TV OSNOVNA 0dB 2M	78	CM25--OL	SET KOPALNIŠKI 3x20A 250V~ 4M OL	106		
KM11--	VTIČNICA TV KONČNA 1dB 1M	78	CM25--OS	SET KOPALNIŠKI 3x20A 250V~ 4M OS	106		
KM12--	VTIČNICA TV PREHODNA 10dB 1M	78	NM41	NOSILEC KOPALNIŠKI SET 4M	107		
KM15--	VTIČNICA SAT OSNOVNA 0dB 1M	79	OL41--	OKVIR LINE KOPALNIŠKI SET	107		
KM24--	VTIČNICA SAT OSNOVNA 0dB 2M	79	OS41--	OKVIR SOFT KOPALNIŠKI SET	107		
KM16--	VTIČNICA SAT KONČNA 1dB 1M	79	ANTIBAKTERIJSKI PROGRAM AW				
KM19--	VTIČNICA R OSNOVNA 0dB 1M	79	TM11AW	TIPKA 1M	109		
KM29--	VTIČNICA R OSNOVNA 0dB 2M	79	TM11AWIN	TIPKA 1M IN	109		
KM25--	VTIČNICA SAT-TV KONČNA 1dB 2M	79	TM12AW	TIPKA 2M	109		
KM22--	VTIČNICA AUDIO 2xRCA 1M	80	TM12AWIN	TIPKA 2M IN	109		
KM23--	VTIČNICA AUDIO ZVOČNIŠKA 1M	80	TM21AW	POLNILO 1M	109		
KM26--	VTIČNICA AUDIO ZVOČNIŠKA 2M	80	TM22AW	POLNILO 2M	109		
KM30--	VTIČNICA TEL LT RJ11 6/4 1M	81	VM10AW	VTIČNICA SCHUKO+KS 2P+E 16A 250V~ 2M	110		
KM31--	VTIČNICA TEL BT SEC 6/6 1M	81	VM11AW	VTIČNICA SCHUKO+KS +POKROV 2P+E 16A 250V~ 2M	110		
KM36--	VTIČNICA TEL KS RJ11 6/4 1M	81	VM20AW	VTIČNICA EURO+KS 2P 10A 250V~ 1M	110		
KM37--	VTIČNICA CAT5e KS RJ45 8/8 1M	81	KM11AW	VTIČNICA TV KONČNA 1dB 1M	110		
KM35--	ADAPTER KS 1M	81	KM35AW	ADAPTER KS 1M	110		
KM38--	ADAPTER KS S PRAŠNO ZAŠČITO 1M	81	OS20AW	OKVIR SOFT 2M	111		
KM39--	VTIČNICA CAT6 SCH KS RJ45 8/8 1M	82	OS24AW	OKVIR SOFT 2x2M	111		
KM50--	ADAPTER KS UNIVERZALNI 1M	82	OS26AW	OKVIR SOFT 3x2M	111		
KM40--	ADAPTER PD 1M	82	OS30AW	OKVIR SOFT 3M	111		
KM43--	ADAPTER PD S PRAŠNO ZAŠČITO 1M	82	OS40AW	OKVIR SOFT 4M	111		
KM46--	ADAPTER R&M 1M	82	OS70AW	OKVIR SOFT 7M	111		
KM47--	ADAPTER R&M S PRAŠNO ZAŠČITO 1M	82	OKVIRJI PURE OP				
KM45--	ADAPTER LK 1M	83	OP20--	OKVIR PURE 2M	114		
KA26	ADAPTER NEXANS SCRACK 2M	83	OP24--	OKVIR PURE 2x2M	114		
KM48--	ADAPTER AT&T SYSTIMAX S PRAŠNO ZAŠČITO 1M	83	OP26--	OKVIR PURE 3x2M	114		
KM51--	VTIČNICA USB TIP A 1M	83	OP30--	OKVIR PURE 3M	115		
			OP40--	OKVIR PURE 4M	115		
			OP70--	OKVIR PURE 7M	115		
			OP13--	OKVIR PURE 1/3M	115		
			OP23--	OKVIR PURE 2/3M	115		

INDEX

šifra	opis izdelka	stran
OKVIRJI LINE OL		
OL20--	OKVIR LINE 2M	118
OL24--	OKVIR LINE 2x2M	118
OL26--	OKVIR LINE 3x2M	118
OL28--	OKVIR LINE 4x2M	118
OL30--	OKVIR LINE 3M	119
OL40--	OKVIR LINE 4M	119
OL70--	OKVIR LINE 7M	119
OL10--	OKVIR LINE 1/2M	119
OL13--	OKVIR LINE 1/3M	119
OL23--	OKVIR LINE 2/3M	119
OKVIRJI SOFT OS		
OS20--	OKVIR SOFT 2M	122
OS24--	OKVIR SOFT 2x2M	122
OS26--	OKVIR SOFT 3x2M	122
OS28--	OKVIR SOFT 4x2M	122
OS30--	OKVIR SOFT 3M	123
OS40--	OKVIR SOFT 4M	123
OS70--	OKVIR SOFT 7M	123
OS72--	OKVIR SOFT 2x7M	123
OS10--	OKVIR SOFT 1/2M	123
OS13--	OKVIR SOFT 1/3M	123
OS23--	OKVIR SOFT 2/3M	123
NOSILCI NM		
NM20	NOSILEC S KREMPELJCI 2M	128
NM21	NOSILEC BREZ VIJAKOV 2M	128
NM24	NOSILEC KOVINSKI S KREMPELJCI 2M	128
NM25	NOSILEC KOVINSKI BREZ VIJAKOV 2M	128
NM30	NOSILEC Z VIJAKI 3M	129
NM40	NOSILEC Z VIJAKI 4M	129
NM70	NOSILEC Z VIJAKI 7M	129
NM72	NOSILEC Z VIJAKI 2x7M	129
NM10	NOSILEC S KREMPELJCI 1/2M	130
NM11	NOSILEC BREZ VIJAKOV 1/2M	130
NM23	NOSILEC S KREMPELJCI 2/3M	130
NM32	NOSILEC Z VIJAKI 2/3M	130
D O Z E		
šifra	opis izdelka	stran
OKROGLE DOZE		
DE10	DOZA OKROGLA PLITKA ZA ZID SM60-01	134
DE11	DOZA OKROGLA GLOBOKA ZA ZID SM60-06	134
DE30	VEZNI ČLEN DOZE ZA ZID SM60-03	134
DE31	VEZNI ČLEN DOZE ZA ZID SM60-04	134
DE12	DOZA OKROGLA ZA ZID 65-46	135
DE13	DOZA OKROGLA ZA ZID 65-60	135
DE14	PODALJSÉK DOZE ZA ZID 65-46	135
DE32	VEZNI ČLEN DOZE ZA ZID 65-71	135
DE33	VEZNI ČLEN DOZE ZA ZID 65-91	135
DE20	POKROV DOZE ZAŠČITNI 60	135
DE21	POKROV DOZE ZAŠČITNI 65	135
DE22	POKROV DOZE DEKORATIVNI SM60	135
HE10	DOZA OKROGLA ZA VOTLE STENE SM68x40	138
HE11	DOZA OKROGLA ZA VOTLE STENE SM68x55	138
BE10	DOZA OKROGLA ZA BETON 60-49	138
BE11	DOZA OKROGLA ZA BETON 60-77	138
BE20	NOSILEC DOZE ZA BETON	138
BE21	UVODNICA DOZE ZA BETON 16	138
PRAVOKOTNE DOZE		
DM30	DOZA PRAVOKOTNA ZA ZID PM3	142
DM31	DOZA PRAVOKOTNA ZA ZID PM3-65	142
DM40	DOZA PRAVOKOTNA ZA ZID PM4	142
DM41	DOZA PRAVOKOTNA ZA ZID PM4-65	142
DM70	DOZA PRAVOKOTNA ZA ZID PM7	143
DM71	DOZA PRAVOKOTNA ZA ZID PM7-65	143
DM72	DOZA PRAVOKOTNA ZA ZID PM72-65	143
DM80	VEZNI ČLEN DOZE PM	143
DM33	POKROV DOZE ZAŠČITNI PM3	144
DM34	POKROV DOZE DEKORATIVNI PM3	144
DM43	POKROV DOZE ZAŠČITNI PM4	144
DM44	POKROV DOZE DEKORATIVNI PM4	144
DM73	POKROV DOZE ZAŠČITNI PM7	144
DM74	POKROV DOZE DEKORATIVNI PM7	144
DM75	POKROV DOZE DEKORATIVNI PM72	145
HM30	DOZA PRAVOKOTNA ZA VOTLE STENE VM3	146
HM40	DOZA PRAVOKOTNA ZA VOTLE STENE VM4	146
HM70	DOZA PRAVOKOTNA ZA VOTLE STENE VM7	146
HM72	DOZA PRAVOKOTNA ZA VOTLE STENE VM72	146
BM30	DOZA PRAVOKOTNA ZA BETON BM3	147
BM40	DOZA PRAVOKOTNA ZA BETON BM4	147
BM70	DOZA PRAVOKOTNA ZA BETON BM7	147
BM80	PRITRDILNI ČLEN ZA DOZE BM	147
BM82	DISTANČNI PROFIL ZA DOZE	147

šifra	opis izdelka	stran
RAZVODNE DOZE		
DW10	RAZVODNA DOZA OKROGLA ZA ZID DSM78	150
HW10	RAZVODNA DOZA OKROGLA ZA VOTLE STENE SM78x45	150
DE23	POKROV DOZE DEKORATIVNI SM78	150
DE24	POKROV DOZE ZAŠČITNI 78	150
HW20	RAZVODNA DOZA KVADRATNA ZA ZID SM105x105	150
PRIBOR ZA OŽIČENJE		
UW10--	SPOANKA ENOREDNA PA 2x2.5mm2 12P	152
UW11--	SPOANKA ENOREDNA PA 2x4mm2 12P	152
UW12--	SPOANKA ENOREDNA PA 2x6mm2 12P	152
UW15--	SPOANKA ENOREDNA ZAPRTA PC 2x2.5mm2 10P	152
UW16--	SPOANKA ENOREDNA ZAPRTA PC 2x4mm2 10P	152
UW17--	SPOANKA ENOREDNA ZAPRTA PC 2x6mm2 10P	152
UW29--	SPOANKA DVOREDNA PA 1.5mm2 12P	152
UW30--	SPOANKA DVOREDNA PA 2.5mm2 12P	152
UW31--	SPOANKA DVOREDNA PA 4-6mm2 12P	152
UW32--	SPOANKA DVOREDNA PA 10mm2 12P	152
UW40--	SPOANKA BREZVIJAČNA PA 1.5mm2 3P	153
UW41--	SPOANKA BREZVIJAČNA PA 1.5mm2 5P	153
UW42--	SPOANKA BREZVIJAČNA PA 1.5mm2 8P	153
UW45--	SPOANKA BREZVIJAČNA PA 2.5mm2 3P	153
UW46--	SPOANKA BREZVIJAČNA PA 2.5mm2 4P	153
UW47--	SPOANKA BREZVIJAČNA PA 2.5mm2 5P	153
UW50--	SPOANKA BREZVIJAČNA PA 2.5mm2 2/1P	153
distribucija —		
šifra	opis izdelka	stran
OHIŠJA CUBO IP20 AC		
AC11--	OHIŠJE NO CUBO Z DNOM IP20 1M	156
AC21--	OHIŠJE NO CUBO Z DNOM IP20 2M	156
AC41--	OHIŠJE NO CUBO Z DNOM IP20 4M	156
AC61--	OHIŠJE NO CUBO Z DNOM IP20 6M	156
OHIŠJA CUBO IP55 AQ		
AQ20--	OHIŠJE NO CUBO IP55 2M	157
AQ22--	OHIŠJE NO CUBO IP55 2x2M	157
AQ30--	OHIŠJE NO CUBO IP55 3M	157
AQ31--	OHIŠJE PO CUBO IP55 3M	157
PARAPETNI KANALI ALUMINIJSKI MA		
RT10	ADAPTER MA 92	158
RT12--	OKVIR MA 92 2/3M	158
RT14--	OKVIR MA 92 4M	158
RT17--	OKVIR MA 92 7M	158
RT20--	OSNOVA KANALA MA 130x65	159
RT21--	OSNOVA KANALA MA 165x65	159
RT25--	POKROV KANALA MA 92	159
RT30	PREGRADA MA 43	159
RT31	PREGRADA AL. MA 43	159
RT32	PREGRADA AL. MA DVOJNA 43	159
RT35--	KONČNI ELEMENT MA 130x65	160
RT36--	KONČNI ELEMENT MA 165x65	160
RT38	RAVNII VEZNI ELEMENT MA 65	160
RT40--	UNIVERZALNI KOT MA 130x65	160
RT41--	UNIVERZALNI KOT MA 165x65	160
RT42	OZEMLJITVENA SPOANKA MA 2x A6.3	160
RT43--	L KOTNI ELEMENT MA 130x65	161
RT44--	L KOTNI ELEMENT MA 165x65	161
RT45--	T ELEMENT MA 130x65	161
RT46--	T ELEMENT MA 165x65	161
RT50--	NOSILEC STEBRIČKA MA ENOJNI 130x65	162
RT51--	NOSILEC STEBRIČKA MA DVOJNI 2x130x65	162
RT52--	STEBRIČEK MA 130x65x500	162
RT53--	STEBRIČEK MA DVOJNI 2x130x65x500	162
TALNE DOZE MT		
RB30	TALNA DOZA MT 7 H=53mm	164
RB40	TALNA DOZA MT 7 H=88mm	164
RB31	PODSTAVEK TALNE DOZE MT 7 H=53mm	164
RB41	PODSTAVEK TALNE DOZE MT 7 H=88mm	164
RB33	TALNA DOZA MT 14 H=53mm	164
RB43	TALNA DOZA MT 14 H=88mm	164
RB34	PODSTAVEK TALNE DOZE MT 14 H=53mm	165
RB44	PODSTAVEK TALNE DOZE MT 14 H=88mm	165
RB36	TALNA DOZA MT 21 H=53mm	165
RB46	TALNA DOZA MT 21 H=88mm	165
RB37	PODSTAVEK TALNE DOZE MT 21 H=53mm	165
RB47	PODSTAVEK TALNE DOZE MT 21 H=88mm	165
RAZVODNE OMARICE MO		
RB10	ADAPTER ZA DIN LETEV 35mm 1M	166
RB11	ADAPTER ZA DIN LETEV 35mm 2M	166
RB20	RAZVODNA OMARICA MO 12+2	167
RB21	RAZVODNA OMARICA MO 24+4	167
RB22	RAZVODNA OMARICA MO 36+6	167
RB23	RAZVODNA OMARICA MO 48+8	167

ekonomik

šifra	opis izdelka	stran
STIKALA SE		
SE10	STIKALO ENOPOLNO 10AX 250V~	180
SE11	TIPKALO ENOPOLNO 10A 250V~	180
SE22	STIKALO DVOPOLNO 16AX 250V~	180
SE50	STIKALO SERIJSKO 10AX 250V~	180
SE51	TIPKALO SERIJSKO 10A 250V~	181
SE52	STIKALO ŽALUŽIJSKO 10AX 250V~	181
SE53	TIPKALO ŽALUŽIJSKO 10A 250V~	181
SE60	STIKALO MENJALNO 10AX 250V~	181
SE63	STIKALO DVOJNO MENJALNO 10AX 250V~	181
SE70	STIKALO KRIŽNO 10AX 250V~	181
SE10--	STIKALO ENOPOLNO 10AX 250V~	182
SE10--IN	STIKALO ENOPOLNO 10AX 250V~ IN	182
SE11--	TIPKALO ENOPOLNO 10A 250V~	182
SE11--TI50	TIPKALO ENOPOLNO 10A 250V~ TI 50	182
SE11--TI51	TIPKALO ENOPOLNO 10A 250V~ TI 51	182
SE11--IL	TIPKALO ENOPOLNO 10A 250V~ IL	182
SE22--IN03	STIKALO DVOPOLNO 16AX 250V~ IN 03	182
SE50--	STIKALO SERIJSKO 10AX 250V~	183
SE51--	TIPKALO SERIJSKO 10A 250V~	183
SE52--NT09	STIKALO ŽALUŽIJSKO 10AX 250V~ NT 09	183
SE53--NT09	TIPKALO ŽALUŽIJSKO 10A 250V~ NT 09	183
SE60--	STIKALO MENJALNO 10AX 250V~	183
SE63--	STIKALO DVOJNO MENJALNO 10AX 250V~	183
SE70--	STIKALO KRIŽNO 10AX 250V~	183
TIPKE TE		
TE10--	TIPKA NAVADNA	184
TE10--IN	TIPKA NAVADNA IN	184
TE13--IL	TIPKA Z NAPISNO PLOŠČICO IL	184
TE11--	TIPKA SERIJSKA	184
INDIKACIJA IA		
IA10--	TLIVKA 230V~ 0,34W	185
IA20--	SIJALKA LED 230V~ AC/DC 0,4W	185
IA21--	SIJALKA LED 24V AC/DC 0,2W	185
IA22--	SIJALKA LED 12V AC/DC 0,1W	185
VTIČNICE VE		
VE10--XO	VTIČNICA SCHUKO 2P+E 16A 250V~ XO	188
VE11--XO	VTIČNICA SCHUKO+POKROV 2P+E 16A 250V~ XO	188
VE12--XO	VTIČNICA SCHUKO 2P+E 16A 250V~ BV XO	188
VE13--XO	VTIČNICA SCHUKO+POKROV 2P+E 16A 250V~ BV XO	188
VE10--	VTIČNICA SCHUKO 2P+E 16A 250V~	188
VE11--	VTIČNICA SCHUKO+POKROV 2P+E 16A 250V~	188
VE12--	VTIČNICA SCHUKO 2P+E 16A 250V~ BV	188
VE13--	VTIČNICA SCHUKO+POKROV 2P+E 16A 250V~ BV	188
VE40--XO	VTIČNICA FRANCOSKA 2P+E 16A 250V~ XO	189
VE41--XO	VTIČNICA FRANCOSKA+POKROV 2P+E 16A 250V~ XO	189
VE42--XO	VTIČNICA FRANCOSKA 2P+E 16A 250V~ BV XO	189
VE43--XO	VTIČNICA FRANCOSKA+POKROV 2P+E 16A 250V~ BV XO	189
VE40--	VTIČNICA FRANCOSKA 2P+E 16A 250V~	189
VE41--	VTIČNICA FRANCOSKA+POKROV 2P+E 16A 250V~	189
VE42--	VTIČNICA FRANCOSKA 2P+E 16A 250V~ BV	189
VE43--	VTIČNICA FRANCOSKA+POKROV 2P+E 16A 250V~ BV	189
VE16--	VTIČNICA SCHUKO DVOJNA 2P+E 16A 250V~	190
VE46--	VTIČNICA FRANCOSKA DVOJNA 2P+E 16A 250V~	190
VE30--	VTIČNICA 2P 16A 250V~	190
KOMUNIKACIJE KE		
KE11	VTIČNICA TV-R KONČNA 2dB	191
KE12	VTIČNICA TV-R PREHODNA 8,5dB	191
KE16	VTIČNICA SAT-TV-R KONČNA 3dB	191
KE36	VTIČNICA TEL KS RJ11 6/4	191
KE37	VTIČNICA CAT5e KS RJ45 8/8	192
KE38	VTIČNICA TEL KS DVOJNA 2x RJ11 6/4	192
KE39	VTIČNICA CAT5e KS DVOJNA 2x RJ45 8/8	192
KE45	ADAPTER KS	192
KE46	ADAPTER KS DVOJNI	192
KE47	ADAPTER PD DVOJNI	192
KE10--	VTIČNICA TV OSNOVNA 0dB	193
KE11--	VTIČNICA TV-R KONČNA 2dB	193
KE12--	VTIČNICA TV-R PREHODNA 8,5dB	193
KE16--	VTIČNICA SAT-TV-R KONČNA 3dB	193
KE22--	VTIČNICA AUDIO 2xRCA	193
KE23--	VTIČNICA AVDIO ZVOČNIŠKA	193
KE36--	VTIČNICA TEL KS RJ11 6/4	194
KE37--	VTIČNICA CAT5e KS RJ45 8/8	194
KE38--	VTIČNICA TEL KS DVOJNA 2x RJ11 6/4	194
KE39--	VTIČNICA CAT5e KS DVOJNA 2x RJ45 8/8	194
KE35--	VTIČNICA TEL LT RJ11 6/4	194
POKROVI PA		
PE10--	POKROV TV-R 2P/3P	195
PE20--	POKROV KS ENOJNI	195
PE21--	POKROV KS/PD DVOJNI	195
PE30--	POKROV TAE/TDO	195
PE32--	POKROV IR STIKALO	195

šifra	opis izdelka	stran
ELEKTRONIKA EE		
EE15	ZATEMNILNIK ROTACIJSKI MEN RL 400W	196
EE16	ZATEMNILNIK ROTACIJSKI MEN RLC 400W	196
EE17	ZATEMNILNIK ROTACIJSKI FAN 600VA	197
EE19	ZATEMNILNIK ROTACIJSKI MEN LED 100W	197
EE15--	ZATEMNILNIK ROTACIJSKI MEN RL 400W	197
EE16--	ZATEMNILNIK ROTACIJSKI MEN RLC 400W	197
EE19--	ZATEMNILNIK ROTACIJSKI MEN LED 100W	198
EE32--	IR STIKALO 5A 230V~	198
POKROVI ELEKTRONIKE PE		
PE41--	POKROV ZATEMNILNO STIKALO 06	200
PRIBOR AE		
AE10--	POLNITO	201
AE20--	PRIKLJUČEK PETPOLNI STALNI 3P+N+E 5x4mm2	201
AE30--	OHIŠJE NO 1	201
AE50--	ŠČITNIK STENSKI	202
AE51--	OTROŠKA ZAŠČITA	202
OKVIRJI OE		
OE10--	OKVIR EKONOMIK 1	203
OE20--	OKVIR EKONOMIK 2 HORIZONTALNI	203
OE21--	OKVIR EKONOMIK 2 VERTIKALNI	203
OE30--	OKVIR EKONOMIK 3 HORIZONTALNI	203
OE31--	OKVIR EKONOMIK 3 VERTIKALNI	204
OE40--	OKVIR EKONOMIK 4 HORIZONTALNI	204
OE41--	OKVIR EKONOMIK 4 VERTIKALNI	204
OE90--	OKVIRČEK EKONOMIK DEKORATIVNI	204

šifra	opis izdelka	stran
fontana		
STIKALA SF		
SF10--	STIKALO ENOPOLNO IP44 10AX 250V~	208
SF10-TI	STIKALO ENOPOLNO IP44 10AX 250V~ TI	208
SF11-TI	TIPKALO ENOPOLNO IP44 10A 250V~ TI	208
SF20--	STIKALO DVOPOLNO IP44 10AX 250V~	208
SF50--	STIKALO SERIJSKO IP44 10A 250V~	209
SF51--	TIPKALO SERIJSKO IP44 10A 250V~	209
SF60--	STIKALO MENJALNO IP44 10AX 250V~	209
SF60-TI	STIKALO MENJALNO IP44 10AX 250V~ TI	209
SF63--	STIKALO DVOJNO MENJALNO 10A 250V~	209
SF70--	STIKALO KRIŽNO IP44 10AX 250V~	209
VTIČNICE VF		
VF10--	VTIČNICA SCHUKO+POKROV IP44 2P+E 16A 250V~	210
VF12--	VTIČNICA SCHUKO+POKROV IP44 2P+E 16A 250V~ BV	210
SETI CF		
CF10--	SET VTIČNICA SCHUKO DVOJNA HORIZ IP44 2x2P+E 16A 250V~	211
CF11--	SET VTIČNICA SCHUKO DVOJNA VERT IP44 2x2P+E 16A 250V~	211
CF12--	SET VTIČNICA SCHUKO DVOJNA VERT IP44 2x2P+E 16A + 10AX 250V~	211
CF13--	SET VTIČNICA SCHUKO DVOJNA VERT IP44 16A + 10AX 250V~	212
CF14--	SET VTIČNICA SCHUKO DVOJNA VERT IP44 2x2P+E 16A 250V~BV	212
CF15--	SET VTIČNICA SCHUKO DVOJNA VERT IP44 2x2P+E 16A 250V~BV	212
CF16--	SET VTIČNICA SCHUKO DVOJNA VERT IP44 16A + 10AX 250V~BV	212
CF17--	SET VTIČNICA SCHUKO DVOJNA VERT IP44 16A + 10AX 250V~BV	212
PRIBOR AF		
AF10--	RAZVODNICA IP44 RN01	213
AF20--	RAZVODNICA IP55 ND01	213

šifra	opis izdelka	stran
VTIČNICE		
VE10--XO	VTIČNICA SCHUKO 2P+E 16A 250V~ XO	188
VE11--XO	VTIČNICA SCHUKO+POKROV 2P+E 16A 250V~ XO	188
VE12--XO	VTIČNICA SCHUKO 2P+E 16A 250V~ BV XO	188
VE13--XO	VTIČNICA SCHUKO+POKROV 2P+E 16A 250V~ BV XO	188
VE10--	VTIČNICA SCHUKO 2P+E 16A 250V~	188
VE11--	VTIČNICA SCHUKO+POKROV 2P+E 16A 250V~	188
VE12--	VTIČNICA SCHUKO 2P+E 16A 250V~ BV	188
VE13--	VTIČNICA SCHUKO+POKROV 2P+E 16A 250V~ BV	188
VE40--XO	VTIČNICA FRANCOSKA 2P+E 16A 250V~ XO	189
VE41--XO	VTIČNICA FRANCOSKA+POKROV 2P+E 16A 250V~ XO	189
VE42--XO	VTIČNICA FRANCOSKA 2P+E 16A 250V~ BV XO	189
VE43--XO	VTIČNICA FRANCOSKA+POKROV 2P+E 16A 250V~ BV XO	189
VE40--	VTIČNICA FRANCOSKA 2P+E 16A 250V~	189
VE41--	VTIČNICA FRANCOSKA+POKROV 2P+E 16A 250V~	189
VE42--	VTIČNICA FRANCOSKA 2P+E 16A 250V~ BV	189
VE43--	VTIČNICA FRANCOSKA+POKROV 2P+E 16A 250V~ BV	189
VE16--	VTIČNICA SCHUKO DVOJNA 2P+E 16A 250V~	190
VE46--	VTIČNICA FRANCOSKA DVOJNA 2P+E 16A 250V~	190
VE30--	VTIČNICA 2P 16A 250V~	190
KOMUNIKACIJE KE		
KE11	VTIČNICA TV-R KONČNA 2dB	191
KE12	VTIČNICA TV-R PREHODNA 8,5dB	191
KE16	VTIČNICA SAT-TV-R KONČNA 3dB	191
KE36	VTIČNICA TEL KS RJ11 6/4	191
KE37	VTIČNICA CAT5e KS RJ45 8/8	192
KE38	VTIČNICA TEL KS DVOJNA 2x RJ11 6/4	192
KE39	VTIČNICA CAT5e KS DVOJNA 2x RJ45 8/8	192
KE45	ADAPTER KS	192
KE46	ADAPTER KS DVOJNI	192
KE47	ADAPTER PD DVOJNI	192
KE10--	VTIČNICA TV OSNOVNA 0dB	193
KE11--	VTIČNICA TV-R KONČNA 2dB	193
KE12--	VTIČNICA TV-R PREHODNA 8,5dB	193
KE16--	VTIČNICA SAT-TV-R KONČNA 3dB	193
KE22--	VTIČNICA AUDIO 2xRCA	193
KE23--	VTIČNICA AVDIO ZVOČNIŠKA	193
KE36--	VTIČNICA TEL KS RJ11 6/4	194
KE37--	VTIČNICA CAT5e KS RJ45 8/8	194
KE38--	VTIČNICA TEL KS DVOJNA 2x RJ11 6/4	194
KE39--	VTIČNICA CAT5e KS DVOJNA 2x RJ45 8/8	194
KE35--	VTIČNICA TEL LT RJ11 6/4	194
POKROVI PA		
PE10--	POKROV TV-R 2P/3P	195
PE20--	POKROV KS ENOJNI	195
PE21--	POKROV KS/PD DVOJNI	195
PE30--	POKROV TAE/TDO	195
PE32--	POKROV IR STIKALO	195





MODUL

— funkcijski elementi
function elements



64

dizajn
design

PURE
—
line
soft



114

doze
boxes



136

distribucija
distribution



158

Ekonomik —

fontana


—



180




208





TEM

TEM ČATEŽ d.d.
Čatež 13, 8212 VELIKA LOKA
SLOVENIJA
tem@tem.si
www.tem.si
T +386(0)7 348 99 00
F +386(0)7 348 99 99



www.tem.si

SLO
2018/2019